INCH-POUND

MIL-T-21869/63A
01 DECEMBER 1989
SUPERSEDING
MIL-T-21869/63
13 January 1984

MILITARY SPECIFICATION SHEET

TRUCK, LIFT, FORK, ELECTRIC, SOLID TIRES, 6,000 POUND (2720 KILOGRAMS) CAPACITY, 144 INCH (3660 MILLIMETERS) LIFT, ASHORE ORDNANCE HANDLING, TYPE EX

The complete requirements for procuring the truck described herein shall consist of this document and specification MIL-T-21869, Trucks, Lift, Fork, Electric, Sit-Down, Front Wheel Drive, Rear Wheel Steer, General Specification For.

REQUIREMENTS

1.	Capacity	6,000 Lbs. (2720 Kg.) at 24 inches (610 mm) load center
2.	Collapsed mast height	91 inches (2310 mm) (maximum)
3.	Fork height	144 inches (3660 mm) (minimum)
4.	Free lift height	60 inches (1520 mm) (minimum)
5.	Fork size	2.5 in. (50 mm) thick (maximum) 6.5 in. (160 mm) wide (maximum) 40 in. (1020 mm) long +0in. (0 mm) -1/2 in. (12 mm)
6.	Fork spacing (measured between outer edges of forks):	40 inch (1020 mm) spread (minimum) 14 inches (360 mm) together (maximum)
7.	Static overhead guard test load	11,000 Lbs.(5000 Kg.)
8.	Overhead guard height	91 inches (2310 mm) (maximum)
9.	Tangential steering force at rim of hand wheel	150 Lbs.(670 N) for nonpower and 25 Lbs.(110 N) for power steering
10.	Right angle turn, dimension "A" (add 4 inches (100 mm) when side shifter attachment is used)	156 inches(3960 mm)
11.	Lifting speed	30 feet (9 m) per minute (minimum)
12.	Lowering speed	60 feet (18 m) per minute (minimum)
13.	High drive speed	7.5 mph (12 kph) (maximum)/4.5 mph (7kph) (minimum)
14.	Slope ascension	15 percent slope (8.5 degrees)
15.	Longitudinal stability - stacking	6 percent slope (3.4 degrees)
	traveling	26.8 percent slope (15 degrees)
16.	Lateral stability - stacking	9 percent slope (5.5 degrees)
	traveling	40 percent slope (22.9 degrees)
17.	Service Brakes	4 wheels
18.	Parking Brakes	Hand brake required

FSC 3930

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:39Z
Check the source to verify that this is the current version before use.

19. Mast Tilt - Forward 3 degrees +/- 0.5 degree
- Rearward 5 degrees +/- 0.5 degree

20. Battery well is required. Dimensions shall be determined from MIL-T-21869 and MS 16974.

Custodians:

Navy - SA

Review Activities:

Navy - OS

Preparing Activity:

Navy - SA

Project No.

3930-0644-13

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:39Z
Check the source to verify that this is the current version before use.