INTERIM FEDERAL SPECIFICATION

LINE GUIDE, LETTERING, ADJUSTABLE

This Interim Federal Specification was developed by the General Services Administration, Federal Supply Service, Washington, D. C. 20407, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

1. SCOPE

1.1 Scope. This specification covers plastic adjustable lettering instruments, for use in constructing uniformally spaced guide and slant lines, for lettering in general drafting practice. These instruments will hereafter be referred to in this specification as Line Guides. This specification covers one type of Line Guide, Lettering, Adjustable (See 6.1).

2. APPLICABLE SPECIFICATIONS, STANDARDS, AND OTHER PUBLICATIONS

2.1 Specifications and standards. The following specifications and standards, of the issues in effect on date of invitation for bids, form a part of this specification.

Federal Specifications:

UU-P-553 - Paper, Wrapping, Tissue
PPP-B-566 - Boxes, Folding, Paperboard
PPP-B-636 - Box, Fiberboard
PPP-B-665 - Boxes; Paperboard, Metal, Stayed (Including Stay Material)
PPP-B-676 - Boxes, Set-up, Paperboard

Federal Standards:

Fed. Std. No. 102 - Preservation, Packaging, and Packing Levels
Fed. Std. No. 123 - Marking for Domestic Shipment (Civil Agencies)

(FOR INSTRUCTIONS ON OBTAINING COPIES OF FEDERAL SPECIFICATIONS AND STANDARDS, SEE LAST PAGE)

Military Specifications:

Mil-P-116 - Preservation, Methods of

Military Standards:

Mil-Std. - 105, Sampling, Procedures and Tables for Inspection by Attributes.
Mil-Std. - 129, Marking for Shipment and Storage

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

2.2 Other publications. There are no other publications applicable to this specification.

3. REQUIREMENTS

3.1 Material. Line Guides shall be manufactured from clear transparent acrylic, or vinylchloride plastic.

3.2 Design. The line guide shall consist of a plastic frame and a plastic disc which, when inserted into the frame permits 360 degree rotation of the disc. The finished line guide shall be essentially flat, with a perimeter approximately the shape of a trapezoid.

3.2.1 Frame. The outer edges of the line guide frame shall form angles with the base of the frame to permit the edges of the line guide frame to be used for drawing 68 degree and 75 degree slant lines for slant lettering when the line guide is placed flat on the drawing medium. The line guide frame shall have the 68 degree slant on its right edge when facing the line guide. The 75 degree slant shall be on the left edge when facing the line guide. The inside of the line guide frame shall form a receptacle to hold the disc in such a manner as to permit the disc to rotate 360 degrees smoothly and without loss motion or play.

FSC 6675

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:50Z
Check the source to verify that this is the currentversion before use.

3.2.2 Disc. The disc shall have not less than 31 guide line holes arranged in three columns. The first column of holes when facing the line guide disc shall be marked with the fraction 2/3, the center column of holes shall be marked with the number 10, and the right column shall be marked with the fraction 3/5, to represent the ratio of the space between the guide line to the total height of the letter to be drawn. The columns of guide line holes shall be grouped, for adjustment in height to facilitate drawing lettering guide lines of all heights within the range of 1/16 inch minimum to 1-1/2 inch maximum. All guide line holes shall be tapered, and of suitable diameter to permit the point of a drawing pencil to penetrate through, for marking the guide lines. The disc shall be graduated and indexed in numbers representing the number of thirty seconds of an inch in height of the guide line selected.

3.2.3. Graduations, index marks and numbers. All graduations, index marks and numbers shall be indented, molded, etched or otherwise permanently marked on the item.

3.3 Dimensions. The line guide shall be 3-3/4 inches long at the base; 1/8 inch plus or minus tolerance will be permitted in length dimension. The line guide shall be 2-3/8 inches high, plus or minus 1/8 inch tolerance. The line guide shall be 1/8 inch thick, plus or minus 1/64 inch tolerance.

3.4 Finish. All surfaces shall be smooth and polished. All edges shall be smooth, straight and free from burrs.

3.5 Workmanship. Workmanship shall be in accordance with standard commercial practice for this type instrument. The finished line guide shall be free from any defects which affect the appearance or which might impair the serviceability or use of the item.

3.6 Identification marking. The name or trademark of the manufacturer shall be stamped or otherwise permanently marked on the face of the line guide.

4. SAMPLING, INSPECTION AND TEST PROCEDURES

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Sampling. Sampling shall be in accordance with MIL-STD-105.

4.3 Inspection. Samples selected in accordance with 4.2 shall be inspected for the following defects. Lot acceptance or rejection shall be based on an Acceptable Quality Level (AQL) of 2.5 percent defective for major defects and 4.0 defects for minor defects.

Classification of defects:

Major

(a) Design not as specified

(b) Material not as specified

(c) Line Guide twisted and does not lie flat

(d) Edges not straight, contains nicks or burrs

(e) Angles of sides not as specified

(f) Index and graduation marks and numbers or hole numbers not as specified

(g) Holes not spaced or shaped as specified

(h) Disc does not work properly

Minor

(a) Nicks, chips, burrs or scratches on surface of line guides (other than working edges).

(b) Identification marking not as specified

(c) Size not as specified

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:50Z
Check the source to verify that this is the current version before use.

4.4 Test. Visual examination shall be made to determine if major defects 4.3 (a), (b), (c), (d) and (f) are applicable. Test for defect (e) shall be determined by comparison with an accurate 68 degree and 75 degree predetermined angle. Test for defect (g) shall be made by inserting a sharpened drawing pencil into each of the holes to be tested. Test for defect (h) shall be made by hand adjustment of the disc.

4.5 Examination of preparation for delivery. An examination shall be made to determine that packaging, packing and marking requirements as required by section 5 of this specification are complied with. Defects shall be scored in accordance with Table I. For examination of contents the sample unit shall be one shipping container fully prepared for delivery selected just prior to the closing operations. Defects of closure listed shall be examined on shipping container fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the AQL shall be 6.0 defects per hundred units.

TABLE I - Classification of Preparation for Delivery Defects

Examine	
Markings (exterior and interior containers)	Omitted; Incorrect; illegible; of improper size, location, sequence or method of application.
Materials	Any component missing or damaged.
Workmanship	Inadequate application of components such as: Incomplete closure of container, loose strapping, bulging or distortion of containers.
Packaging and Packing	Packages improperly sealed. Shipping containers not waterproofed. Contents more or less than specified. Shipping containers not tape reinforced.

5. PREPARATION FOR DELIVERY

(For civil agency procurement the definitions and applications of the levels of packaging and packing shall be in accordance with Fed. Std. No. 102).

5.1 Packaging. Packaging shall be level A, B, or C as specified (see 6.1).

5.1.1 Unit packaging.

5.1.1.1 Level A. Each guide shall be wrapped in paper conforming to UU-P-553, type I, and packaged in accordance with MIL-P-116, method IC-1.

5.1.1.2 Level B. Each guide shall be placed in a Kraft or glassine envelope. Six guides shall be packaged in a box conforming to PPP-B-566, style and type optional; or to PPP-B-676, type, class and style optional; or to PPP-B-665, style optional. Each box shall be securely closed to prevent accidental opening.

5.1.1.3 Level C. The guides shall be packaged in accordance with the suppliers commercial practice.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.1).

5.2.1 Level A. Guides, of one type and description, shall be packed in boxes conforming to PPP-B-636, class 2, V3c, style RSC. The gross weight of the box shall not exceed the weight limitations of the box specification. Each box shall be closed, waterproof sealed with tape and reinforced with bands of filament tape in accordance with the appendix to the box specification.

5.2.2 Level B. Eight intermediate packages of guides (288 guides) shall be packed in a box conforming to PPP-B-636, type I, class 1, style RSC. Sealing and closure shall be in accordance with the appendix to the box specification. When quantities less than specified are required (see 6.2) the guides shall be packed in a box conforming to that specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:50Z
Check the source to verify that this is the current version before use.

5.3 Marking.

5.3.1 Civil agencies. In addition to markings required by the contract or order, the interior packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.3.2 Military activities. In addition to markings required by the contract or order, the interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The Line Guides covered by this specification are intended for general drafting room use. This does not exclude their use by military service schools, or civil agency drafting schools, trade schools and the like.

6.2 Ordering data. Purchasers should exercise any desired options offered herein and procurement documents should specify the following:

(a) Title, symbol and date of this specification

(b) Inspection responsibility, if other than specified (4.1)

(c) Level of packaging and packing required (5.1, 5.2).

6.3 Transportation description. Transportation descriptions and minimum weights applicable to this commodity are:

Rail:

Drawing instruments, not otherwise indexed by name.

Carload minimum weight 12,000 pounds, subject to Rule 34, Uniform Freight Classification.

Motor:

Drawing instruments, not otherwise indexed.

Truckload minimum weight 12,000 pounds, subject to Rule 115, National Motor Freight Classification.

NOTICE: See last page.

GSA WASH DC 84-10400

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:50Z
Check the source to verify that this is the current version before use.

ADDENDUM

INSTRUCTIONS ON OBTAINING COPIES OF FEDERAL SPECIFICATIONS AND STANDARDS

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications, Standards and Handbooks and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington 25, D. C.

(Single copies of this specification and other, product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D. C., Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, and Auburn, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications, Standards and Handbooks from established distribution points in their agencies.)

NOTICE

When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:50Z
Check the source to verify that this is the current version before use.