INCH-POUND

MS9439A
AMENDMENT 1
8 JULY 2003

# MILITARY STANDARD

## SCREW, MACHINE-STEEL, AMS 6304, DIFFUSED NICKEL-CADMIUM PLATED, HEXAGON HEAD, DRILLED, .164-36 UNJF-3A

**This amendment forms a part of MS9439A, dated 13 DECEMBER 1972, and is approved for use by all Departments and Agencies of the Department of Defense.**

**PAGE 1**

**Screw illustration view at the right: Delete "MIL-S-8879" from ".164-36 UNJF-3A MIL-S-8879" and substitute "AS8879".**

**For view A enlarged view: Add "(SEE NOTE 13)" after ".272 DIA MIN BEARING SURFACE".**

**Add the word "NOTES:" above note 1.**

**Note 8: Delete "AMS 7455" and substitute ""AS7455".**

**Note 9: Delete "AS291" and substitute "ASME B46.1".**

**Add new note: "13. BEARING SURFACE: BEARING SURFACE SHALL BE FLAT AND WASHER FACED. DIAMETER OF BEARING SURFACE SHALL BE EQUAL TO THE MAXIMUM WIDTH ACROSS FLATS WITHIN A TOLERANCE OF MINUS 10% IN ACCORDANCE WITH ASME B18.2.1."**

**Custodians:**
Navy - AS
DLA-IS

**Preparing Activity:**
DLA-IS

**(Project 5305-2545)**

**AMSC N/A** **FSC 5305**

**DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.**

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:17Z
Check the source to verify that this is the current version before use.