MILITARY SPECIFICATION

CONTAINER, SHIPPING AND STORAGE

GUIDED MISSILE CNU-163/E

This specification is approved for use by the Naval Air Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification establishes the requirements for the procurement of one type of shipping and storage container for the PHOENIX Missile AIM-54A Armament Section.

2. APPLICABLE DOCUMENTS

2.1 Issues of Documents. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of the specification to the extent specified herein.

STANDARDS:

FEDERAL

FED-STD-101	Preservation, Packaging and Packing Materials: Test Procedures

MILITARY

MIL-STD-105	Sampling Procedure and Tables for Inspection by Attributes
MIL-STD-129	Marking for Shipment and Storage
MIL-STD-648	Design Criteria for Specialized Shipping Containers

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to Commander, Naval Air Systems Command, Engineering Division, Standardization Section, Code: AIR-52021, Department of the Navy, Washington, D.C. 20361, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC. 8140

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:28Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS·

MILITARY

MIL-D-3464	Desiccants, Activated, Bagged
MIL-P-19644C	Plastic Molding Material (Polystyrene Foam, Expanded Bead)

PUBLICATIONS:

DL-67A242F1	Container, CNU-163/E

(Copies of specifications, standards, drawings and publications required by Contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

AMERICAN SOCIETY FOR TESTING AND MATERIALS

ASTM D1692-76	Rate of Burning and/or Extent and Time of Burning of Cellular Plastics using a specimen supported by a horizonal screen. Standard Test Method 4.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103)

3. REQUIREMENTS

3.1 General Requirements

3.1.1 Construction. The CNU-163/E Container shall be manufactured in accordance with NAVAIR Data Lists (DL) 67A242F1 and all documents referenced herein.

3.1.2 Conflicting Requirements Conflicting requirements arising between this specification and any specification, publication or drawing listed herein shall be referred in writing to the procuring agency or Contracting Office for interpretation and clarification.

3.1.3 Preproduction Sample. Unless otherwise specified in the contract or purchase order (see 6.2), two (2) preproduction samples of the container shall be manufactured using methods and procedures proposed

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:28Z
Check the source to verify that this is the current version before use.

for production. The sample will be tested as specified in Section 4 herein for the purpose of determining that, prior to starting production, the contractor's production methods are capable of yielding items that comply with the technical requirements of this specification.

3.2 Performance Requirements and Product Characteristics. Containers covered by this specification shall be capable of meeting the following performance requirements and product characteristics.

3.2.1 Antistatic Test. The container shall be judged non-conductive when successfully passing the test described in 4.4.0.

3.2.2 Self-Extinguishing. The container shall be judged self-extinguishing (non-burning) when successfully meeting the definition of non-burning of ASTM D1692, Part 27, as demonstrated by test in 4.4.1.

3.2.3 Shock and Vibration. There shall be no evidence of structural failure or inability of the container to protect its contents when the container is subjected to the following tests

a. Low Order Repetitive Shock - 4.4.2

b. Rotational Drop - 4.4.3

c. Impact - 4.4.4

3.2.4 Stacking. There shall be no evidence of breakage or permanent distortion, temporary distortion damaging the contents, or development of an unstable configuration when the container is subjected to the stacking test described in 4.4.5.

3.3 Workmanship. Workmanship in the fabrication and assembly of containers, shall be of sufficiently high quality to assure that completed equipment will comply with all requirements of this specification. Particular attention shall be paid to bonding, painting, riveting, and marking. The assembled containers shall be thoroughly clean of all dirt, chips, and other foreign matter. The standards of workmanship exhibited in any approved preproduction sample, subject to any qualification stated in the Government's notice of approval, shall be determinative of the requirements of the contract relative to workmanship insofar as not specifically covered by applicable specifications.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for Inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:28Z
Check the source to verify that this is the current version before use.

set forth in the specifications where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Classification of Inspections. Inspection of the container shall be classified as follows:

a. First Article Inspection (see 4.4)

b. Quality Conformance Inspection (see 4.5)

4.3 First Article

4.3.1 First Article Sample. Two (2) preproduction samples of containers manufactured in accordnace with 3.1.1 and 3.1.3 shall be subjected to the preproduction tests detailed in 4.4. Acceptance of the preproduction samples shall be based on no defects in the samples.

4.4 First Article Inspection. Preproduction samples, after satisfactorily passing the examinations of 4.5.1 shall be subjected by the Naval Weapons Station Earle, Colts Neck, New Jersey 07722, to the following tests.

4.4.0 Antistatic Test. The sample container shall be dried at 100°F for 6 hours and cooled at room temperature for a minimum of 1/2 hour prior to conducting this test. The container half (top or bottom) shall be placed on a non-conductive (electrical) surface and a flat section shall be stroked ten (10) times with a cat skin (Control Scientific Company, catalogue no. 78640). The container half will not be touched (grounded) while being tested. A Keithley Static Meter, Model 600A, detecting head no. 2501, will be held such that the lip is 3/8 inches from the surface tested The reading shall be taken within 20 seconds after the last cat skin stroke. The maximum reading shall not exceed 2.0 kilovolts

4.4.1 Burn Test. Containers shall be judged "self-extinguishing" when tested in accordance with ASTM D1692, Part 27.

4.4.2 Low Order Repetitive Shock Test. The loaded container shall be tested at ambient temperature in accordance with MIL-STD-648 paragraph 5.2.2 and shall meet the requirements of 3.2.3.

4.4.3 Cornerwise (Rotational) Drop Test The loaded container shall be tested at -20°F and +140°F in accordance with FED-STD-101 Method 5005 level B and shall meet the requirements of 3.2.3.

4.4.4. Incline Impact Test. The loaded container shall be tested at -20°F and +140°F in accordance with FED-STD-101 Method 5023 with optional timber except endwise impacts shall be at a velocity of 10 feet per second and shall meet the requirements of 3.2.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:28Z
Check the source to verify that this is the current version before use.

4 4.5 Stacking Test. The loaded container shall have a superimposed load of 1,680 pounds applied for a period of one hour on its load bearing area and shall meet the requirements of 3.2.4.

4.5 Quality Conformance Inspection

4 5.1 Examination. Containers shall be examined for compliance with the requirements of NAVAIR Data List DL 67A242F1 (see 4.5.2).

4.5.2 Lot and Acceptable Quality Level. All containers of the same design and configuration, manufactured under the same conditions and presented for acceptance at one time, shall be considered an inspection lot for quality conformance tests. Inspection shall be conducted in accordance with MIL-STD-105 at Level II with an Acceptable Quality Level (AQL) of 1.0.

4.5.3 Test and Equipment and Test Facilities Unless otherwise specified, the manufacturer (see 4.1) shall furnish and maintain all normal test equipment, facilities and personnel necessary for performing all quality conformance tests. The test equipment shall be adequate in quantity, and unless definite requirements are specified, they shall be of sufficient accuracy and quality to permit performance of the required quality conformance test.

4.5.4 Test Conditions. Unless otherwise specified in a particular test, all tests shall be performed at a temperature between 50°F and 90°F with ambient humidity.

4.6 Certification of Conformance The manufacturer shall provide in writing a certificate of conformance, certifying that the material of all containers manufactured is in accordance with MIL-P-19644C, Type II, Fire Retardant Class I, 2 lb/ft^3 density.

5. PREPARATION FOR DELIVERY

5.1 Preservation. Twenty-four (24) units of fresh desiccant, MIL-D-3464, shall be placed in each container and the container cover secured

5.2 Packing. Each container shall be overpacked in a fiberboard carton and taped closed.

5.3 Marking. In addition to any special marking required by the contract or purchase order, containers shall be marked in accordance with the applicable marking drawing and MIL-STD-129.

6. NOTES

6.1 Intended Use. Containers supplies under this specification

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:28Z
Check the source to verify that this is the current version before use.

are intended for use in the shipment and storage of PHOENIX Missile AIM-54A Armament Sections.

6.2 Ordering Data.

a. Title, number and date of this specification.

b. First Article sample size, if different (see 4.3.1).

c. Activity designated to perform testing (see 4.4).

Preparing Activity:
Navy-AS

Project 8140- N423

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:28Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No 22 R25[illegible]

INSTRUCTIONS The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay or will otherwise enhance use of the document DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government Fold on lines on reverse side, staple in corner and send to preparing activity Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements Attach any pertinent data which may be of use in improving this document If there are additional papers, attach to form and place both in an envelope addressed to preparing activity

DOCUMENT IDENTIFIER AND TITLE MILITARY SPECIFICATION MIL-C-85124(AS)
Container, Shipping and Storage Guided Missile CNU-163/E

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1 HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A GIVE PARAGRAPH NUMBER AND WORDING

B RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2 COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3 IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4 REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED S/N 0102-014-1802

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:28Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commanding Officer
Naval Air Engineering Center
Engineering Specifications and Standards
Department (ESSD) Code 93
Lakehurst, NJ 08733

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:28Z
Check the source to verify that this is the current version before use.