INCH-POUND
MIL-DTL-83528/13G
07 March 2019
SUPERSEDING
MIL-DTL-83528/13F
13 August 2013

DETAIL SPECIFICATION SHEET

GASKETING MATERIAL, CONDUCTIVE, SHIELDING GASKET, ELECTRONIC, ELASTOMER, ELECTRICAL, EMI/RFI, WAVEGUIDE

This specification sheet is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the gasketing material described herein shall consist of this specification sheet and the latest issue of MIL-DTL-83528.

TABLE I. Selection guide (see figures 1-5 for configurations and dimensions).

Frequency range (GHz)	Band	EIA wave-guide size	Waveguide designation per MIL-DTL-85	Flange designation per MIL-DTL-3922			Flange type	Gasket config-uration	Part or Identifying Number (PIN) M83528/013X
				UG	CPR	CMR			
26.5-40.0	K_a	WR28	RG-96/U (Silver)	UG-599/U			Cover	A	001 1/
				UG-600A/U			Choke	E	002
18.0-26.5	K	WR42	RG-53/U (Brass)	UG-595/U UG-597/U			Cover	A	003 1/
			RG-121/U (Aluminum)	UG-596A/U UG-598A/U			Choke	E	004
12.4-18.0	K_u	WR62	RG-91 (Brass)	UG-419/U			Cover	A	005 1/
			RG-107/U (Silver)	UG-541A/U			Choke	E	006
10.0-15.0		WR75					Cover	A	007
							Choke	E	008
8.2-12.4	X	WR90	RG-52/U (Brass) RG-67/U (Aluminum)	UG-39/U UG-135/U			Cover	A	009
				UG-1736/U UG-1737/U	CPR-90F		Flat contact	A	010 1/
				UG-136A/U UG-40A/U			Choke	E	011
				UG-136B/U UG-40B/U			Choke	E	012
				UG-1360/U UG-1361/U	CPR-90G		Contact	C	013
7.0-11.0		WR102		UG-1494/U			Choke	E	014
7.05-10.0	X_1	WR112	RG-51/U (Brass) RG-68/U (Aluminum)	UG-51/U UG-138/U			Cover	A	015
				UG-1734/U UF-1735/U	CPR-112F		Flat contact	A	016 1/
				UG-52B/U UG-137B/U			Choke	E	017
				UG-1358/U UF-1359/U	CPR-112G		Contact	C	018

See footnote at end of table.


Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:41Z
Check the source to verify that this is the current version before use.

TABLE I. Selection guide (see figures 1 - 5 for configurations and dimensions) - Continued.

Frequency range (GHz)	Band	EIA wave-guide size	Waveguide designation per MIL-DTL-85	Flange designation per MIL-DTL-3922			Flange type	Gasket config-uration	Part or Identifying Number (PIN) M83528/013X
				UG	CPR	CMR			
5.85-8.2	X_b	WR137	RG-50/U (Brass) RG-106/U (Aluminum)	UG-334/U UG-441/U			Cover	B	019
				UG-1732/U UG-1733/U	CPR-137F		Flat contact		020 1/
						CMR-137	Flat contact	A	021 1/
				UG-343B/U UG-440B/U			Choke	D	022
				UG-1356/U UG-1357/U	CPR-137G		Contact	C	023
4.9-7.05		WR159		UG-1730/U UG-1731/U	CPR-159F		Flat contact	A	024 1/
						CMR-149	Flat contact	A	025 1/
3.95-5.85	C	WR187	RG-49/U (Brass) RG-95/U (Aluminum)	UG-149A/U UG-407/U			Cover	B	026
				UG-1728/U UG-1729/U	CPR-187F		Flat contact	A	027 1/
						CMR-187	Flat contact	A	028 1/
				UG-148C/U UG-406B/U			Choke	D	029
				UG-1352/U UG-1353/U	CPR-187G		Contact	C	030
3.30-4.90		WR229		UG-1726/U UG-1727/U	CPR-229F		Flat contact	A	031 1/
						CMR-229	Flat contact	A	032 1/
2.6-3.95	S	WR284	RG-48/U (Brass) RG-75/U (Aluminum)	UG-53/U UG-584/U			Cover	B	033 1/
				UG-1724/U UG-1725/U	CPR-284F		Flat contact	A	034 1/
						CMR-284	Flat contact	A	035 1/
				UG-54B/U UG-585A/U			Choke	E	036
				UG-1348/U UG-1349/U	CPR-284G		Contact	C	037
2.2-3.3		WR340	RG-112U (Brass) RG-112/U (Aluminum)	UG-533/U UG-554/U			Flat contact	A	038 1/
					CPR-340F		Flat contact	A	039 1/
1.7-2.6	W	WR340	RG-104/U (Brass) RG-105/U (Aluminum)	UG-435A/U UG-437A/U			Flat contact	A	040 1/
					CPR-430F		Flat contact	A	041 1/
1.12-1.7	L	WR650	RG-69/U (Brass) RG-103/U (Aluminum)	UG-417A/U UG-418A/U			Flat contact	A	042 1/

1/ This gasket will seal a maximum pressure of 20 psig.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:41Z
Check the source to verify that this is the current version before use.



CONFIGURATION A – DIE CUT SQUARE AND RECTANGULAR

NOTE: Shaded area indicates optional raised lip. When included, the lip shall be a nominal of .187 (4.75 mm) wide. Thickness T_1 shall be .004 (0.10 mm) ± .002 (0.05 mm). Lip is standard on configuration A dash numbers without footnote 1/ reference in table I. For dash numbers in table I with footnote 1/ reference, lip is optional.

Dimensions (Configuration A)							Part or Identifying Number (PIN) M83528/013X	Cross section area (cm^2) 2/
A ± .015 (0.38)	B ± .015 (0.38)	C ± .015 (0.38) -.000 (0.00)	D ± .015 (0.38) -.000 (0.00)	E 1/ ± .010 (0.25)	T ± .003 (0.08)	F Radius ± .010 (0.25)		
.750 (19.05)	.750 (19.05)	.145 (3.68)	.285 (7.24)	.116 (2.95)	.027 (0.69)	.469 (11.91)	001	.0082
.875 (22.23)	.875 (22.23)	.175 (4.45)	.425 (10.80)	.116 (2.95)	.027 (0.69)	.563 (14.30)	003	.0095
1.313 (33.35)	1.313 (33.35)	.630 (16.00)	.320 (8.13)	.140 (3.56)	.027 (0.69)	.875 (22.23)	005	.0095
1.496 (38.00)	1.496 (38.00)	.760 (19.30)	.385 (9.78)	.155 (3.94)	.027 (0.69)	.450 (11.43)	007	.0099
1.625 (41.28)	1.625 (41.28)	.905 (22.99)	.405 (10.29)	.169 (4.29)	.027 (0.69)	.469 (11.91)	009	.0097
1.594 (40.49)	2.094 (53.19)	.405 (10.29)	.905 (22.99)	.169 (4.29)	.027 (0.69)	.250 (6.35)	010	.0161
1.875 (47.63)	1.875 (47.63)	1.130 (28.70)	.505 (12.83)	.180 (4.57)	.027 (0.69)	1.15 (29.21)	015	.0101
1.750 (44.45)	2.500 (63.50)	.505 (12.83)	1.130 (28.70)	.171 (4.34)	.027 (0.69)	.250 (6.35)	016	.076
1.937 (49.20)	2.687 (68.25)	.633 (16.08)	1.380 (35.05)	.206 (5.23)	.027 (0.69)	.250 (6.35)	020	.0176
1.531 (38.89)	2.281 (57.94)	.632 (16.05)	1.382 (35.10)	.150 (3.81)	.027 (0.69)	.125 (3.18)	021	.0121
2.438 (61.93)	3.188 (80.98)	.805 (20.45)	1.600 (40.64)	.257 (6.53)	.027 (0.69)	.313 (7.95)	024	.0220

See footnotes at end of table.

FIGURE 1. Configuration A dimensions.


Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:41Z
Check the source to verify that this is the current version before use.

Dimensions (Configuration A)							Part or Identifying Number (PIN) M83528/013X	Cross section area (cm^2) 2/
A ± .015 (0.38)	B ± .015 (0.38)	C ± .015 (0.38) -.000 (0.00)	D ± .015 (0.38) -.000 (0.00)	E 1/ ± .010 (0.25)	T ± .003 (0.08)	F Radius ± .010 (0.25)		
1.750 (44.45)	2.500 (63.50)	.800 (20.32)	1.600 (40.64)	.160 (4.06) .150 (3.81)	.027 (0.69)	.125 (3.18)	025	.0128
3.500 (88.90)	2.500 (63.50)	1.880 (47.75)	.880 (22.35)	.266 (6.76)	.027 (0.69)	.313 (7.95)	027	.0219
1.784 (45.31)	2.781 (70.64)	.882 (22.40)	1.882 (47.80)	.156 (3.96) .141 (3.58)	.027 (0.69)	.125 (3.18)	028	.0122
2.750 (69.85)	3.875 (98.43)	1.155 (29.34)	2.300 (58.42)	.270 (6.86)	.027 (0.69)	.312 (7.92)	031	.0215
2.000 (50.80)	3.156 (80.16)	1.155 (29.34)	2.300 (58.42)	.150 (3.81)	.027 (0.69)	.125 (3.18)	032	.0114
4.500 (114.30)	3.000 (76.20)	2.850 (72.39)	1.350 (34.29)	.266 (6.76)	.027 (0.69)	.313 (7.95)	034	.0223
3.844 (97.64)	2.344 (59.54)	2.850 (72.39)	1.350 (34.29)	.172 (4.37) .188 (4.78)	.027 (0.69)	.125 (3.18)	035	.0134
3.750 (95.25)	5.440 (138.18)	1.710 (43.43)	3.410 (86.61)	.264 (6.71) .250 (6.35)	.027 (0.69)	.250 (6.35)	038	.0275
3.750 (95.25)	5.438 (138.13)	1.710 (43.43)	3.410 (86.61)	.266 (6.76)	.027 (0.69)	.250 (6.35)	039	.0275
4.188 (106.38)	6.344 (161.14)	2.160 (54.86)	4.310 (109.47)	.266 (6.76) .281 (7.14)	.027 (0.69)	.250 (6.35)	040	.0274
6.344 (161.14)	4.188 (106.38)	4.310 (109.47)	2.160 (54.86)	.266 (6.76)	.027 (0.69)	.250 (6.35)	041	.0275
5.438 (138.13)	8.688 (220.68)	3.260 (82.80)	6.510 (165.35)	.250 (6.35) .328 (8.33)	.027 (0.69)	.250 (6.35)	042	.0294

1/ Number and location of holes conform to holes in standard waveguide flanges identified in table I. Where two hole diameters are given, flange has holes of two different diameters.
2/ For calculation of volume resistivity (surface probe).

FIGURE 1. Configuration A dimensions – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:41Z
Check the source to verify that this is the current version before use.



CONFIGURATION B – DIE CUT CIRCULAR


NOTE: Shaded area indicates optional raised lip. When included, the lip shall be a nominal of .187 (4.75 mm) wide. Thickness T_1 shall be .004 (0.10 mm) ± .002 (0.05 mm). Lip is standard on configuration B dash numbers without footnote 1/ reference in table I. For dash numbers in table I with footnote 1/ reference, lip is optional.

Dimensions (Configuration B)					Part or Identifying Number (PIN) M83528/013X	Cross section area (cm^2) 2/
A ± .015 (0.38)	B ± .015 (0.38) -0.000 (0.00)	C ± .015 (0.38) -0.000 (0.00)	D 1/ ± .010 (0.25)	T ± .005 (0.13)		
3.125 (79.38)	.632 (16.05	1.382 (35.10)	.234 (5.94)	.027 (0.69)	019	.0337
3.625 (92.08)	.882 (22.40)	1.882 (47.80)	.234 (5.94)	.027 (0.69)	026	.0370
5.312 (134.92)	1.350 (34.29)	2.850 (72.39)	.290 (7.37)	.027 (0.69)	033	.0535

1/ Number and location of holes conform to holes in standard waveguide flanges identified in table I.
2/ For calculation of volume resistivity (surface probe).

FIGURE 2. Configuration B dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:41Z
Check the source to verify that this is the current version before use.



CONFIGURATION C – MOLDED RECTANGULAR WITH "O" CROSS SECTION


NOTE: Molding flash of .003 (0.08 mm) in width (maximum) and .005 (0.13 mm) in thickness (maximum) is allowed.

Dimensions (Configuration C)			Part or Identifying Number (PIN) M83528/013X	Cross section area (cm^2) 1/
A	B	T dia.		
1.368 (34.75) ± .012 (0.30)	.868 (22.05) ± .010 (0.25)	.103 (2.62) ± .003 (0.08)	013	.0538
1.616 (41.05) ± .015 (0.38)	.991 (25.17) ± 0.010 (0.25)	.103 (2.62) ± .003 (0.08)	018	.0538
1.866 (41.05) ± .015 (0.38)	1.116 (28.35) ± .012 (0.30)	.103 (2.62) ± .003 (0.08)	023	.0538
2.449 (62.20) ± .020 (0.51)	1.449 (36.80) ± .013 (0.33)	.139 (3.53) ± .004 (0.10)	030	.0979
3.451 (87.67) ± .024 (0.61)	1.951 (49.56) ± .018 (0.46)	.139 (3.53) ± .004 (0.10)	037	.0979

1/ For calculation of volume resistivity (surface probe).

FIGURE 3. Configuration C dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:41Z
Check the source to verify that this is the current version before use.



CONFIGURATION D – MOLDED CIRCULAR WITH “O” CROSS SECTION


NOTE: Molding flash of .003 (0.08 mm) in width (maximum) and .005 (0.13 mm) in thickness (maximum) is allowed.

Dimensions (Configuration D)		Part or Identifying Number (PIN) M83528/013X	Cross section area (cm^2) 1/
D (ID)	T		
2.011 (51.08) ± .018 (0.46)	.139 (3.53) ± .004 (0.10)	022	.0979
2.683 (68.15) ± .024 (0.61)	.115 (2.92) ± .004 (0.10)	029	.0670

1/ For calculation of volume resistivity (surface probe).

FIGURE 4. Configuration D dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:41Z
Check the source to verify that this is the current version before use.



CONFIGURATION E – MOLDED CIRCULAR WITH "D" CROSS SECTION

NOTE: Molding flash of .003 (0.08 mm) in width (maximum) and .005 (0.13 mm) in thickness (maximum) is allowed.

Dimensions (Configuration E)				Part or Identifying Number (PIN) M83528/013X	Cross section area (cm^2) 1/
A	B	D (ID)	T		
.056 (1.42)	.041 (1.04)	.410 (10.41)	.082 (2.08)	002	.025
.048 (1.22)	.039 (0.99)	.587 (14.91)	.078 (1.98)	004	.020
.125 (3.18)	.078 (1.98)	.885 (22.48)	.155 (3.94)	006	.109
.065 (1.65)	.049 (1.24)	1.122 (28.50)	.099 (2.51)	008	.035
.088 (2.24)	.048 (1.22)	1.340 (34.04)	.095 (2.41)	011	.048
.077 (1.96)	.058 (1.47)	1.310 (33.27)	.115 (2.92)	012	.048
.085 (2.16)	.048 (1.22)	1.392 (35.36)	.095 (2.41)	014	.046
.078 (2.16)	.053 (1.35)	1.550 (39.37)	.105 (2.67)	017	.045
.188 (4.78)	.120 (3.05)	3.910 (99.31) ± .026 (0.66)	.240 (6.10)	036	.251

1/ For calculation of volume resistivity (surface probe).

NOTES:
1. Dimensions are in inches/ metric equivalents are given in parenthesis and are for general information only.
2. Unless otherwise indicated, tolerances shall be as follows:

Dimensions		Tolerance
Under	.101 (2.57)	± .005 (0.13)
	.101 to .200 (2.57 to 5.08)	± .008 (0.20)
	.201 to .300 (5.11 to 7.62)	± .010 (0.25)
	.301 to .500 (7.65 to 12.70)	± .015 (0.38)
Over	.500 (12.70)	± .020 (0.51)

FIGURE 5. Configuration E dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:41Z
Check the source to verify that this is the current version before use.

SELECTION GUIDE: See table I.

REQUIREMENTS:

Design and interface: See figures 1-5 and table I.

Materials:

Configuration A: Type G.

Configuration B: Type G.

Configuration C: Types C, F, H, or K.

Configuration D: Types C, F, H, or K.

Configuration E: Types C, F, H, or K.

Part or Identifying Number (PIN): See table I and figures 1-5. An "X" in the PIN represents the material type (see above). PIN example: M83528/013G001. Gaskets with optional high-pressure raised lip (see table I and figures 1-5) will have a "Z" added to their PIN's. Example: M83528/013G001Z.

Supersession information: See table II.

TABLE II. Supersession information. 1/

MIL-G-83528/13B PIN M83528/013X	Superseded MIL-G-83528/13A PIN M83528/013X	Superseded DESC drawing PIN 85118X
002	001	001
004	002	002
006	003	003
008	004	004
012	005	005
011	006	006
014	007	007
017	008	008
036	009	009

1/ "X" in the PIN indicates the applicable material type.

Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Referenced documents. In addition to MIL-DTL-83528, this document references the following:

MIL-DTL-85 MIL-DTL-3922

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:41Z
Check the source to verify that this is the current version before use.

Custodians:
Army – CR
Navy – EC
Air Force – 85
DLA – CC

Review activities:
Air Force – 19
NASA – NA

Preparing activity:
DLA – CC

(Project 5999-2019-003)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:41Z
Check the source to verify that this is the current version before use.