PERFORMANCE SPECIFICATION

CAPACITOR, FIXED, CERAMIC DIELECTRIC,
SWITCH MODE POWER SUPPLY
(GENERAL PURPOSE AND TEMPERATURE STABLE),
STANDARD RELIABILITY AND HIGH RELIABILITY,
GENERAL SPECIFICATION FOR

This amendment forms part of MIL-PRF-49470A, dated 11 January 2000, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

TABLE IV, delete and substitute:

"TABLE IV. Configuration.

Symbol (last digit of PIN)	Lead style	Height profile (Dimension A)	Formed lead length, L (inches)
N	N (straight)	Standard	N/A
L	L (formed)	Standard	.070 ± .010
M	L (formed)	Standard	.045 ± .010
J	J (formed)	Standard	.070 ± .010
K	J (formed)	Standard	.045 ± .010
A	N (straight)	Low	N/A
B	L (formed)	Low	.070 ± .010
D	L (formed)	Low	.045 ± .010
C	J (formed)	Low	.070 ± .010
F	J (formed)	Low	.045 ± .010

"

PAGE 7

3.21, following the capacitance requirement, add:

"Dissipation factor As specified in 3.12."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:11Z
Check the source to verify that this is the current version before use.

Custodians:
Army - CR
Navy - EC
Air Force - 11
NASA - NA
DLA - CC

Review activities:
Army - AR, AT, AV, CR4, MI
Navy - MC
Air Force - 19, 99

Preparing activity:
Army - CR

Agent:
DLA - CC

(Project 5910-2099)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:11Z
Check the source to verify that this is the current version before use.