INCH-POUND
MIL-PRF-49470B
SUPPLEMENT 1
13 January 2003

PERFORMANCE SPECIFICATION

CAPACITOR, FIXED, CERAMIC DIELECTRIC, SWITCH MODE POWER SUPPLY (GENERAL PURPOSE AND TEMPERATURE STABLE), STANDARD RELIABILITY AND HIGH RELIABILITY, GENERAL SPECIFICATION FOR

This supplement forms a part of MIL-PRF-49470B, dated 13 January 2003.

SPECIFICATION SHEETS

MIL-PRF-49470/1 - Capacitor, Fixed, Ceramic Dielectric, Switch Mode Power Supply (General Purpose and Temperature Stable), Standard Reliability and High Reliability, Unencapsulated, Horizontally Stacked, Style PS01.

MIL-PRF-49470/2 - Capacitor, Fixed, Ceramic Dielectric, Switch Mode Power Supply (General Purpose and Temperature Stable), Standard Reliability and High Reliability, Encapsulated, Horizontally Stacked, Style PS02.

MIL-PRF-49470/3 - Capacitor, Fixed, Ceramic Dielectric, Switch Mode Power Supply (General Purpose and Temperature Stable), Standard Reliability and High Reliability, Conformally Coated, Horizontally Stacked, Style PS03.

MIL-PRF-49470/4 - Capacitor, Fixed, Ceramic Dielectric, Switch Mode Power Supply (General Purpose and Temperature Stable), Standard Reliability and High Reliability, Unencapsulated, Vertically Stacked, Style PS04.

MIL-PRF-49470/5 - Capacitor, Fixed, Ceramic Dielectric, Switch Mode Power Supply (General Purpose and Temperature Stable), Standard Reliability and High Reliability, Encapsulated, Vertically Stacked, Style PS05.

MIL-PRF-49470/6 - Capacitor, Fixed, Ceramic Dielectric, Switch Mode Power Supply (General Purpose and Temperature Stable), Standard Reliability and High Reliability, Conformally Coated, Vertically Stacked, Style PS06.

Preparing activity:
Army - CR

Agent:
DLA - CC

(Project 5910-2208-99)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:11Z
Check the source to verify that this is the current version before use.