INCH-POUND

MIL-PRF-49471/4 (CR)
AMENDMENT 1
1 October 1998

PERFORMANCE SPECIFICATION SHEET

BATTERY, NON-RECHARGEABLE, HIGH PERFORMANCE, BA-X567/U

This amendment forms a part of MIL-PRF-49471/4 (CR), dated 2 June 1995, and is approved for use by the Communications - Electronics Command, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

Under requirements, add: "State Of Charge Indicator is not required. Charge Protection is not required."

PAGE 3

Under "Closed circuit voltage test", add: "Cell closed circuit test: Load resistance of 20 ohms shall be used. Voltage shall be above 2/3 of the cell 's minimum useful open circuit voltage within five (5) seconds. Cell forced discharge and cell series string tests are not required. For this battery, only the cell short circuit, cell closed circuit voltage and electrolyte leakage test of Table I are required. Sample size: 9 cells. Cell water content certification is required."

Custodian:
Army-CR

Preparing Activity:
Army-CR

(Project 6135-0398-04)

AMSC N/A

FSC 6135

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:12Z
Check the source to verify that this is the current version before use.