INCH-POUND

MIL-PRF-49471/5 (CR)
AMENDMENT 1
1 October 1998

PERFORMANCE SPECIFICATION SHEET

BATTERY, NON-RECHARGEABLE, HIGH PERFORMANCE, BA-X847/U

This amendment forms a part of MIL-PRF-49471/5 (CR), dated 2 June 1995, and is approved for use by the Communications - Electronics Command, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

Under requirements, add: "State Of Charge Indicator is required."

PAGE 3

Add to Capacity Test List: "LR1, 48 hours; LR2, 96 hours."

PAGE 4

Under "Methods Of Examination And Tests, (2) Discharge" add: "For the LR1 test, the batteries shall be cycled continuously at 1.2 W for 1 minute followed by 110 mA for 4 minutes to zero volts. For the LR2 test, the batteries shall be cycled continuously at 0.60 W for 1 minute followed by 55 mA for 4 minutes to zero volts.

Under "Closed circuit voltage test", add: "Cell closed circuit test: Load resistance of 1.50 ohms shall be used. Voltage shall be above 2/3 of the cell 's minimum useful open circuit voltage within five (5) seconds."

Custodian:
Army - CR

Preparing Activity:
Army - CR

(Project 6135-0398-05)

AMSC N/A

FSC 6135

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:12Z
Check the source to verify that this is the current version before use.