INCH-POUND

MIL-PRF-49471/9 (CR)
AMENDMENT 1
1 October 1998

PERFORMANCE SPECIFICATION SHEET

BATTERY, NON-RECHARGEABLE, HIGH PERFORMANCE, BA-X372/U

This amendment forms a part of MIL-PRF-49471/9 (CR), dated 2 June 1995, and is approved for use by the Communications - Electronics Command, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

Under Requirements, add: "State Of Charge Indicator is not required. Complete Discharge Device is not required. The cell electrolyte leakage amount shall not exceed 1.0% of the total electrolyte in the cell when tested as specified in the basic specification."

Under Requirements, delete "Safety Feature (cell)" and replace with:

"Safety Feature (cell): Applicable.

PAGE 3

Under "Closed circuit voltage test", add: "Cell closed circuit test: Load resistance of 150 ohms shall be used. Voltage shall be above 2/3 of the cell 's minimum useful open circuit voltage within five (5) seconds."

Custodian:
Army-CR

Preparing Activity:
Army-CR

(Project 6135-0398-09)

AMSC N/A | 1 of 1 | FSC 6135

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:12Z
Check the source to verify that this is the current version before use.