INCH-POUND

MIL-M-38510/753A
AMENDMENT 1
23 November 1994

MILITARY SPECIFICATION

MICROCIRCUITS, DIGITAL, ADVANCED CMOS
FLIP-FLOPS, MONOLITHIC SILICON, POSITIVE LOGIC

This amendment forms a part of MIL-M-38510/753A, dated 27 May 1994, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

TABLE I, high level output voltage, V_{OH3}, device type column: Add "04" after "02,07" for RHA levels of M, D, and R.

TABLE I, high level output voltage, V_{OH5}, device type column: Add "04" after "02,07" for RHA levels of M, D, and R.

PAGE 5

TABLE I, high level output voltage, V_{OH7}, device type column: Add "04" after "02,07" for RHA levels of M, D, and R.

TABLE I, low level output voltage, V_{OL3}, device type column: Add "04" after "02,07" for RHA levels of M, D, and R.

TABLE I, low level output voltage, V_{OL5}, device type column: Add "04" after "02,07" for RHA levels of M, D, and R.

PAGE 6

TABLE I, low level output voltage, V_{OL7}, device type column: Add "04" after "02,07" for RHA levels of M, D, and R.

TABLE I, positive input clamp voltage, V_{IC+}, device type column: Add "04" after "02,07" for RHA levels of M, D, and R.

TABLE I, negative input clamp voltage, V_{IC-}, device type column: Add "04" after "02,07" for RHA levels of M, D, and R.

TABLE I, input current high, I_{IH}, device type column: Add "04" after "02,07" for RHA levels of M, D, and R.

TABLE I, input current low, I_{IL}, device type column: Add "04" after "02,07" for RHA levels of M, D, and R.

PAGE 7

TABLE I, quiescent supply current output high, I_{CCH}, device type column: Add "04" after "02,07" for RHA levels of M, D, and R.

TABLE I, quiescent supply current output low, I_{CCL}, device type column: Add "04" after "02,07" for RHA levels of M, D, and R.

PAGE 8

TABLE I, truth table test output voltage, device type column: Add "04" after "02,07" for RHA levels of M, D, and R.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:02Z
Check the source to verify that this is the current version before use.

PAGE 9

TABLE I, propagation delay time, clock to Q or $\overline{Q}$, t_{PHL}, t_{PLH}, device type column: Add "04" after "02" for RHA levels of M, D, and R (six places).

PAGE 10

TABLE I, propagation delay time, $\overline{SD}$ or $\overline{CD}$ to Q or $\overline{Q}$, t_{PHL}, t_{PLH}, device type column: Add "04" after "02" for RHA levels of M, D, and R (six places).

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 17
NASA - NA

Review activities:
Army - AR, MI, SM
Air Force - 19, 85, 99
DLA - ES
Navy - AS, CG, MC, OC, SH

Preparing activity:
Air Force - 17

Agent:
DLA - ES

(Project 5962-1408)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:02Z
Check the source to verify that this is the current version before use.