INCH-POUND
MIL-M-38510/756A
AMENDMENT 1
24 November 1997

MILITARY SPECIFICATION

MICROCIRCUITS, DIGITAL, ADVANCED CMOS, FLIP-FLOPS, MONOLITHIC SILICON, POSITIVE LOGIC

Inactive for new design after 9 August 1996

This amendment forms a part of MIL-M-38510/756A, dated 7 November 1994, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 5

Table I, high level output voltage, V_{OH3}, device type column; add “04” after “01, 02” for RHA levels M, D, and R.
Table I, high level output voltage, V_{OH5}, device type column; add “04” after “01, 02” for RHA levels M, D, and R.

PAGE 6

Table I, high level output voltage, V_{OH7}, device type column; add “04” after “01, 02” for RHA levels M, D, and R.
Table I, low level output voltage, V_{OL3}, device type column; add “04” after “01, 02” for RHA levels M, D, and R.
Table I, low level output voltage, V_{OL5}, device type column; add “04” after “01, 02” for RHA levels M, D, and R.

PAGE 7

Table I, low level output voltage, V_{OL7}, device type column; add “04” after “01, 02” for RHA levels M, D, and R.
Table I, positive input clamp voltage, V_{IC+}, device type column; add “04” after “01, 02” for RHA levels M, D, and R.
Table I, negative input clamp voltage, V_{IC-}, device type column; add “04” after “01, 02” for RHA levels M, D, and R.
Table I, input current high, I_{IH}, device type column; add “04” after “01, 02” for RHA levels M, D, and R.
Table I, input current low, I_{IL}, device type column; add “04” after “01, 02” for RHA levels M, D, and R.

PAGE 8

Table I, quiescent supply current outputs high, I_{CCH}, device type column; add “04” after “01, 02” for RHA level M, and add “04” after “01” for RHA levels D and R.
Table I, quiescent supply current outputs low, I_{CCL}, device type column; add “04” after “01, 02” for RHA level M, and add “04” after “01” for RHA levels D and R.
Table I, quiescent supply current outputs three-state, I_{CCZ}, device type column and limits column; add “04” with the max limit of “15 μA” to RHA level M, add “04” with the max limit of “75 μA” to RHA level D and add “04” with the max limit of “700 μA” to RHA level R.
Table I, three-state output leakage current high, I_{OZH}, device type column; add “04” after “02” for RHA levels M, D, and R.
Table I, three-state output leakage current low, I_{OZL}, device type column; add “04” after “02” for RHA levels M, D, and R.

FSC 5962

AMSC N/A
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:03Z
Check the source to verify that this is the current version before use.

PAGE 10

Table I, truth table test, device type column; add “04” after “01, 02” for RHA levels M, D, and R.

PAGE 11

Table I, propagation delay time, CP to Yn, $\overline{Yn}$, V_{CC} = 3.0 V, device type column; add “04” after “02” for RHA levels M, D, and R.

PAGE 12

Table propagation delay time, CP to Yn, $\overline{Yn}$, V_{CC} = 4.5 V, device type column; add “04” after “02” for RHA levels M, D, and R.

PAGE 13

Table I, unit column, add “ns” two places

Table I, output enable time, OE to Yn, Yn , V_{CC} = 3.0 V, add a row to RHA limit M for device type “04” with a limit of “1.0” for the min column and “11.0” for the max column, add a row to RHA limit D for device type “04” with a limit of “1.0” for the min column and “11.0” for the max column, and add a row to RHA limit R for device type “04” with a limit of “1.0” for the min column and “11.0” for the max column.

Table I, output enable time, OE to Yn, Yn , V_{CC} = 4.5 V, add a row to RHA limit M for device type “04” with a limit of “1.0” for the min column and “8.5” for the max column, add a row to RHA limit D for device type “04” with a limit of “1.0” for the min column and “8.5” for the max column, and add a row to RHA limit R for device type “04” with a limit of “1.0” for the min column and “8.5” for the max column.

PAGE 14

Table I, unit column, add “ns” two places.

Table I, output disable time, OE to Yn, Yn , V_{CC} = 3.0 V, add a row to RHA limit M for device type “04” with a limit of “1.0” for the min column and “12.0” for the max column, add a row to RHA limit D for device type “04” with a limit of “1.0” for the min column and “12.0” for the max column, and add a row to RHA limit R for device type “04” with a limit of “1.0” for the min column and “12.0” for the max column.

Table I, output disable time, OE to Yn, Yn , V_{CC} = 4.5 V, add a row to RHA limit M for device type “04” with a limit of “1.0” for the min column and “10.0” for the max column, add a row to RHA limit D for device type “04” with a limit of “1.0” for the min column and “10.0” for the max column, and add a row to RHA limit R for device type “04” with a limit of “1.0” for the min column and “10.0” for the max column.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 17
NASA - NA

Preparing activity:
DLA - CC

Review activities:
Navy - OS, TD, AS, CG, MC, SH
Army - AR, MI, SM
Air Force - 19, 85, 99

(Project 5962-1808)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:03Z
Check the source to verify that this is the current version before use.