NOT MEASUREMENT SENSITIVE

MIL-HDBK-780D
w/Change 1
6 January 2012
SUPERSEDING
MIL-HDBK-780D
28 May 2004

DEPARTMENT OF DEFENSE HANDBOOK

STANDARD MICROCIRCUIT DRAWINGS

This handbook is for guidance only.
Do not cite this document as a requirement.

AMSC N/A

FSC 5962

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.

FOREWORD

1. This handbook is approved for use by all Departments and Agencies of the Department of Defense.

2. This handbook provides guidance on standard microcircuit drawings (SMD's). The purpose of the SMD program is to minimize the proliferation of specification and source control drawings within the Department of Defense (DoD). The use of one SMD for an item of supply in use by DoD Departments and Agencies is the objective of this program.

3. It is intended that the issue of SMD's affect DoD procurement through minimizing the proliferation of duplicate drawings for an item of supply.

4. It is also the objective of the SMD Program that the resulting drawing be multi-user in actual implementation.

5 The application of this handbook is currently confined to the acquisition of microcircuits until such time that applicability to federal supply classes other than FSC 5962 is deemed appropriate.

* 6. Comments, suggestions, or questions on this document should be addressed to Commander, Defense Logistics
* Agency, DLA Land and Maritime, ATTN: VA, P. O. Box 3990, Columbus, OH 43218-3990 or emailed to
* STD1835@dla.mil. Since contact information can change, you may want to verify the currency of this address
* information using the ASSIST Online database at https://assist.daps.dla.mil/.

* SUMMARY OF CHANGE 1 MODIFICATIONS

1. References to MIL-HDBK-512 has been changed to MIL-STD-3018, which supersedes it.

2. References to MIL-STD-1835 and SD-19 have been added.

3. References to ASME Y14.5M has been changed to ASME Y14.5, which supersedes it.

4. The organization notated as ASME has been changed from American Society of Mechanical Engineers to ASME International to reflect the current name.

5. Section 2, and throughout, the web address for acquiring government specifications and standards has been changed to the current address for the Assist online services.

6. Section 4.2.5.5, Classification of conformance inspections has been edited to include Group E which was missing.

7. In various locations, Defense Supply Center Columbus has been changed to DLA Land Maritime to reflect the current name.

8. Figures 1-6 has been changed to reflect current boiler plates.

9. Where applicable, changes were made to comply with MIL-STD-967 for preparation of a military handbook.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.

CONTENTS

PARAGRAPH		PAGE
1.	SCOPE	1
1.1	Scope	1
2.	APPLICABLE DOCUMENTS	1
2.1	General	1
2.2	Government documents	1
2.2.1	Specifications, standards, and handbooks	1
* 2.2.2	Other Government documents, drawings, and publications	1
2.3	Non-Government publications	1
2.4	Order of precedence	2
3.	DEFINITIONS	2
3.1	Standard microcircuit drawing	2
3.2	General specification	2
3.3	Military Parts Control Advisory Group (MPCAG)	2
4.	GENERAL GUIDANCE	2
4.1	Introduction	2
4.2	Sectional arrangement of an SMD	2
4.2.1	Subject matter	2
4.2.2	Section 1	2
4.2.2.1	Scope	2
4.2.2.2	Part or Identifying Number (PIN)	2
4.2.3	Section 2	3
4.2.3.1	Listing of references	3
4.2.3.1.1	Government documents	3
4.2.3.1.2	Nongovernment standards and other publications	4
4.2.3.1.3	Order of precedence	4
4.2.4	Section 3	4
4.2.4.1	Requirements	4
4.2.4.1.1	Organization of requirements	5
4.2.4.1.2	Sequencing of requirements and tests	5
4.2.4.2	Materials	5
4.2.4.3	Design	5
4.2.4.4	Construction	5
4.2.4.5	Hardware	5
4.2.4.6	Performance characteristics	5
4.2.4.7	Dimensions	6
4.2.4.8	Finish	6
4.2.4.9	Marking	6
4.2.4.10	Selection of alternative materials, construction, etc.	6
4.2.4.11	Certificate of compliance	6
4.2.4.12	Certificate of conformance	6
4.2.4.13	Notification of change or discontinuance	6

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.

CONTENTS

PARAGRAPH		PAGE
4.2.4.14	Verification and review	6
4.2.5	Section 4	6
4.2.5.1	Quality assurance provisions	6
4.2.5.2	Responsibility for inspection	6
4.2.5.3	Responsibility for compliance	7
4.2.5.4	Conformance inspection	7
4.2.5.4.1	Conformance inspection sampling	7
4.2.5.5	Classification of conformance inspections	7
4.2.5.6	Tabular listing of conformance inspection	8
4.2.6	Section 5	8
4.2.6.1	Packaging, packing, and marking	8
4.2.7	Section 6	8
4.2.7.1	Notes	8
4.2.7.2	Intended use	8
4.2.7.3	Comments	8
4.2.7.4	Sources of supply	8
4.3	Approved SMD's	9
4.3.1	SMD user	9
4.3.2	Changes to SMD's	9
4.3.3	Nonconcurrence with proposed changes	9
5.	DETAILED GUIDANCE	9
5.1	Introduction	9
5.2	Drawing preparation	9
5.3	Initial drawing preparation	9
5.3.1	Blank drawings	9
5.3.2	SMD coordination	9
5.3.3	Preliminary and final draft submittal	9
5.3.3.1	Preliminary draft construction	9
5.3.4	Maintenance	9
5.3.5	SMD content preparation	9
5.3.5.1	Section 1, scope	9
5.3.5.1.1	Scope	9
5.3.5.1.2	PIN	9
5.3.5.1.2.1	PIN length	10
5.3.5.1.3	Radiation hardness assurance (RHA) Designator	10
5.3.5.1.4	Device type(s)	10
5.3.5.1.5	Device class designator	10
5.3.5.1.6	Case outline	10
5.3.5.1.7	Lead finish	10
5.3.5.1.8	Absolute maximum ratings	10
5.3.5.1.9	Recommended operating conditions	10

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.

CONTENTS

PARAGRAPH		PAGE
5.3.5.2	Section 2, applicable documents	10
5.3.5.2.1	Order of precedence	10
5.3.5.3	Section 3, requirements	10
5.3.5.3.1	Item requirements	10
5.3.5.3.2	Design, construction and physical dimensions	10
5.3.5.3.3	Terminal connections	10
5.3.5.3.4	Block diagram	11
5.3.5.3.5	Truth tables	11
5.3.5.3.6	Case outline(s)	11
5.3.5.3.7	Electrical performance characteristics and post irradiation parameter limits	11
5.3.5.3.8	Electrical test requirements	11
5.3.5.3.9	Marking	11
5.3.5.3.10	Tables	11
5.3.5.3.11	Graphics	11
5.3.5.3.12	Certificate of compliance	11
5.3.5.3.13	Certificate of conformance	11
5.3.5.3.14	Notification of change	11
5.3.5.3.15	Verification of change	11
5.3.6	Section 4, verification	12
5.3.6.1	Sampling and inspection	12
5.3.6.2	Screening	12
5.3.6.3	Qualification inspection	12
5.3.6.4	Conformance inspection	12
5.3.6.4.1	Group A inspection	12
5.3.6.4.2	Group C inspection	12
5.3.6.4.3	Group D inspection	12
5.3.6.4.4	Group E inspection	12
5.3.6.5	Tables, electrical tests	12
5.3.7	Section 5, packaging	12
5.3.7.1	Packaging requirements	12
5.3.8	Section 6, notes	12
5.3.8.1	Intended use	12
5.3.8.1.1	Replaceability	12
5.3.8.1.2	Substitutability	13
5.3.8.2	Configuration control of SMD's	13
5.3.8.3	Record of users	13
5.3.8.4	Comments	13
5.3.8.5	Abbreviations, symbols, and definitions	13
5.3.8.6	Sources of supply	13

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.

CONTENTS

PARAGRAPH PAGE

6 NOTES 13
6.1 Intended use 13
6.1.1 Standard microcircuit drawing program (SMDP) 13
6.2 Draft construction 13
6.3 Certificate of compliance 13
6.4 Subject term (key word) listing 13
* 6.5 Change notations 13

FIGURES

1. Drawing, title sheet 14
2. Drawing, continuation sheet 15
3. Certificate of compliance 16
4. SMD preparation flowchart 19
5. SMD with boilerplate 21
6. Sample SMD 29

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.

1. SCOPE

1.1 Scope. This handbook provides guidance and information concerning standard microcircuit drawings (SMD's). System applications are subject to the approval of the applicable program office. This handbook is for guidance only and cannot be cited as a requirement.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed below are not necessarily all of the documents referenced herein, but are those needed to understand the information provided by this handbook.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein.

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-PRF-38534 - Hybrid Microcircuits, General Specification for
MIL-PRF-38535 - Integrated Circuits (Microcircuits) Manufacturing, General Specification for

DEPARTMENT OF DEFENSE STANDARD

MIL-STD-883 - Test Method Standard Microcircuits
* MIL-STD-1835 - Department of Defense Interface Standard, Electronic Component Case Outlines
* MIL-STD-3018 - Parts Management Standard

DEPARTMENT OF DEFENSE HANDBOOK

MIL-HDBK-103 - List of Standard Microcircuit Drawings (SMD's)

* (Copies of these documents are available online at https://assist.daps.dla.mil/quicksearch/ or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

* 2.2.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract

DEFENSE STANDARDIZATION PROGRAM OFFICE.

* SD-19 - Parts Management Guide

(Copies of these documents are available online at https://assist.daps.dla.mil/quicksearch/ or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

2.3 Non-Government publications. The following documents form a part of this document to the extent specified herein.

* ASME International (ASME)

* ASME Y14.5 - Dimensioning and Tolerancing
ASME Y14.100 - Engineering Drawing Practices

* (Copies of these documents are available online at http://www.asme.org/ or from the ASME International, Three Park Avenue, New York, NY 10016-5990).

2.4 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.

3. DEFINITIONS

3.1 Standard microcircuit drawing (SMD). SMD's depict the Government's requirements for an existing commercial item, tested for a military application, disclosing applicable configuration, envelope dimensions, mounting and mating dimensions, interface dimensional characteristics, specified performance requirements, and inspection and acceptance test requirements as appropriate for a military environment.

3.2 General specification. A general specification is prepared in the six-section format and covers requirements and test procedures that are common to a group of parts, materials, or equipments. It is used with either associated device specifications, specification sheets or SMD's (not a mixture); e.g., MIL-PRF-38534 or MIL-PRF-38535 for microcircuits.

3.3 Military Parts Control Advisory Group (MPCAG). A DoD organization which provides advice to the military departments and military contractors on the selection of parts in assigned commodity classes, and collects data on nonstandard parts for developing and updating military specifications and standards.

4. GENERAL GUIDANCE

4.1 Introduction. This section provides general guidelines regarding contents, organization, and paragraphing applicable to the preparation of SMD's. SMD's should be in a standard drawing format in accordance with the guidance contained herein (see figures 1 and 2).

4.2 Sectional arrangement of an SMD. An SMD contains six sections, titled and numbered as shown below. SMD's should be in standard drawing format in accordance with ASME Y14.100 (see figures 1 and 2).

1. SCOPE
2. APPLICABLE DOCUMENTS
3. REQUIREMENTS
4. VERIFICATION
5. PACKAGING
6. NOTES

4.2.1 Subject matter. Subject matter should be kept within the scope of the sections so that the same requirements or information will always appear in the same section of every SMD. If there is no information pertinent to a section, the following should appear below the section heading:

"This section is not applicable to this drawing".

4.2.2 Section 1.

4.2.2.1 Scope. The scope should repeat the item name and its modifiers, and provide a clear, concise abstract of the coverage of the SMD. This brief statement is the beginning paragraph. The scope should not contain requirements that should be part of section 3. Figures are not included in the scope.

4.2.2.2 Part or Identifying Number (PIN). Section 1 includes a paragraph entitled "PIN" which describes how the SMD PIN is constructed (see 5.3.5.1.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.

4.2.3 Section 2.

4.2.3.1 Listing of references. Section 2 is used to list those documents referenced in the SMD. Government specifications, standards, adopted non-Government standards, international standardization documents, handbooks, drawings, and approved publications may be referenced in microcircuit drawings. Other non-Government documents promulgated by non-Government standards bodies may also be referenced. Government regulations or codes are referenced as applicable. Military Activity Regulations and other documents not readily available from or through the contracting activity are not referenced in an SMD. Care should be taken in referencing non-Government publications to assure the availability of copies and to acquire prior approval of copyright owner. All those documents identified and referred to in sections 3, 4, and 5 of the SMD are listed in section 2. References are confined to documents currently available at the time of issuance of the SMD. Figures bound integrally with the SMD are not listed in section 2 unless they are reduced-size copies of drawings provided for information only.

4.2.3.1.1 Government documents. Referenced Government documents are listed by document title and identifier excluding revision letters (unless otherwise specified) or suffix (preparing activity symbols) and the "00" designation for "USED IN LIEU OF". The titles should be taken from the documents rather than an index. Government specifications, standards, handbooks, drawing and publications as applicable are listed numerically (except Federal specifications which are listed alpha-numerically) under these headings and in individual groups such as Federal, Military, and Departmental activity (such as Naval Air Systems Command, etc.). These listings should be included under the following paragraph:

"2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract."

The following types of publications should all be listed (as applicable) in the order shown after 2.1.1:

Federal Specifications
Federal Standards
Federal Information Processing Standards
Department of Defense Specifications
Department of Defense Standards
Department of Defense Handbooks

"2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this drawing to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract."

The following types of publications should be listed (as applicable) in the order shown after 2.1.2:

Other Government documents (e.g., Department of Transportation Specifications, U.S. Department of Agriculture Specifications, etc.)

Drawings
Publications

List only those documents that are applicable. Where detailed drawings referred to in an SMD are listed in an assembly drawing, it is only necessary to list the assembly drawing. The following parenthetical source paragraph is included at the end of 2.1.2:

"(Copies of specifications, standards, handbooks, drawings, publications, and other government documents required by contractors in connection with specified acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)"

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.

4.2.3.1.2 Non-Government standards and other publications. Non-Government standards and other publications including DoD adopted documents not normally furnished by the Government should be listed in appropriate order (numerically or alpha-numeric) under the headings of the respective non-Government standard bodies. Titles should be taken from the document rather than from an index. This listing is included under the following subparagraph.

"2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of documents are the issues of the documents cited in the solicitation."

In addition, the following parenthetical source statement follows each individual publication which may be obtained from a common source:

"(Application for copies should be addressed to the (name and address of the source.)"

The following source paragraph is placed at the bottom of the list when applicable.

"(Non-Government standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)"

4.2.3.1.3 Order of precedence. In order to avoid confusion in the possible conflict between the requirements of the drawing and the documents referenced therein, the following statement should be included:

"2.3 Order of precedence. In the event of a conflict between the text of this drawing and the reference cited herein the text of this drawing shall take precedence. Nothing in this document, however, supersedes applicable lows and regulations unless a specified exemption has been obtained. "

4.2.4 Section 3.

4.2.4.1 Requirements. Section 3 of the SMD states the necessary requirements (materials, physical and performance characteristics, processes, reliability, human factors, marking, workmanship, etc.) for obtaining the product which the SMD is prepared. The requirements should represent the actual essential needs of the Government to satisfy the intended use and application. Care should be exercised to ensure that the stated essential needs result in acquisition of acceptable quality products at the least life cycle cost to the Government. Requirements should be described in a manner to encourage competition and to avoid restrictive features which would limit acceptance to one or a relatively few contractors. Requirements should be so worded as to provide a definite basis for rejection when testing and examination of product reveals the product is unsuitable for the purpose intended. Care should be exercised to avoid unrealistic or ambiguous requirements and those which conflict with supplier capabilities and referenced documents.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.

4.2.4.1.1 Organization of requirements. Care should be taken to provide for a systematic arrangement of requirements to facilitate design, manufacturing, and inspections.

4.2.4.1.2 Sequencing of requirements and tests. When possible, the test paragraphs in section 4 should be placed in the same sequence as the requirement paragraph in section 3. An example of sequencing requirements and tests is as follows:

Requirement	Test
3.6 Shock	4.7.1 Shock
3.7 Vibration	4.7.2 Vibration
3.8 Noise	4.7.3 Noise
3.9 Electromagnetic interference	4.7.4 Electromagnetic interference

4.2.4.2 Materials. Requirements for materials to be used in the item(s) covered by the SMD are stated under this heading, except where it is more practical to include the information in other paragraphs. Requirements of general nature should be followed by specific requirements for the material. Definitive documents should be referenced for the material when such documents cover materials of the minimum required quality.

4.2.4.3 Design. The major functional characteristics should be specified. The intended use is covered in Section 6 of the SMD. Detailed design should be covered in individual paragraphs.

4.2.4.4 Construction. The specified points of construction should be included, as applicable. Construction requirements should be related to the physical limitations imposed and the stresses that equipment is expected to withstand.

4.2.4.5 Hardware. Standard military hardware should be designed into assemblies to the maximum extent possible. This includes mounting hardware when required to be furnished with the product. Selection of the hardware should be made from existing standards (such as MS, NAS, and AN standards), if possible, or from other standards required by contract.

4.2.4.6 Performance characteristics. General and detail performance characteristics should be included under this or other appropriate headings specifying what is expected of the commodity. Each requirement in Section 3 should have a corresponding test method in section 4. The requirement paragraph should reference the applicable test paragraph; "(see 4._)".

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.

4.2.4.7 Dimensions. Dimensions and tolerances will be in accordance with ASME Y14.5.

*

4.2.4.8 Finish. Finish should include such properties as surface roughness, freedom from burrs, corrosion, metallic and nonmetallic coatings.

4.2.4.9 Marking. Requirements for marking should reference MIL-PRF-38534 or MIL-PRF-38535. When section 3 specifies that certain item marking is to be placed on the unit container, section 5 should specify the container marking described. When part numbering is a requirement, the section 3 paragraph should reference section 1 paragraph or the appropriate appendix for a description of the part numbering scheme.

4.2.4.10 Selection of alternative materials, construction, etc. When alternate acceptable materials, construction, appearance, or other characteristics are stated in SMD's without specific provisions as to selectivity to be exercised in acquisition, the alternatives are to be considered interchangeable. In such cases, it should be clearly stated in the SMD that the selection of a specific alternative is at the option of the contractor.

4.2.4.11 Certificate of compliance. A certificate of compliance (see figure 3) is required from a manufacturer in order to be listed as a source of supply in MIL-HDBK-103 (see 4.2.7.4). The certificate of compliance submitted prior to listing as a source of supply should affirm that the manufacturer's product meets the requirements of the applicable specification (see 6.3).

4.2.4.12 Certificate of conformance. The certificate of conformance should be in accordance with the applicable general specification and should be provided with each lot of items delivered to the SMD.

4.2.4.13 Notification of change or discontinuance. Requirements for notification of change or discontinuance should reference MIL-PRF-38534 or MIL-PRF-38535.

4.2.4.14 Verification and review. The Government retains the option to review the device manufacturer's facility and applicable required documentation.

4.2.5 Section 4.

4.2.5.1 Verification. Section 4 should include all inspections (by reference when applicable) to be performed in order to determine that the item conforms to requirements of sections 3 and 5 of the SMD.

4.2.5.2 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for all inspection requirements specified. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the SMD where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.

4.2.5.3 Responsibility for compliance. All items must meet all requirements of sections 3 and 5 of the SMD. The inspection set forth in the SMD should become part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the SMD does not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in conformance inspection does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2.5.4 Conformance inspection. The tests listed in section 4 of the SMD to determine conformance with sections 3 and 5 requirements, should include, when necessary, a measurement or comparison with specified characteristics and checks and tests of the performance and reliability requirements. Each item must meet all sections 3 and 5 requirements. The test methods in section 4 of the SMD are minimum inspection and test methods to be used to document compliance to the SMD requirement.

4.2.5.4.1 Conformance inspection sampling. When it is desirable to specify the sampling procedure to be used by contractors for the performance of conformance inspection, the sampling procedure should:

a. Impose no inspection procedures that are less efficient and effective than would normally be used by the industry.

b. Clearly identify the sampling plan to be used in the manufacturing process when inspections are to be performed at intermediate points, as well as, on the end item.

c. Be capable of assuring compliance with requirements under various conditions of manufacturing or purchasing, e.g., mass or job lot production and large or small lot purchasing.

When inspections are to be based on lots of material, a definition of a lot size(s) should be furnished in this section by reference, if applicable. Restrictions concerning the formation of inspection lots such as restricting inspection lots of units of the same type, class, size, should be specified. Restriction of units forming the lot of those produced from the same assembly line, etc., should also be specified, when applicable.

4.2.5.5 Classification of conformance inspections. Conformance inspections should be classified into group A, B, C, D or E in accordance with the following groupings, when applicable:

Group A - Nondestructive inspections of all items produced or all samples from an inspection lot demonstrate product compliance with contractual requirements. Group A inspection examines characteristics most affected by variations in production processes or skills, and functions vital to successful completion of the design mission.

Group B - Generally nondestructive inspections that are more complex or of a longer duration than group A inspection. Group B inspection examines characteristics more affected by part or equipment quality and less affected by variations in production processes or skills, and functions requiring special fixtures or environments. Fewer samples are inspected than for group A inspections and test articles may be offered for acceptance with little or no refurbishment. Each commodity should be individually evaluated regarding its issue after performing group B and C inspections.

Group C - Periodic and generally destructive tests of characteristics depending upon product design and materials. Group C inspection consists of more complex tests, usually including emulated service environments, is generally destructive and may require major refurbishment before tested articles can be used by the services. Tests are based on production quantities or time period.

Group D - Destructive test or test of long duration that consumes all or a considerable portion of design service life. Articles subjected to group D inspection should not be issued. Tests are performed on few samples based on production quantities or time period.

* Group E – Radiation hardness assurance testing performed, generally as an option, to determine the levels of susceptibility for damages that would come from exposure to various doses of radiation. The testing is most commonly performed following burn-in.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.

4.2.5.6 Tabular listing of conformance inspection. Where it will lead to better understanding of their functions, the inspections should be listed as group A, B, C, D or E in tabular form with appropriate references to applicable requirements, and inspection methods in MIL-STD-883, MIL-PRF-38534, or MIL-PRF-38535 as illustrated below:

" 4.3 Conformance inspection. Conformance inspection shall be in accordance with method 5005 of MIL-STD-883 including groups A, B, C, and D inspections. The following additional criteria shall apply.

Test requirements	Subgroups (in accordance with MIL-STD-883, method 5005, table I)
Interim electrical parameters	
Final electrical test parameters	
Group A test requirements	
Groups C and D end-point electrical parameters	

"

4.2.6 Section 5.

4.2.6.1 Packaging, packing, and marking. Packaging, packing, and marking should be as specified in the applicable general specification.

4.2.7 Section 6.

4.2.7.1 Notes. Section 6 should contain information of a general or explanatory nature and no requirements should appear therein. It should contain information designed to assist in determining the applicability of the SMD.

4.2.7.2 Intended use. Items conforming to the SMD are intended for use for Government microcircuit applications (original equipment), design applications, and logistics purposes.

4.2.7.3 Comments. Comments on the SMD should be directed to the applicable MPCAG.

4.2.7.4 Sources of supply. Sources of supply will be identified in MIL-HDBK-103 (see 4.3) or the appropriate Qualified Manufacturers List (QML). The vendors so listed will have agreed to the SMD and submitted a certificate of compliance (see 4.2.4.11) and completed qualification requirements. Additional sources will be added to these listings as they become available.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.

4.3 Approved SMD's. SMD's in use by DoD and industry are listed in MIL-HDBK-103.

4.3.1 SMD user. When a contractor or DoD component has a system application for an existing SMD, as listed in MIL-HDBK-103, it is essential that the applicable MPCAG be informed accordingly.

4.3.2 Changes to SMD's. Utilizing user identification in accordance with MIL-HDBK-103, proposed changes or draft revisions are coordinated with all users of record. Changes are implemented in accordance with the provisions of MIL-PRF-38535. SMD's are maintained by the MPCAG. Approved revisions to SMD's are distributed by the MPCAG to all known users of record.

4.3.3 Nonconcurrence with proposed changes. User nonconcurrence with a proposed change to an SMD requires MPCAG resolution of the stated nonconcurrence. Unresolved nonconcurrence will require MPCAG action as appropriate, i.e., nonconcurrence reply, with technical justification, to the originator of the change proposal, new SMD's that address the diverse needs of the users involved, or advisory to user of need to generate new part acquisition documentation.

5. DETAILED GUIDANCE

5.1 Introduction. This section contains guidance for SMD's.

5.2 Drawing preparation. In coordination with and with the approval of the applicable Program Office, a MPCAG (see 3.3) will respond to a parts approval request with a drawing preparation package consisting of the following:

a. Drawing number

b. All known sources of supply

5.3 Initial drawing preparation.

5.3.1 Blank drawings. Blank drawings are not provided. Drawing format should be in conformance to figures 1 and 2.

5.3.2 SMD coordination. Preliminary draft coordinations with MPCAG and device manufacturers, comment resolution, certificate of compliance transmittal and final SMD preparation should be in conformance with figure 4.

5.3.3 Preliminary and final draft submittal. Preliminary draft will be typed and spaced in accordance with the drawing format (figures 1 and 2). Handwritten or pasted catalog excerpts are not acceptable. This preliminary draft may be on standard 8 1/2" x 11" paper. Once started by the contractor, it is expected that the process described herein will be completed. Preliminary drafts should be clearly marked preliminary draft on the first and last pages.

5.3.3.1 Preliminary draft construction. The preliminary draft is constructed through communication with the applicable MPCAG (see 6.2).

5.3.4 Maintenance. Maintenance of approved SMD's is the responsibility of the applicable MPCAG.

5.3.5 SMD content preparation. The following detail should be reviewed in conjunction with figure 5, especially regarding "boilerplate" location and content. The following detail reflects the current exclusive applicability of SMD's to Microcircuits.

5.3.5.1 Section 1, scope. 1. SCOPE should be as shown on figure 5 and conform to 4.2.2.1 as specified herein.

5.3.5.1.1 Scope. 1.1 Scope. should be as shown on figure 5.

5.3.5.1.2 PIN. The PIN should be structured in accordance with figure 5. The device type should be a two digit number, assigned sequentially, starting with 01, 02, 03, etc., depending upon how many parts are being included in the drawing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.

5.3.5.1.2.1 PIN length. The length of the PIN should comply with ASME Y14.100 and not exceed 32 characters.

5.3.5.1.3 Radiation hardness assurance (RHA) designator. Radiation hardness assurance should be as shown on figure 5 in 1.2.1.

5.3.5.1.4 Device type(s). Device type(s) should be as shown on figure 5 in 1.2.2.

5.3.5.1.5 Device class designator. The device class designator should be as shown on figure 5 in 1.2.3.

5.3.5.1.6 Case outline. The case outline(s) should be as shown on figure 5 in 1.2.4.

5.3.5.1.7 Lead finish. Lead finish should be as shown on figure 5 in 1.2.5.

5.3.5.1.8 Absolute maximum ratings.

a. The absolute maximum rating will be typed in two columns with dashes connecting as shown in the sample SMD, on figure 6.

b. The absolute maximum ratings will be as defined in the valid characterization data supplied by the manufacturer for the specific part and must include the thermal resistance, as specified in MIL-STD-1835 for the applicable case outline.

c. Foot notes referenced in this paragraph will be located at the bottom of the page.

5.3.5.1.9 Recommended operating conditions.

a. The recommended operating conditions will be typed in two columns with dashes connecting, as shown in the sample SMD, on figure 6.

b. The recommended operating conditions will be as defined in the valid characterization data supplied by the manufacturer for the specific part.

c. Foot notes referenced in paragraph 1.4 will be located at the bottom of the page.

5.3.5.2 SECTION 2, applicable documents. Section 2 should appear as shown on figure 5 and follow the guidelines of 4.2.3 as contained herein.

5.3.5.2.1 Order of precedence. Order of precedence should be as shown on figure 5 in 2.2 and 4.2.3.1.3 as specified herein.

5.3.5.3 Section 3, requirements. Section 3 should appear as shown on figure 5 and the guidelines furnished in 4.2.4. Specific requirement paragraphs should be included in an SMD or on an as required basis.

5.3.5.3.1 Item requirements. Item requirements should be as shown on figure 5 in 3.1.

5.3.5.3.2 Design, construction and physical dimensions. Design, construction and physical dimensions should be as shown on figure 5 in 3.2.

5.3.5.3.3 Terminal connections. Terminal connections should be as shown on figure 5 in 3.2.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.

5.3.5.3.4 Block diagram. Although figure 5, 3.2.4 specifies block diagram, this paragraph will be used to designate block, functional, or logic diagram, as appropriate, for the device being documented.

5.3.5.3.5 Truth tables. Truth tables should appear as on figure 5 in 3.2.3.

5.3.5.3.6 Case outline(s). Case outline(s) should appear as on figure 5 in 3.2.1.

5.3.5.3.7 Electrical performance characteristics and postirradiation parameter limits. Electrical performance characteristics should be as shown on figure 5 in 3.3. Valid characterization data supplied by the manufacture will determine the use of ambient or case operation temperature range.

5.3.5.3.8 Electrical test requirements. Electrical test requirements should be as shown on figure 5 in 3.4.

5.3.5.3.9 Marking. Marking should be as shown on figure 5 in 3.5.

5.3.5.3.10 Tables. Tables e.g., table I, electrical performance characteristics, should be as shown on figure 5. If necessary, a device type column may be added between the Conditions and group A subgroups column to accommodate differences in test conditions and limits, when more than one device type is being specified.

Required temperature parameters for each specific part will be typed under the heading Conditions, as shown on figure 5.

5.3.5.3.11 Graphics.

a. Views that are referenced as shown on figure 5 in 3.2, will be located after table 1.

b. All data necessary for terminal connections will be identified in a table format or be drawn as defined in MIL-STD-1835. Refer to sample SMD, figure 6.

c. Whenever two different case outlines are required, an additional page will be added to accommodate the required data with figure 1 continued.

d. All data necessary for additional views will be drawn as defined in MIL-PRF-38535. Refer to sample SMD, figure 6. Use valid characterization data supplied by the manufacturer for the specific device type.

e. Switching times test circuit and waveforms that are required will be drawn similar in format to that shown on the sample SMD, figure 6. Use valid characterization data supplied by the manufacturer for the specific device type.

5.3.5.3.12 Certificate of compliance. The certificate of compliance execution should be as shown on figure 5 in 3.6.

5.3.5.3.13 Certificate of conformance. The certificate of conformance should be as shown on figure 5 in 3.7.

5.3.5.3.14 Notification of change. Notification of change should be as shown on figure 5 in 3.8.

5.3.5.3.15 Verification of change. Verification of change should be as shown on figure 5 in 3.9.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.

5.3.6 Section 4, verfication. Section 4 should appear as shown on figure 5 and 4.2.5 as contained herein.

5.3.6.1 Sampling and inspection. Sampling and inspection should be as shown on figure 5 in 4.1.

5.3.6.2 Screening. Screening should be as shown on figure 5 in 4.2. Valid characterization data supplied by the manufacturer will be used for figure 5, 4.2.1a and 4.2.1b.

5.3.6.3 Qualification inspection. Qualification inspection should be as shown on figure 5 in 4.3.

5.3.6.4 Conformance inspection. Conformance inspection should be as shown on figure 5 in 4.4 and the guidance contained in 4.2.5.4 herein.

5.3.6.4.1 Group A inspection. Additional group A inspection requirements should be as shown on figure 5 in 4.4.1. Valid characterization data supplied by the manufacturer will be used for 4.4.1 subparagraphs (see figure 5).

5.3.6.4.2 Group C inspection. Additional group C inspection requirements should be as shown on figure 5 in 4.4.2. Valid characterization data supplied by the manufacturer will be used for 4.4.2 subparagraphs (see figure 5).

5.3.6.4.3 Group D inspection. Additional group D inspection requirements should be as shown on figure 5 in 4.4.3.

5.3.6.4.4 Group E inspection. Additional group E inspection requirements should be as shown on figure 5 in 4.4.4. Valid characterization data supplied by the manufacturer will be used for 4.4.4 subparagraphs.

5.3.6.5 Tables, electrical tests.

a. The table of electrical test requirements will be formatted as shown on figure 5, table II.

b. The identification of subgroups and tests will be defined in the applicable general specification and valid characterization data supplied by the manufacturer.

c. Any footnote referenced in the table will be located a minimum of two line spaces below the bottom line of the table.

d. Notes using the term guaranteed will not be included as a part of the preliminary draft, before submittal to the sources of supply.

5.3.7 Section 5, packaging. Section 5 should appear as shown on figure 5 and the guidance indicated in 4.2.6.1 as specified herein.

5.3.7.1 Packaging requirements. The packaging requirements should be as shown on figure 5 in 5.1.

5.3.8 Section 6, notes. Section 6 should appear as shown on figure 5 and the guidance in 4.2.7 as specified herein.

5.3.8.1 Intended use. The intended use should be as shown on figure 5 in 6.1 and the guidance in 4.2.7.2 as specified herein.

5.3.8.1.1 Replaceability. The replaceability should be as shown on figure 5 in 6.1.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.

5.3.8.1.2 Substitutability. The substitutability should be as shown on figure 5 in 6.1.2.

5.3.8.2 Configuration control of SMD's. The configuration control of SMD's should be as shown on figure 5 in 6.2.

5.3.8.3 Record of users. The record of users should be as shown on figure 5 in 6.3.

5.3.8.4 Comments. The comments should be as shown on figure 5 in 6.4.

5.3.8.5 Abbreviations, symbols, and definitions. The abbreviations, symbols, and definitions should be as shown on figure 5 in 6.5.

5.3.8.6 Sources of supply. The sources of supply paragraph should be as shown on figure 5 in 6.6.

6. NOTES

6.1 Intended use. The issue of SMD's is intended to minimize the proliferation of duplicate drawings for an item of supply. The use of one drawing for an item of supply within DoD is the objective of the SMD program. SMD's are currently applicable to the acquisition of microcircuits only.

6.1.1 Standard microcircuit drawing program (SMDP). The SMDP is related to the Configuration Management and Parts Management Programs. SMDs are recognized in ASME Y14.100 for application by the DoD for microcircuits
* compliant with MIL-STD-883. Non-standard microcircuits parts approval is obtained through the procedures of MIL-STD-3018 and SD-19.

6.2 Draft construction. Communication with the MPCAG point of contact for the purpose of draft SMD construction
* will usually be through use of computer or word processor. DLA Land and Maritime - VA, should be contacted concerning system capability, and modem and telecommunication compatibility (see figure 4).


6.3 Certificate of compliance. A Certificate of Compliance (C of C) is a document by which an authorized official of the microcircuit manufacturer certifies that the microcircuit being supplied in accordance with the applicable SMD by the vendor meets the Item Requirements as stated therein. The C of C is delivered by the vendor to the MPCAG with the final SMD.

6.4 Subject term (key word) listing.

Certificate of compliance
Military parts control advisory group
Parts Management program
Standard microcircuit drawing
Qualified manufacturers list

* 6.5 Change notations. The left margins of this handbook are marked with asterisks to indicate modifications generated by this change. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.



REVISIONS			
LTR	DESCRIPTION	DATE (YR-MO-DA)	APPROVED

REV																			
SHEET																			
REV																			
SHEET	15	16	17																
REV STATUS				REV															
OF SHEETS				SHEET	1	2	3	4	5	6	7	8	9	10	11	12	13	14	


PMIC N/A	PREPARED BY Your name here	DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990 http://www.landandmaritime.dla.mil
STANDARD MICROCIRCUIT DRAWING THIS DRAWING IS AVAILABLE FOR USE BY ALL DEPARTMENTS AND AGENCIES OF THE DEPARTMENT OF DEFENSE AMSC N/A	CHECKED BY APPROVED BY DRAWING APPROVAL DATE REVISION LEVEL	MICROCIRCUIT, DIGITAL, MONOLITHIC SILICON SIZE A | CAGE CODE 67268 | 5962-XXXXX SHEET 1 OF XX

DSCC FORM 2233
APR 97

5962-EXXXX

* FIGURE 1. Drawing, title sheet.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.



* FIGURE 2. Drawing, continuation sheet.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.

FOR DEVICE CLASSES M, N, Q, T, or V

STANDARD MICROCIRCUIT DRAWING NUMBER _____ REV _____ DLA Land and Maritime -VA Contact _____
Telephone: (614) 692-

CERTIFICATE OF COMPLIANCE

MANUFACTURER'S NAME, LOCATION AND CAGE CODE: _____

I (We) have reviewed the enclosed drawing and hereby certify that our MIL-PRF-38535 compliant device(s) or MIL-STD-883 compliant device(s), listed below, meet the requirements of the SMD (The SMD Part Number includes the drawing number, rad hard designator, device type, class designator, case outline, and lead finish designator):

SMD Part Number	Vendor Part Number

(Use a C of C Continuation Sheet if more than 5 part numbers are on the SMD.)

and fabricated, assembled and tested at our plant(s) located in:

Fabrication location(s) : _____
Assembly location(s): _____
Test location(s): _____

PART MEETS OR EXCEEDS THE PERFORMANCE REQUIREMENT OF THE DRAWING/SPECIFICATION EITHER:

☐ as proposed or ☐ with essential comments as marked on draft

PART HAS COMPLETED CONVERSION OF CUSTOMER REQUIREMENTS AND IS COVERED BY
CERTIFICATION AND QUALIFICATION TO MIL-PRF-38535 ☐ YES ☐ NO
or
COMPLIANCE TO MIL-STD-883 (APPENDIX A OF MIL-PRF-38535) ☐ YES ☐ NO

DEVICE CLASS LEVEL: ☐ N ☐ Q ☐ T ☐ V CERTIFICATION MARK: ☐ Q/QML ☐ QD
or
DEVICE CLASS LEVEL: ☐ M COMPLIANCE MARK: ☐ C ☐ D

BURN-IN CIRCUIT IS UNDER DOCUMENT CONTROL AND AVAILABLE UPON REQUEST: ☐ YES ☐ NO

RHA MAXIMUM TOTAL DOSE VALUE: ☐ N/A ☐ M ☐ D ☐ P ☐ L ☐ R ☐ F ☐ G ☐ H

ESD CLASS FOR NEW/REQUALIFIED DEVICES: ☐ 0 ☐ 1A ☐ 1B ☐ 1C ☐ 2 ☐ 3A ☐ 3B
(AS OF 10 SEPT 06)

or

ESD CLASS and VOLTAGE FOR EXISTING DEVICES: ☐ 1 ☐ 2 ☐ 3 VOLTAGE LEVEL: _____
(NO REQUALIFICATION REQUIRED AT THIS TIME)

I (We) understand that this certificate is not to be used nor construed as a guarantee of continued or indefinite availability as an Approved Source for the described drawing item. I further understand that this certificate does not relieve this company from conducting the required testing and lot record keeping detailed in the drawing/specification. I further agree that our company will furnish a separate certificate of conformance in company format, pertaining to actual lot date codes shipped.

_____ Authorized Signature(s)

_____ Date

_____ Name and Title of Authorizing Official (shall be typed)

( ) - _____ Telephone

Submittal of this information to DLA Land and Maritime-VA does not relieve the device manufacturer of the requirements of MIL-PRF-38535. This dated C of C form (3 August 2010) shall not be modified. Modification may result in no acceptance.

* Figure 3. Certificate of Compliance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.

CERTIFICATE OF COMPLIANCE CONTINUATION SHEET
FOR DEVICE CLASSES M, N, Q, T or V

STANDARD MICROCIRCUIT DRAWING _____ REV _____ DLA Land and Maritime-VA Contact Telephone:(614)692-

Date :

I (We) have reviewed the enclosed drawing and hereby certify that our MIL-PRF-38535 compliant device(s), listed below meet the requirements of the SMD (The SMD Part Number includes the drawing number, rad hard designator, device type, class designator, case outline, and lead finish designator):

SMD Part Number	Vendor Part Number

This Continuation Sheet shall be used only if the subject SMD has more than 5 part numbers. This sheet must be accompanied by a completed Certificate of Conformance (C of C) form (3 August 2010). If necessary, this sheet may be duplicated and used as needed for each C of C.

* FIGURE 3. Certificate of Compliance - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.

Authorization Criteria
Standard Microcircuit Drawing
Certificate of Compliance
Dated 3 August 2010

The authorized signature shall provide certification signed by the corporate officer responsible for the production of the C of C described product. The responsible corporate officer may delegate authority to sign the C of C to specific individuals within the cognizant quality assurance organization. However, the corporate officer retains responsibility for the accuracy of the C of C.

When authority to sign a C of C is delegated, the responsible corporate office shall submit a letter to DLA Land and Maritime - VA which identifies the name, address, phone number and title of the individual having been granted signature authority.

.

* FIGURE 3. Certificate of Compliance. - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.




FIGURE 4. SMD preparation flowchart.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.





FIGURE 4. SMD preparation flowchart - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.

1. SCOPE

1.1 Scope. This drawing documents two product assurance class levels consisting of high reliability (device classes Q and M) and space application (device class V). A choice of case outlines and lead finishes are available and are reflected in the Part or Identifying Number (PIN). When available, a choice of Radiation Hardness Assurance (RHA) levels is reflected in the PIN.

1.2 PIN. The PIN is as shown in the following example:



1.2.1 RHA designator. Device classes Q and V RHA marked devices meet the MIL-PRF-38535 specified RHA levels and are marked with the appropriate RHA designator. Device class M RHA marked devices meet the MIL-PRF-38535, appendix A specified RHA levels and are marked with the appropriate RHA designator. A dash (-) indicates a non-RHA device.

1.2.2 Device type(s). The device type(s) identify the circuit function as follows:

Device type	Generic number	Circuit function
01	XXXXXX	XXXXXXXXXXXXXXXXXXXXXXXXXXXX

1.2.3 Device class designator. The device class designator is a single letter identifying the product assurance level as follows:

Device class	Device requirements documentation
M	Vendor self-certification to the requirements for MIL-STD-883 compliant, non-JAN class level B microcircuits in accordance with MIL-PRF-38535, appendix A
Q or V	Certification and qualification to MIL-PRF-38535

1.2.4 Case outline(s). The case outline(s) are as designated in MIL-STD-1835 and as follows:

Outline letter	Descriptive designator	Terminals	Package style
X	XXXXXXXX	XX	XXXXXXXXXXXXXXXXXXXXXXXX

1.2.5 Lead finish. The lead finish is as specified in MIL-PRF-38535 for device classes Q and V or MIL-PRF-38535, appendix A for device class M.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-XXXXX
		REVISION LEVEL	SHEET 2

DSCC FORM 2234
APR 97

* FIGURE 5. SMD with boilerplate.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.

1.3 Absolute maximum ratings. 1/

1.4 Recommended operating conditions.

1.5 Radiation features.

Maximum total dose available (dose rate = 50 – 300 rads(Si)/s) ..... _____ rads(Si)

Note: All RHA tests performed need to be specified in 1.5 and/or paragraph 4.4.4. Make sure the manufacturer is performing the test if it is specified as such in 4.4.4.

2. APPLICABLE DOCUMENTS

2.1 Government specification, standards, and handbooks. The following specification, standards, and handbooks form a part of this drawing to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATION

MIL-PRF-38535 - Integrated Circuits, Manufacturing, General Specification for.

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-883 - Test Method Standard Microcircuits.
MIL-STD-1835 - Interface Standard Electronic Component Case Outlines.

DEPARTMENT OF DEFENSE HANDBOOKS

MIL-HDBK-103 - List of Standard Microcircuit Drawings.
MIL-HDBK-780 - Standard Microcircuit Drawings.

(Copies of these documents are available online at https://assist.daps.dla.mil/quicksearch/ or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

2.2 Order of precedence. In the event of a conflict between the text of this drawing and the references cited herein, the text of this drawing takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

1/ Stresses above the absolute maximum rating may cause permanent damage to the device. Extended operation at the maximum levels may degrade performance and affect reliability.

* FIGURE 5. SMD with boilerplate - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Item requirements. The individual item requirements for device classes Q and V shall be in accordance with MIL-PRF-38535 as specified herein, or as modified in the device manufacturer's Quality Management (QM) plan. The modification in the QM plan shall not affect the form, fit, or function as described herein. The individual item requirements for device class M shall be in accordance with MIL-PRF-38535, appendix A for non-JAN class level B devices and as specified herein.

3.2 Design, construction, and physical dimensions. The design, construction, and physical dimensions shall be as specified in MIL-PRF-38535 and herein for device classes Q and V or MIL-PRF-38535, appendix A and herein for device class M.

3.2.1 Case outline(s). The case outline(s) shall be in accordance with 1.2.4 herein and figure ___.

3.2.2 Terminal connections. The terminal connections shall be as specified on figure ___.

3.2.3 Truth table(s). The truth table(s) shall be as specified on figure ___.

3.2.4 Block or logic diagram(s). The block or logic diagram(s) shall be as specified on figure ___.

3.2.5 Radiation exposure circuit. The radiation exposure circuit shall be as specified on figure ___.
or
3.2.5 Radiation exposure circuit. The radiation exposure circuit shall be maintained by the manufacturer under document revision level control and shall be made available to the preparing and acquiring activity upon request.

3.3 Electrical performance characteristics and postirradiation parameter limits. Unless otherwise specified herein, the electrical performance characteristics and postirradiation parameter limits are as specified in table I and shall apply over the full case operating temperature range.

3.4 Electrical test requirements. The electrical test requirements shall be the subgroups specified in table II. The electrical tests for each subgroup are defined in table I.

3.5 Marking. The part shall be marked with the PIN listed in 1.2 herein. In addition, the manufacturer's PIN may also be marked. For packages where marking of the entire SMD PIN number is not feasible due to space limitations, the manufacturer has the option of not marking the "5962-" on the device. For RHA product using this option, the RHA designator shall still be marked. Marking for device classes Q and V shall be in accordance with MIL-PRF-38535. Marking for device class M shall be in accordance with MIL-PRF-38535, appendix A.

3.5.1 Certification/compliance mark. The certification mark for device classes Q and V shall be a "QML" or "Q" as required in MIL-PRF-38535. The compliance mark for device class M shall be a "C" as required in MIL-PRF-38535, appendix A.

3.6 Certificate of compliance. For device classes Q and V, a certificate of compliance shall be required from a QML-38535 listed manufacturer in order to supply to the requirements of this drawing (see 6.6.1 herein). For device class M, a certificate of compliance shall be required from a manufacturer in order to be listed as an approved source of supply in MIL-HDBK-103 (see 6.6.2 herein). The certificate of compliance submitted to DLA Land and Maritime-VA prior to listing as an approved source of supply for this drawing shall affirm that the manufacturer's product meets, for device classes Q and V, the requirements of MIL-PRF-38535 and herein or for device class M, the requirements of MIL-PRF-38535, appendix A and herein.

3.7 Certificate of conformance. A certificate of conformance as required for device classes Q and V in MIL-PRF-38535 or for device class M in MIL-PRF-38535, appendix A shall be provided with each lot of microcircuits delivered to this drawing.

3.8 Notification of change for device class M. For device class M, notification to DLA Land and Maritime -VA of change of product (see 6.2 herein) involving devices acquired to this drawing is required for any change that affects this drawing.

3.9 Verification and review for device class M. For device class M, DLA Land and Maritime, DLA Land and Maritime's agent, and the acquiring activity retain the option to review the manufacturer's facility and applicable required documentation. Offshore documentation shall be made available onshore at the option of the reviewer.

3.10 Microcircuit group assignment for device class M. Device class M devices covered by this drawing shall be in microcircuit group number xxx (see MIL-PRF-38535, appendix A).

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-XXXXX
		REVISION LEVEL	SHEET 4

DSCC FORM 2234
APR 97

* FIGURE 5. SMD with boilerplate - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical performance characteristics.

Test	Symbol	Conditions $-55°C \le T_C \le +125°C$ unless otherwise specified	Group A subgroups	Device type	Limits		Unit
					Min	Max	

See footnotes at end of table.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-XXXXX
		REVISION LEVEL	SHEET 5

DSCC FORM 2234
APR 97

* FIGURE 5. SMD with boilerplate - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.

FIGURE 1. Case outline.

FIGURE 2. Terminal connections.

FIGURE 3. Truth table.

FIGURE 4. Block diagram.

FIGURE 5. Timing waveforms.

FIGURE 5. Radiation exposure circuit.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-XXXXX
		REVISION LEVEL	SHEET 6

DSCC FORM 2234
APR 97

* FIGURE 5. SMD with boilerplate - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.

4. VERIFICATION

4.1 Sampling and inspection. For device classes Q and V, sampling and inspection procedures shall be in accordance with MIL-PRF-38535 or as modified in the device manufacturer's Quality Management (QM) plan. The modification in the QM plan shall not affect the form, fit, or function as described herein. For device class M, sampling and inspection procedures shall be in accordance with MIL-PRF-38535, appendix A.

4.2 Screening. For device classes Q and V, screening shall be in accordance with MIL-PRF-38535, and shall be conducted on all devices prior to qualification and technology conformance inspection. For device class M, screening shall be in accordance with method 5004 of MIL-STD-883, and shall be conducted on all devices prior to quality conformance inspection.

4.2.1 Additional criteria for device class M.

a. Burn-in test, method 1015 of MIL-STD-883.

(1) Test condition or . The test circuit shall be maintained by the manufacturer under document revision level control and shall be made available to the preparing or acquiring activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in method 1015 of MIL-STD-883.

(2) T_A = +125°C, minimum.

b. Interim and final electrical test parameters shall be as specified in table II herein.

4.2.2 Additional criteria for device classes Q and V.

a. The burn-in test duration, test condition and test temperature, or approved alternatives shall be as specified in the device manufacturer's QM plan in accordance with MIL-PRF-38535. The burn-in test circuit shall be maintained under document revision level control of the device manufacturer's Technology Review Board (TRB) in accordance with MIL-PRF-38535 and shall be made available to the acquiring or preparing activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in method 1015 of MIL-STD-883.

b. Interim and final electrical test parameters shall be as specified in table II herein.

c. Additional screening for device class V beyond the requirements of device class Q shall be as specified in MIL-PRF-38535, appendix B.

4.3 Qualification inspection for device classes Q and V. Qualification inspection for device classes Q and V shall be in accordance with MIL-PRF-38535. Inspections to be performed shall be those specified in MIL-PRF-38535 and herein for groups A, B, C, D, and E inspections (see 4.4.1 through 4.4.4).

4.4 Conformance inspection. Technology conformance inspection for classes Q and V shall be in accordance with MIL-PRF-38535 including groups A, B, C, D, and E inspections and as specified herein. Quality conformance inspection for device class M shall be in accordance with MIL-PRF-38535, appendix A and as specified herein. Inspections to be performed for device class M shall be those specified in method 5005 of MIL-STD-883 and herein for groups A, B, C, D, and E inspections (see 4.4.1 through 4.4.4).

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-XXXXX
		REVISION LEVEL	SHEET 7

DSCC FORM 2234
APR 97

* FIGURE 5. SMD with boilerplate - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.

4.4.1 Group A inspection.

a. Tests shall be as specified in table II herein.

b. For device class M, subgroups 7 and 8 tests shall be sufficient to verify the truth table. For device classes Q and V, subgroups 7 and 8 shall include verifying the functionality of the device.

TABLE II. Electrical test requirements.

Test requirements	Subgroups (in accordance with MIL-STD-883, method 5005, table I)	Subgroups (in accordance with MIL-PRF-38535, table III)	
	Device class M	Device class Q	Device class V
Interim electrical parameters (see 4.2)			
Final electrical parameters (see 4.2)	1/	1/	2/
Group A test requirements (see 4.4)			
Group C end-point electrical parameters (see 4.4)			
Group D end-point electrical parameters (see 4.4)			
Group E end-point electrical parameters (see 4.4)			

1/ PDA applies to subgroup 1.
2/ PDA applies to subgroups 1 and 7.

4.4.2 Group C inspection. The group C inspection end-point electrical parameters shall be as specified in table II herein.

4.4.2.1 Additional criteria for device class M. Steady-state life test conditions, method 1005 of MIL-STD-883:

a. Test condition or . The test circuit shall be maintained by the manufacturer under document revision level control and shall be made available to the preparing or acquiring activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in method 1005 of MIL-STD-883.

b. T_A = +125°C, minimum.

c. Test duration: 1,000 hours, except as permitted by method 1005 of MIL-STD-883.

4.4.2.2 Additional criteria for device classes Q and V. The steady-state life test duration, test condition and test temperature, or approved alternatives shall be as specified in the device manufacturer's QM plan in accordance with MIL-PRF-38535. The test circuit shall be maintained under document revision level control by the device manufacturer's TRB in accordance with MIL-PRF-38535 and shall be made available to the acquiring or preparing activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in method 1005 of MIL-STD-883.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-XXXXX
		REVISION LEVEL	SHEET 8

DSCC FORM 2234
APR 97

* FIGURE 5. SMD with boilerplate - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.

4.4.3 Group D inspection. The group D inspection end-point electrical parameters shall be as specified in table II herein.

4.4.4 Group E inspection. Group E inspection is required only for parts intended to be marked as radiation hardness assured (see 3.5 herein).

a. End-point electrical parameters shall be as specified in table II herein.

b. For device classes Q and V, the devices or test vehicle shall be subjected to radiation hardness assured tests as specified in MIL-PRF-38535 for the RHA level being tested. For device class M, the devices shall be subjected to radiation hardness assured tests as specified in MIL-PRF-38535, appendix A for the RHA level being tested. All device classes must meet the postirradiation end-point electrical parameter limits as defined in table I at T_A = +25°C ±5°C, after exposure, to the subgroups specified in table II herein.

Note: All radiation testing being performed must be specified in 4.4.4.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-PRF-38535 for device classes Q and V or MIL-PRF-38535, appendix A for device class M.

6. NOTES

6.1 Intended use. Microcircuits conforming to this drawing are intended for use for Government microcircuit applications (original equipment), design applications, and logistics purposes.

6.1.1 Replaceability. Microcircuits covered by this drawing will replace the same generic device covered by a contractor prepared specification or drawing.

6.1.2 Substitutability. Device class Q devices will replace device class M devices.

6.2 Configuration control of SMD's. All proposed changes to existing SMD's will be coordinated with the users of record for the individual documents. This coordination will be accomplished using DD Form 1692, Engineering Change Proposal.

6.3 Record of users. Military and industrial users should inform DLA Land and Maritime when a system application requires configuration control and which SMD's are applicable to that system. DLA Land and Maritime will maintain a record of users and this list will be used for coordination and distribution of changes to the drawings. Users of drawings covering microelectronic devices (FSC 5962) should contact DLA Land and Maritime -VA, telephone (614) 692-0547.

6.4 Comments. Comments on this drawing should be directed to DLA Land and Maritime -VA, Columbus, Ohio 43218-3990, or telephone (614) 692-0540.

6.5 Abbreviations, symbols, and definitions. The abbreviations, symbols, and definitions used herein are defined in MIL-PRF-38535 and MIL-HDBK-1331.

6.6 Sources of supply.

6.6.1 Sources of supply for device classes Q and V. Sources of supply for device classes Q and V are listed in QML-38535. The vendors listed in QML-38535 have submitted a certificate of compliance (see 3.6 herein) to DLA Land and Maritime -VA and have agreed to this drawing.

6.6.2 Approved sources of supply for device class M. Approved sources of supply for class M are listed in MIL-HDBK-103. The vendors listed in MIL-HDBK-103 have agreed to this drawing and a certificate of compliance (see 3.6 herein) has been submitted to and accepted by DLA Land and Maritime -VA.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-XXXXX
		REVISION LEVEL	SHEET 9

DSCC FORM 2234
APR 97

* FIGURE 5. SMD with boilerplate - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.

REVISIONS

LTR	DESCRIPTION	DATE (YR-MO-DA)	APPROVED
A	Add device class V devices and Table IIB. - ro	05-08-02	R. MONNIN
B	Add 1.5 and 3.2.3 for radiation hardened requirements. Make changes to 1.2, Table I, Table IIA, 4.4.4, and add 4.4.4.1. - ro	05-10-25	R. MONNIN
C	Update drawing as part of 5 year review. jt	10-09-22	C. SAFFLE
D	Add device type 02. Add enhanced low dose rate sensitivity (ELDRS) free requirements. Delete footnote 2/ from final electrical row as specified under Table IIA - ro	11-07-19	C. SAFFLE

REV																			
SHEET																			
REV																			
SHEET																			
REV STATUS	REV	D	D	D	D	D	D	D	D	D	D	D							
OF SHEETS	SHEET	1	2	3	4	5	6	7	8	9	10	11							

PMIC N/A

PREPARED BY
GLENN TRAYLOR

DLA LAND AND MARITIME
COLUMBUS, OHIO 43218-3990
http://www.landandmaritime.dla.mil

STANDARD MICROCIRCUIT DRAWING

THIS DRAWING IS AVAILABLE FOR USE BY ALL DEPARTMENTS AND AGENCIES OF THE DEPARTMENT OF DEFENSE

CHECKED BY
RAJESH R. PITHADIA

APPROVED BY
RAYMOND MONNIN

DRAWING APPROVAL DATE
04-03-04

MICROCIRCUIT, LINEAR, ULTRA LOW DISTORTION, CURRENT FEEDBACK WIDEBAND, OPERATIONAL AMPLIFIER, MONOLITHIC SILICON

AMSC N/A

REVISION LEVEL
D

SIZE	CAGE CODE	
A	67268	5962-02546

SHEET 1 OF 11

DSCC FORM 2233
APR 97

5962-E419-11


* FIGURE 6. Sample SMD.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.

1. SCOPE

1.1 Scope. This drawing documents two product assurance class levels consisting of high reliability (device classes Q and M) and space application (device class V). A choice of case outlines and lead finishes are available and are reflected in the Part or Identifying Number (PIN). When available, a choice of Radiation Hardness Assurance (RHA) levels is reflected in the PIN.

1.2 PIN. The PIN is as shown in the following example:



1.2.1 RHA designator. Device classes Q and V RHA marked devices meet the MIL-PRF-38535 specified RHA levels and are marked with the appropriate RHA designator. Device class M RHA marked devices meet the MIL-PRF-38535, appendix A specified RHA levels and are marked with the appropriate RHA designator. A dash (-) indicates a non-RHA device.

1.2.2 Device type(s). The device type(s) identify the circuit function as follows:

Device type	Generic number	Circuit function
01	LMH6702	Ultra low distortion, current feedback wideband, operational amplifier
02	LMH6702	Ultra low distortion, current feedback wideband, operational amplifier

1.2.3 Device class designator. The device class designator is a single letter identifying the product assurance level as follows:

Device class	Device requirements documentation
M	Vendor self-certification to the requirements for MIL-STD-883 compliant, non-JAN class level B microcircuits in accordance with MIL-PRF-38535, appendix A
Q or V	Certification and qualification to MIL-PRF-38535

1.2.4 Case outline(s). The case outline(s) are as designated in MIL-STD-1835 and as follows:

Outline letter	Descriptive designator	Terminals	Package style
P	GDIP1-T8 or CDIP2-T8	8	Dual-in-line
Z	GDFP1-G10	10	Flat pack with gullwing leads

1.2.5 Lead finish. The lead finish is as specified in MIL-PRF-38535 for device classes Q and V or MIL-PRF-38535, appendix A for device class M.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-02546
		REVISION LEVEL D	SHEET 2

DSCC FORM 2234
APR 97

* FIGURE 6. Sample SMD - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.

1.3 Absolute maximum ratings. 1/

Supply voltage (V_{CC})	±6.75 V dc
Common mode input voltage (V_{CM})	V- to V+
Power dissipation (P_D) 2/	1 W
Junction temperature (T_J)	+175°C
Lead temperature (soldering, 10 seconds) (T_L)	300°C
Storage temperature range	-65°C ≤ T_A ≤ +150°C
Thermal resistance, junction-to-ambient (θ_{JA}):	
Case P	170°C/W (still air)
	100°C/W (500 linear feet per min air flow)
Case Z	220°C/W (still air)
	150°C/W (500 linear feet per min air flow)
Thermal resistance, junction-to-case (θ_{JC}):	
Case P	35°C/W
Case Z	37°C/W

1.4 Recommended operating conditions.

Supply voltage (V_{CC})	±5 V dc to ±6 V dc
Gain range	±1 to ±10
Ambient operating temperature range (T_A)	-55°C to +125°C

1.5 Radiation features. 3/

Maximum total dose available (dose rate = 50 – 300 rads(Si)/s) :	
Device type 01	300 krads (Si)
Maximum total dose available (dose rate = 10 mrad(Si)/s):	
Device type 02	300 krads (Si)

For device type 02, the manufacturer supplying RHA parts on this drawing has performed a characterization test to demonstrate that the parts do not exhibit enhanced low dose rate sensitivity (ELDRS) according to MIL-STD-883 method 1019 paragraph 3.13.1.1. Therefore device 02 may be considered ELDRS free. Since the redesigned part did not demonstrate ELDRS per method 1019 and the 01 device may exhibit ELDRS, device type 02 will be added to distinguish it from the 01 device.

1/ Absolute maximum ratings are limits beyond which damage to the device may occur. Operating ratings are conditions for which the device is functional, but do not guarantee specific performance limits. For guaranteed specifications and test conditions see the electrical characteristics. The guaranteed specification apply only for the test conditions listed. Some performance characteristics may degrade when the device is not operated under the listed test conditions.

2/ The maximum power dissipation must be derated at elevated temperatures and is dictated by T_{JMAX} (maximum junction temperature), θ_{JA} (package junction to ambient thermal resistance), and T_A (ambient temperature). The maximum allowable power dissipation at any temperature is $P_{DMAX} = (T_{JMAX} - T_A) / \theta_{JA}$ or the number given in the absolute maximum ratings, whichever is lower.

3/ For device type 01, this part may be dose rate sensitive in a space environment and may demonstrate enhanced low dose rate effects. Radiation end point limits for the noted parameters are guaranteed only for the conditions as specified in MIL- STD-883, method 1019, condition A. For device type 02, this part has been tested and does not demonstrate low dose rate sensitivity. Radiation end point limits for the noted parameters are guaranteed for the conditions specified in MIL-STD-883, method 1019, condition D.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-02546
		REVISION LEVEL D	SHEET 3

DSCC FORM 2234
APR 97

* FIGURE 6. Sample SMD – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Government specification, standards, and handbooks. The following specification, standards, and handbooks form a part of this drawing to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATION

MIL-PRF-38535 - Integrated Circuits, Manufacturing, General Specification for.

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-883 - Test Method Standard Microcircuits.
MIL-STD-1835 - Interface Standard Electronic Component Case Outlines.

DEPARTMENT OF DEFENSE HANDBOOKS

MIL-HDBK-103 - List of Standard Microcircuit Drawings.
MIL-HDBK-780 - Standard Microcircuit Drawings.

(Copies of these documents are available online at https://assist.daps.dla.mil/quicksearch/ or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

2.2 Order of precedence. In the event of a conflict between the text of this drawing and the references cited herein, the text of this drawing takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Item requirements. The individual item requirements for device classes Q and V shall be in accordance with MIL-PRF-38535 and as specified herein or as modified in the device manufacturer's Quality Management (QM) plan. The modification in the QM plan shall not affect the form, fit, or function as described herein. The individual item requirements for device class M shall be in accordance with MIL-PRF-38535, appendix A for non-JAN class level B devices and as specified herein.

3.2 Design, construction, and physical dimensions. The design, construction, and physical dimensions shall be as specified in MIL-PRF-38535 and herein for device classes Q and V or MIL-PRF-38535, appendix A and herein for device class M.

3.2.1 Case outline. The case outline shall be in accordance with 1.2.4 herein.

3.2.2 Terminal connections. The terminal connections shall be as specified on figure 1.

3.2.3 Radiation exposure circuit. The radiation exposure circuit shall be maintained by the manufacturer under document revision level control and shall be made available to the preparing and acquiring activity upon request.

3.3 Electrical performance characteristics and postirradiation parameter limits. Unless otherwise specified herein, the electrical performance characteristics and postirradiation parameter limits are as specified in table I and shall apply over the full ambient operating temperature range.

3.4 Electrical test requirements. The electrical test requirements shall be the subgroups specified in table IIA. The electrical tests for each subgroup are defined in table I.

3.5 Marking. The part shall be marked with the PIN listed in 1.2 herein. In addition, the manufacturer's PIN may also be marked. For packages where marking of the entire SMD PIN is not feasible due to space limitations, the manufacturer has the option of not marking the "5962-" on the device. For RHA product using this option, the RHA designator shall still be marked. Marking for device classes Q and V shall be in accordance with MIL-PRF-38535. Marking for device class M shall be in accordance with MIL-PRF-38535, appendix A.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-02546
		REVISION LEVEL D	SHEET 4

DSCC FORM 2234
APR 97

* FIGURE 6. Sample SMD - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical performance characteristics.

Test	Symbol	Conditions 1/ 2/ 3/ $-55°C \le T_A \le +125°C$ unless otherwise specified	Group A subgroups	Device type	Limits 4/ Min	Limits 4/ Max	Unit
DC parameters							
Input bias current, noninverting	I_{BN}		1, 2	01,02	-15	15	µA
			3		-21	21	
		M,D,P,L,R,F	1		-15	15	
Input bias current, inverting	I_{BI}		1, 2	01,02	-30	30	µA
			3		-34	34	
		M,D,P,L,R,F	1		-30	30	
Input offset voltage	V_{IO}		1, 3	01,02	-4.5	4.5	mV
			2		-6.0	6.0	
		M,D,P,L,R,F	1		-4.5	4.5	
Supply current, no load	I_{CC}	R1 = infinity	1, 2, 3	01,02		15	mA
		M,D,P,L,R,F	1			15	
Power supply rejection ratio	PSSR	$-V_{CC}$ = -4.5 V to -5.0 V, $+V_{CC}$ = +4.5 V to +5.0 V	1, 2, 3	01,02	45		dB
		M,D,P,L,R,F	1		45		
AC parameters							
3rd harmonic distortion	HD3	2 V_{P-P} at 20 MHz 5/	4	01,02		-62	dBc
Gain flatness peaking, low	GFPL	0.1 MHz to 75 MHz, 5/ $V_{OUT} < 0.5$ V_{P-P}	4	01,02		0.4	dB
Gain flatness peaking, high	GFPH	> 75 MHz, 5/ $V_{OUT} < 0.5$ V_{P-P}	4	01,02		2.0	dB
Gain flatness rolloff	GFRH	75 MHz to 125 MHz, 5/ $V_{OUT} < 0.5$ V_{P-P}	4	01,02		0.2	dB
2nd harmonic distortion	HD2	2 V_{P-P} at 20 MHz 5/	4	01,02		-52	dBc

See footnotes at end of table I.

* FIGURE 6. Sample SMD - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical performance characteristic - continued.

1/ R1 = 100 Ω, V_{CC} = ±5 V dc, A_V = +2, feedback resistor (R_f) = 250 Ω, gain resistor (R_g) = 250 Ω.

2/ RHA devices supplied to this drawing meet all levels M, D, P, L, R, and F of irradiation however this device is only tested at the R and F levels (see 1.5 herein). Pre and post irradiation values are identical unless otherwise specified in table I. When performing post irradiation electrical measurements for any RHA level, T_A = +25°C.

3/ For device type 01, this part may be dose rate sensitive in a space environment and may demonstrate enhanced low dose rate effects. Radiation end point limits for the noted parameters are guaranteed only for the conditions as specified in MIL- STD-883, method 1019, condition A. For device type 02, this part has been tested and does not demonstrate low dose rate sensitivity. Radiation end point limits for the noted parameters are guaranteed for the conditions specified in MIL-STD-883, method 1019, condition D.

4/ The algebraic convention, whereby the most negative value is a minimum and most positive is a maximum, is used in this table. Negative current shall be defined as conventional current flow out of a device terminal.

5/ This parameter is not post irradiation tested.

3.5.1 Certification/compliance mark. The certification mark for device classes Q and V shall be a "QML" or "Q" as required in MIL-PRF-38535. The compliance mark for device class M shall be a "C" as required in MIL-PRF-38535, appendix A.

3.6 Certificate of compliance. For device classes Q and V, a certificate of compliance shall be required from a QML-38535 listed manufacturer in order to supply to the requirements of this drawing (see 6.6.1 herein). For device class M, a certificate of compliance shall be required from a manufacturer in order to be listed as an approved source of supply in MIL-HDBK-103 (see 6.6.2 herein). The certificate of compliance submitted to DLA Land and Maritime-VA prior to listing as an approved source of supply for this drawing shall affirm that the manufacturer's product meets, for device classes Q and V, the requirements of MIL-PRF-38535 and herein or for device class M, the requirements of MIL-PRF-38535, appendix A and herein.

3.7 Certificate of conformance. A certificate of conformance as required for device classes Q and V in MIL-PRF-38535 or for device class M in MIL-PRF-38535, appendix A shall be provided with each lot of microcircuits delivered to this drawing.

3.8 Notification of change for device class M. For device class M, notification to DLA Land and Maritime -VA of change of product (see 6.2 herein) involving devices acquired to this drawing is required for any change that affects this drawing.

3.9 Verification and review for device class M. For device class M, DLA Land and Maritime, DLA Land and Maritime's agent, and the acquiring activity retain the option to review the manufacturer's facility and applicable required documentation. Offshore documentation shall be made available onshore at the option of the reviewer.

3.10 Microcircuit group assignment for device class M. Device class M devices covered by this drawing shall be in microcircuit group number 49 (see MIL-PRF-38535, appendix A).

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-02546
		REVISION LEVEL D	SHEET 6

DSCC FORM 2234
APR 97

* FIGURE 6. Sample SMD - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.

Device types	01 and 02	
Case outlines	P	Z
Terminal number	Terminal symbol	
1	N/C	N/C
2	V_{INV}	V_{INV}
3	$V_{NON-INV}$	$V_{NON-INV}$
4	$-V_{CC}$	$-V_{CC}$
5	N/C	N/C
6	V_{OUT}	N/C
7	$+V_{CC}$	N/C
8	N/C	V_{OUT}
9	—	$+V_{CC}$
10	—	N/C

N/C = No connection

FIGURE 1. Terminal connections.

* FIGURE 6. Sample SMD - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.

4. VERIFICATION

4.1 Sampling and inspection. For device classes Q and V, sampling and inspection procedures shall be in accordance with MIL-PRF-38535 or as modified in the device manufacturer's Quality Management (QM) plan. The modification in the QM plan shall not affect the form, fit, or function as described herein. For device class M, sampling and inspection procedures shall be in accordance with MIL-PRF-38535, appendix A.

4.2 Screening. For device classes Q and V, screening shall be in accordance with MIL-PRF-38535, and shall be conducted on all devices prior to qualification and technology conformance inspection. For device class M, screening shall be in accordance with method 5004 of MIL-STD-883, and shall be conducted on all devices prior to quality conformance inspection.

4.2.1 Additional criteria for device class M.

a. Burn-in test, method 1015 of MIL-STD-883.

(1) Test condition A, B, C, or D. The test circuit shall be maintained by the manufacturer under document revision level control and shall be made available to the preparing or acquiring activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in method 1015 of MIL-STD-883.

(2) T_A = +125°C, minimum.

b. Interim and final electrical test parameters shall be as specified in table IIA herein.

4.2.2 Additional criteria for device classes Q and V.

a. The burn-in test duration, test condition and test temperature, or approved alternatives shall be as specified in the device manufacturer's QM plan in accordance with MIL-PRF-38535. The burn-in test circuit shall be maintained under document revision level control of the device manufacturer's Technology Review Board (TRB) in accordance with MIL-PRF-38535 and shall be made available to the acquiring or preparing activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in method 1015 of MIL-STD-883.

b. Interim and final electrical test parameters shall be as specified in table IIA herein.

c. Additional screening for device class V beyond the requirements of device class Q shall be as specified in MIL-PRF-38535, appendix B.

4.3 Qualification inspection for device classes Q and V. Qualification inspection for device classes Q and V shall be in accordance with MIL-PRF-38535. Inspections to be performed shall be those specified in MIL-PRF-38535 and herein for groups A, B, C, D, and E inspections (see 4.4.1 through 4.4.4).

4.4 Conformance inspection. Technology conformance inspection for classes Q and V shall be in accordance with MIL-PRF-38535 including groups A, B, C, D, and E inspections and as specified herein. Quality conformance inspection for device class M shall be in accordance with MIL-PRF-38535, appendix A and as specified herein. Inspections to be performed for device class M shall be those specified in method 5005 of MIL-STD-883 and herein for groups A, B, C, D, and E inspections (see 4.4.1 through 4.4.4).

4.4.1 Group A inspection.

a. Tests shall be as specified in table IIA herein.

b. Subgroups 5, 6, 7, 8, 9, 10, and 11 in table I, method 5005 of MIL-STD-883 shall be omitted.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-02546
		REVISION LEVEL D	SHEET 8

DSCC FORM 2234
APR 97

* FIGURE 6. Sample SMD - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.

TABLE IIA. Electrical test requirements.

Test requirements	Subgroups (in accordance with MIL-STD-883, method 5005, table I)	Subgroups (in accordance with MIL-PRF-38535, table III)	
	Device class M	Device class Q	Device class V
Interim electrical parameters (see 4.2)	—	—	—
Final electrical parameters (see 4.2)	1,2,3 1/	1,2,3 1/	1,2,3 1/
Group A test requirements (see 4.4)	1,2,3,4	1,2,3,4	1,2,3,4
Group C end-point electrical parameters (see 4.4)	1	1	1,2,3 2/
Group D end-point electrical parameters (see 4.4)	1	1	1,2,3
Group E end-point electrical parameters (see 4.4)	1	1	1

1/ PDA applies to subgroup 1.
2/ Delta limits as specified in table IIB shall be required where specified, and delta limits shall be computed with reference to the previous endpoint electrical parameters.

TABLE IIB. Delta value parameters. 1/ 2/

Parameter	Symbol	Subgroup	Limits		Unit
			Min	Max	
Input bias current noninverting	I_{BN}	1	-0.3	+0.3	µA
Input bias current inverting	I_{BI}	1	-3.0	+3.0	µA
Input offset voltage	V_{IO}	1	-0.3	+0.3	mV

1/ R1 = 100 Ω, V_{CC} = ±5 V dc, A_V = +2, feedback resistor (R_f) = 250 Ω, gain resistor (R_g) = 250 Ω.
2/ The algebraic convention, whereby the most negative value is a minimum and most positive is a maximum, is used in this table. Negative current shall be defined as conventional current flow out of a device terminal.

* FIGURE 6. Sample SMD - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.

4.4.2 Group C inspection. The group C inspection end-point electrical parameters shall be as specified in table IIA herein.

4.4.2.1 Additional criteria for device class M. Steady-state life test conditions, method 1005 of MIL-STD-883:

a. Test condition A, B, C, or D. The test circuit shall be maintained by the manufacturer under document revision level control and shall be made available to the preparing or acquiring activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in method 1005 of MIL-STD-883.

b. T_A = +125°C, minimum.

c. Test duration: 1,000 hours, except as permitted by method 1005 of MIL-STD-883.

4.4.2.2 Additional criteria for device classes Q and V. The steady-state life test duration, test condition and test temperature, or approved alternatives shall be as specified in the device manufacturer's QM plan in accordance with MIL-PRF-38535. The test circuit shall be maintained under document revision level control by the device manufacturer's TRB in accordance with MIL-PRF-38535 and shall be made available to the acquiring or preparing activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in method 1005 of MIL-STD-883.

4.4.3 Group D inspection. The group D inspection end-point electrical parameters shall be as specified in table IIA herein.

4.4.4 Group E inspection. Group E inspection is required only for parts intended to be marked as radiation hardness assured (see 3.5 herein).

a. End-point electrical parameters shall be as specified in table IIA herein.

b. For device classes Q and V, the devices or test vehicle shall be subjected to radiation hardness assured tests as specified in MIL-PRF-38535 for the RHA level being tested. For device class M, the devices shall be subjected to radiation hardness assured tests as specified in MIL-PRF-38535, appendix A for the RHA level being tested. All device classes must meet the post-irradiation end-point electrical parameter limits as defined in table I at T_A = +25°C ±5°C, after exposure, to the subgroups specified in table IIA herein.

4.4.4.1 Total dose irradiation testing. Total dose irradiation testing shall be performed in accordance with MIL-STD-883 method 1019 condition A for device type 01, condition D for device type 02 and as specified herein.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-PRF-38535 for device classes Q and V or MIL-PRF-38535, appendix A for device class M.

6. NOTES

6.1 Intended use. Microcircuits conforming to this drawing are intended for use for Government microcircuit applications (original equipment), design applications, and logistics purposes.

6.1.1 Replaceability. Microcircuits covered by this drawing will replace the same generic device covered by a contractor prepared specification or drawing.

6.1.2 Substitutability. Device class Q devices will replace device class M devices.

6.2 Configuration control of SMD's. All proposed changes to existing SMD's will be coordinated with the users of record for the individual documents. This coordination will be accomplished using DD Form 1692, Engineering Change Proposal.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-02546
		REVISION LEVEL D	SHEET 10

DSCC FORM 2234
APR 97

* FIGURE 6. Sample SMD - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.

6.3 Record of users. Military and industrial users should inform DLA Land and Maritime when a system application requires configuration control and which SMD's are applicable to that system. DLA Land and Maritime will maintain a record of users and this list will be used for coordination and distribution of changes to the drawings. Users of drawings covering microelectronic devices (FSC 5962) should contact DLA Land and Maritime -VA, telephone (614) 692-0544.

6.4 Comments. Comments on this drawing should be directed to DLA Land and Maritime -VA, Columbus, Ohio 43218-3990, or telephone (614) 692-0540.

6.5 Abbreviations, symbols, and definitions. The abbreviations, symbols, and definitions used herein are defined in MIL-PRF-38535 and MIL-HDBK-1331.

6.6 Sources of supply.

6.6.1 Sources of supply for device classes Q and V. Sources of supply for device classes Q and V are listed in QML-38535. The vendors listed in QML-38535 have submitted a certificate of compliance (see 3.6 herein) to DLA Land and Maritime -VA and have agreed to this drawing.

6.6.2 Approved sources of supply for device class M. Approved sources of supply for class M are listed in MIL-HDBK-103. The vendors listed in MIL-HDBK-103 have agreed to this drawing and a certificate of compliance (see 3.6 herein) has been submitted to and accepted by DLA Land and Maritime -VA.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-02546
		REVISION LEVEL D	SHEET 11

DSCC FORM 2234
APR 97

* FIGURE 6. Sample SMD - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.

STANDARD MICROCIRCUIT DRAWING BULLETIN

DATE: 11-07-19

Approved sources of supply for SMD 5962-02546 are listed below for immediate acquisition information only and shall be added to MIL-HDBK-103 and QML-38535 during the next revision. MIL-HDBK-103 and QML-38535 will be revised to include the addition or deletion of sources. The vendors listed below have agreed to this drawing and a certificate of compliance has been submitted to and accepted by DLA Land and Maritime -VA. This information bulletin is superseded by the next dated revision of MIL-HDBK-103 and QML-38535. DLA Land and Maritime maintains an online database of all current sources of supply at http://www.dscc.landandmaritime.mil/Programs/Smcr/.

Standard microcircuit drawing PIN 1/	Vendor CAGE number	Vendor similar PIN 2/
5962-0254601QPA	27014	LMH6702J-QML
5962-0254601QZA	27014	LMH6702WG-QML
5962-0254601VPA	27014	LMH6702J-QMLV
5962-0254601VZA	27014	LMH6702WG-QMLV
5962F0254601VPA	27014	LMH6702JFQMLV
5962F0254601VZA	27014	LMH6702WGFQMLV
5962F0254602VPA	27014	LMH6702JFLQMLV
5962F0254602VZA	27014	LMH6702WGFLQMLV

1/ The lead finish shown for each PIN representing a hermetic package is the most readily available from the manufacturer listed for that part. If the desired lead finish is not listed contact the vendor to determine its availability.

2/ Caution. Do not use this number for item acquisition. Items acquired to this number may not satisfy the performance requirements of this drawing.

Vendor CAGE number	Vendor name and address
27014	National Semiconductor Corporation 2900 Semiconductor Drive P.O. Box 58090 Santa Clara, CA 95052-8090

The information contained herein is disseminated for convenience only and the Government assumes no liability whatsoever for any inaccuracies in the information bulletin.

* FIGURE 6. Sample SMD - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.

Custodians:
Army - CR
Navy - EC
* Air Force - 85
DLA-CC

* Review activities:
Army - AR, MI, SM
* Navy - AS, CG, MC, SH
Air Force - 03, 19, 99

Preparing activity:
DLA-CC

(Project 5962-2011-010)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the
* ASSIST Online database at https://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:50Z
Check the source to verify that this is the current version before use.