The documentation and process conversion measures necessary to comply with this revision shall be completed by 18 November 2011.

INCH-POUND

MIL-PRF-19500/430C
18 August 2011
SUPERSEDING
MIL-PRF-19500/430B
30 July 1999

* PERFORMANCE SPECIFICATION SHEET

SEMICONDUCTOR DEVICE, DUAL FIELD EFFECT TRANSISTORS, N-CHANNEL, SILICON
TYPES 2N5545, 2N5546, AND 2N5547, JAN, JANTX, AND JANTXV

This specification is approved for use by all Departments and Agencies of the Department of Defense.

* The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-19500.

1. SCOPE

1.1 Scope. This specification covers the performance requirements for two electrically isolated, matched N-channel, junction, silicon field-effect transistors in one package. Three levels of product assurance are provided for each device type as specified in MIL-PRF-19500.

1.2 Physical dimensions. See figure 1 (similar to TO-71).

1.3 Maximum ratings. T_A = +25°C, unless otherwise specified.

P_T (1) T_A = +25°C		V_{DG}	V_{GS}	I_G	T_{STG}
One section	Both sections				
mW	mW	V dc	V dc	mA dc	°C
250	400	50	-50	30	-65 to +200

(1) For T_A > +25°C, derate linearly 1.67 mW/°C one section, 2.67 mW/°C both sections.

* 1.4 Primary electrical characteristics. T_C = +25°C, unless otherwise specified.

Limits	I_{DSS} V_{GS} = 0 V_{DS} = 15 V dc	$V_{GS(off)}$ V_{DS} = 15 V dc I_D = 0.5 nA dc	$\|y_{fs}\|$ V_{DS} = 15 V dc V_{GS} = 0 f = 1 kHz	$\|y_{fs}\|$ V_{DS} = 15 V dc V_{GS} = 0 f = 100 MHz	Nf V_{DG} = 15 V dc I_D = 200 µA dc R_G = 1 MΩ f = 10 Hz		C_{iss} V_{DS} = 15 V dc V_{GS} = 0 f = 1 MHz	C_{rss} V_{DS} = 15 V dc V_{GS} = 0 f = 1 MHz
					2N5545 dB	2N5546 dB		
	mA dc	V dc	mmho	mmho			pF	pF
Min	0.5	-0.5	1.5	1.5				
Max	8.0	-4.5	6.0		3.5	5.0	6.0	2.0

* Comments, suggestions, or questions on this document should be addressed to DLA Land and Maritime, ATTN: VAC, P.O. Box 3990, Columbus, OH 43218-3990, or emailed to Semiconductor@dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.daps.dla.mil/.

AMSC N/A FSC 5961

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T01:46Z
Check the source to verify that this is the current version before use.

* 1.4 Primary electrical characteristics - Continued.

	I_{DSS1} / I_{DSS2} V_{DG} = 15 V dc V_{GS} = 0			$\lvert y_{fs}\rvert_1$ / $\lvert y_{fs}\rvert_2$ V_{DG} = 15 V dc I_D = 200 µA dc f = 1 kHz			$\lvert V_{GS1} - V_{GS2}\rvert_2$ V_{DG} = 15 V dc I_D = 200 µA dc			$\lvert\Delta(V_{GS1} - V_{GS2})\Delta T_A\rvert$ (1)					
										V_{DG} = 15 V dc I_D = 200 µA dc $T_{A(1)}$ = +25°C $T_{A(2)}$ = -55°C			V_{DG} = 15 V dc I_D = 200 µA dc $T_{A(1)}$ = +25°C $T_{A(2)}$ = +125°C		
2N#	5545	5546	5547	5545	5546	5547	5545	5546	5547	5545	5546	5547	5545	5546	5547
							mV dc	mV dc	mV dc	mV dc	mV dc	mV dc	mV dc	mV dc	mV dc
Min	0.95	0.9	0.9	0.97	0.95	0.9									
Max	1.05	1.10	1.10	1.03	1.05	1.10	5	10	15	0.8	1.6	3.2	1	2	4

(1) Pulsed, (see 4.5.1).

2. APPLICABLE DOCUMENTS

* 2.1 General. The documents listed in this section are specified in sections 3, 4, or 5 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3, 4, or 5 of this specification, whether or not they are listed.

2.2 Government documents.

* 2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

MIL-PRF-19500 - Semiconductor Devices, General Specification for.

* DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-750 - Test Methods for Semiconductor Devices.

* (Copies of these documents are available online at https://assist.daps.dla.mil/quicksearch/ or https://assist.daps.dla.mil/ or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)


* 2.3 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

* 3.1 General. The individual item requirements shall be as specified in MIL-PRF-19500 and as modified herein.

* 3.2 Qualification. Devices furnished under this specification shall be products that are manufactured by a manufacturer authorized by the qualifying activity for listing on the applicable qualified manufacturer's list (QML) before contract award (see 4.2 and 6.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T01:46Z
Check the source to verify that this is the current version before use.



CONNECTION DIAGRAM

Ltr	Dimensions				Notes
	Inches		Millimeters		
	Min	Max	Min	Max	
ϕA	.209	.230	5.31	5.84	
ϕB	.178	.195	4.52	4.95	
C	.170	.210	4.32	5.33	
D	.500	.750	12.70	19.05	
E		.021		0.53	3
F	.016	.019	0.41	0.48	4
J	.028	.048	0.71	1.22	7
K	.036	.046	0.91	1.17	
L		.020		0.51	
N	.0146 Nom.		.037 Nom.		5
P	.0354 Nom.		.90 Nom.		5

NOTES:
1. Dimensions are in inches.
* 2. Millimeters are given for general information only.
3. Measured in the zone beyond .250 inch (6.35 mm) from the seating plane.
4. Measured in the zone from .50 inch (1.27 mm) to .250 inch (6.35 mm) from the seating plane.
5. When measured in a gauging plane .054 +.001, -.000 inch (1.37 -0.03, -0.00 mm) below the seating plane of the transistor, maximum diameter leads shall be within .007 inch (0.18 mm) of their true location relative to a maximum width tab. Smaller diameter leads shall fall within the outline of the maximum diameter lead tolerance.
6. All leads electrically insulated from case and each section electrically isolated from the other.
7. Measured from the maximum diameter of the actual device.

* FIGURE 1. Physical dimensions (similar to TO-71).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T01:46Z
Check the source to verify that this is the current version before use.

3.3 Abbreviations, symbols, and definitions. Abbreviations, symbols, and definitions used herein shall be as specified in MIL-PRF-19500.

$\frac{|I_{DSS1}|}{|I_{DSS2}|}$ ..... Zero-gate-voltage drain current ratio.

$|I_{G1} - I_{G2}|$ ..... Gate current differential.

$|V_{GS1} - V_{GS2}|$ ..... Gate-source voltage differential.

$|\Delta(V_{GS1} - V_{GS2})\Delta T_A|$ ..... Gate-source voltage differential change with temperature.

V_n ..... Equivalent short circuit input noise voltage for unity bandwidth.

$\frac{|y_{fs}|1}{|y_{fs}|2}$ ..... Small-signal common-source forward transfer admittance ratio.

$||y_{os}|1 - |y_{os}|2|$ ..... Small-signal common-source output admittance differential.

* 3.4 Interface and physical dimensions. The interface and physical dimensions shall be as specified in MIL-PRF-19500 and on figure 1 herein.

3.4.1 Lead finish. Lead finish shall be solderable in accordance with MIL-PRF-19500. Where a choice of lead finish is desired, it shall be specified in the acquisition document (see 6.2).

3.5 Marking. Marking shall be in accordance with MIL-PRF-19500.

3.6 Electrostatic discharge protection. The devices covered by this specification require electrostatic protection.

* 3.6.1 Handling. MOS devices must be handled with certain precautions to avoid damage due to the accumulation of electrostatic charge. The following handling practices shall be followed:

a. Devices shall be handled on benches with conductive handling devices.

b. Ground test equipment, tools, and personnel handling devices.

c. Do not handle devices by the leads.

d. Store devices in conductive foam or carriers.

e. Avoid use of plastic, rubber, or silk in MOS areas.

f. Maintain relative humidity above 50 percent, if practical.

g. Care shall be exercised, during test and troubleshooting, to apply not more than maximum rated voltage to any lead.

* h. Gate must be terminated to source, $R \leq 100$ kΩ, whenever bias voltage is to be applied drain to source.

3.7 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in 1.3, 1.4 and table I.

* 3.8 Electrical test requirements. The electrical test requirements shall be specified in table I herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T01:46Z
Check the source to verify that this is the current version before use.

* 3.9 Workmanship. Semiconductor devices shall be processed in such a manner as to be uniform in quality and shall be free from other defects that will affect life, serviceability, or appearance.

* 4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. Qualification inspection (see 4.2).

b. Screening (see 4.3).

* c. Conformance inspection (see 4.4 and tables I and II).

4.2 Qualification inspection. Qualification inspection shall be in accordance with MIL-PRF-19500 and as specified herein.

* 4.2.1 Group E qualification. Group E inspection shall be performed for qualification or re-qualification only. In case qualification was awarded to a prior revision of the specification sheet that did not request the performance of table III tests, the tests specified in table III herein that were not performed in the prior revision shall be performed on the first inspection lot of this revision to maintain qualification.

4.3 Screening (JANTX and JANTXV levels only). Screening shall be in accordance with table E-IV of MIL-PRF-19500), and as specified herein. The following measurements shall be made in accordance with table I herein. Devices that exceed the limits of table I herein shall not be acceptable.

Screen (see table E-IV of MIL-PRF-19500	Measurement
	JANTX and JANTXV levels
9	Not applicable.
10	Not applicable.
11	I_{DSS}, I_{GSS}, $\lvert y_{fs} \rvert$
12	See 4.3.1.
13	Subgroup 2 of table I herein; ΔI_{GSS} = 0.1 nA dc or 100 percent of initial value, whichever is greater. $\lvert \Delta y_{fs} \rvert$ = ±20 percent of initial value. ΔI_{DSS} = 10 percent of initial value.

4.3.1 Power burn-in. Power burn-in conditions are in accordance with MIL-STD-750, method 1039, condition A and as follows: T_A = +175°C; V_{GS} = -40 V dc; V_{DS} = 0.

* 4.4 Conformance inspection. Conformance inspection shall be in accordance with MIL-PRF-19500 and as specified herein. Alternate flow is allowed for quality conformance inspection in accordance with MIL-PRF-19500.

4.4.1 Group A inspection. Group A inspection shall be conducted in accordance with MIL-PRF-19500 and table I herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T01:46Z
Check the source to verify that this is the current version before use.

4.4.2 Group B inspection. Group B inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-VIB (JAN, JANTX, and JANTXV) of MIL-PRF-19500 and as follows. Electrical measurements (end-points) and delta requirements shall be in accordance with the applicable steps of table II herein.

Subgroup	Method	Condition
B3	1027	V_{GS} = -40 V dc; T_A = +175°C; V_{DS} = 0.

4.4.3 Group C inspection. Group C inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-VII of MIL-PRF-19500 and 4.4.3.1 (JAN, JANTX, and JANTXV) herein for group C testing. Electrical measurements (end-points) and delta requirements shall be in accordance with the applicable steps of table II herein.

Subgroup	Method	Condition
C2	2036	Lead fatigue: Test condition E.
C6	1027	V_{GS} = -40 V dc; T_A = +175°C; V_{DS} = 0.

(4.4.4 Gate current differential. The gate current of each individual section of a dual unit shall be measured at the specified conditions and the absolute value of the difference of the two currents shall be calculated. If possible, this difference shall be measured directly to improve accuracy.

* 4.4.5 Gate-source voltage differential. The gate-source voltage of each individual section of a dual unit shall be measured at the specified conditions and the absolute value of the difference of the two voltages shall be calculated. If possible, this difference shall be measured directly to improve accuracy.

* 4.4.6 Gate-source voltage differential change with temperature. The gate-source voltage differential shall be measured at the two specified temperatures in accordance with 4.4.5 herein except that the polarities of the differentials and identities of the individual sections shall be maintained. The absolute value of the algebraic differences between the values at the two temperatures shall be calculated. If possible, this difference should be measured directly to improve accuracy. A mathematical formula for the parameter is:

$$|(V_{GS1} - V_{GS2})T_1 - (V_{GS1} - V_{GS2})T_2|$$

* 4.4.7 Zero-gate-voltage drain current ratio. The value for the zero-gate-voltage drain current for each individual section of a dual unit shall be measured using method 3413 of MIL-STD-750. The zero-gate-voltage drain current ratio shall be calculated by dividing one of the values by the other. If possible, this ratio shall be measured directly to improve accuracy.

* 4.4.8 Small-signal common-source forward transfer admittance ratio. The magnitude for the small-signal common-source forward transfer admittance ratio for each individual section of a dual unit shall be measured using method 3455 of MIL-STD-750. The small-signal common-source forward transfer admittance ratio shall be calculated by dividing one of the values by the other. If possible, this ratio shall be measured directly to improve accuracy.

* 4.4.9 Small-signal common-source output admittance differential. The magnitude for the small-signal common-source output admittance differential for each individual section of a dual unit shall be measured using method 3453 of MIL-STD-750. The small-signal common-source output admittance differential shall be calculated by dividing one of the values by the other. If possible, this ratio shall be measured directly to improve accuracy.

4.4.10 Spot noise figure and equivalent input noise voltage. These tests should be conducted with a model 2173C Quan Tech Laboratories test set or equivalent. Conditions shall be as specified in table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T01:46Z
Check the source to verify that this is the current version before use.

* 4.4.11 Group E inspection. Group E inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-IX of MIL-PRF-19500 and as specified in table III herein. Electrical measurements (end-points) shall be in accordance with table I, subgroup 2 herein.

4.5 Methods of inspection. Methods of inspection shall be as specified in the appropriate tables and as follows.

4.5.1 Pulse measurements. Conditions for pulse measurement shall be as specified in section 4 of MIL-STD-750.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T01:46Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection.

	Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
		Method	Conditions		Min	Max	
	Subgroup 1 2/						
	Visual and mechanical 3/ examination	2071	n = 45 devices, c = 0				
	Subgroup 2						
	Reverse gate current	3411	Bias condition C; V_{GS} = -50 V dc; V_{DS} = 0	I_{GSS1}		-1.0	µA dc
	Reverse gate current	3411	Bias condition C; V_{GS} = -30 V dc; V_{DS} = 0	I_{GSS2}		-0.1	nA dc
	Drain current	3413	Bias condition C; V_{DS} = 15 V dc; V_{GS} = 0	I_{DSS}	0.5	8.0	mA dc
	Gate current		V_{DG} = 15 V dc I_D = 200 µA dc	I_G		-50	pA dc
	Gate-source cutoff voltage	3403	V_{DS} = 15 V dc I_D = 0.5 nA dc	$V_{GS(off)}$	-0.5	-4.5	V dc
*	Gate-source voltage differential	3403	V_{DG} = 15 V dc; I_D = 50 µA dc; (see 4.4.4)	$\lvert V_{GS1} - V_{GS2} \rvert 1$			
	2N5545					5	mV dc
	2N5546					10	mV dc
	2N5547					15	mV dc
*	Gate-source voltage differential	3403	V_{DG} = 15 V dc; I_D = 200 µA dc; (see 4.4.4)	$\lvert V_{GS1} - V_{GS2} \rvert 2$			
	2N5545					5	mV dc
	2N5546					10	mV dc
	2N5547					15	mV dc

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T01:46Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Subgroup 2 -continued						
Gate-source voltage differential change with temperature	3403	V_{DG} = 15 V dc; I_D = 200 µA dc; $T_{A(1)}$ = +25°C; $T_{A(2)}$ = -55°C; (see 4.4.5)	$\lvert\Delta(V_{GS1} - V_{GS2})\Delta T_A\rvert$			
2N5545					.8	mV dc
2N5546					1.6	mV dc
2N5547					3.2	mV dc
Gate-source voltage differential change with temperature	3403	V_{DG} = 15 V dc; I_D = 200 µA dc; $T_{A(1)}$ = +25°C; $T_{A(2)}$ = +125°C; (see 4.4.6)	$\lvert\Delta(V_{GS1} - V_{GS2})\Delta T_A\rvert$			
2N5545					1	mV dc
2N5546					2	mV dc
2N5547					4	mV dc
Zero-gate-voltage drain current ratio	3413	Bias condition C; V_{DS} = 15 V dc; V_{GS} = 0; (see 4.4.7)	$\frac{I_{DSS1}}{I_{DSS2}}$			
2N5545				0.95	1.05	
2N5546				0.90	1.10	
2N5547				0.90	1.10	
Small-signal common-source short-circuit forward transfer admittance ratio	3455	V_{DG} = 15 V dc; I_D = 200 µA dc; f = 1 kHz; (see 4.4.8)	$\frac{\lvert y_{fs}\rvert_1}{\lvert y_{fs}\rvert_2}$			
2N5545				0.97	1.03	
2N5546				0.95	1.05	
2N5547				0.90	1.10	
Small -signal common-source short-circuit, output admittance differential	3453	V_{DS} = 15 V dc; V_{GS} = 0; f = 1 kHz	$\lvert\lvert y_{os}\rvert_1 - \lvert y_{os}\rvert_2\rvert$			
2N5545					1	µmho
2N5546					2	µmho
2N5547					3	µmho
Subgroup 3						
High temperature operation:		T_A = +150°C				
* Reverse gate current	3411	Bias condition C; V_{GS} = -30 V dc; V_{DS} = 0	I_{GSS3}		-150	nA dc
Gate current differential		V_{DG} = 15 V dc; I_D = 200 µA dc; T_A = +125°C; (see 4.4.4)	$\lvert I_{G1} - I_{G2}\rvert$		5	nA dc

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T01:46Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Subgroup 4			$\lvert y_{fs} \rvert$	1.5	6.0	mmho
Small-signal common-source short-circuit forward transfer admittance	3455	V_{DS} = 15 V dc; V_{GS} = 0; 100 kHz ≤ f ≤ 1 MHz				
Small signal common-source short-circuit, output admittance	3453	V_{DS} = 15 V dc; V_{GS} = 0; 100 kHz ≤ f ≤ 1 MHz	$\lvert y_{os} \rvert$		25	µmho
Small signal common-source short-circuit, input capacitance	3431	V_{GS} = 0 V dc; V_{DS} = 15; 100 kHz ≤ f ≤ 1 MHz	C_{iss}		6	pF
Small signal common-source short-circuit, reverse transfer capacitance	3433	V_{GS} = 0 V dc; V_{DS} = 15; 100 kHz ≤ f ≤ 1 MHz	C_{rss}		2	pF
Spot noise figure (2N5545, 2N5546 only)		V_{DS} = 15 V dc; I_D = 200 µA dc; f = 10 Hz; R_G = 1 MΩ; Noise bandwidth = 5 Hz (see 4.4.10)	NF			
2N5545					3.5	dB
2N5546					5.0	dB
Equivalent input noise voltage		V_{DS} = 15 V dc; I_D = 200 µA dc; Noise bandwidth = 5 Hz (see 4.4.10)	V_n			
2N5545					180	$nV\sqrt{Hz}$
2N5546					200	$nV\sqrt{Hz}$
Subgroups 5 and 6						
Not applicable						
Subgroup 7						
Low temperature operation:		T_A = -65°C				
Magnitude of small-signal common-source short-circuit forward transfer admittance	3455	V_{DS} = 15 V dc; V_{GS} = 0; f = 1 kHz	$\lvert y_{fs} \rvert$		10.0	mmho

1/ For sampling plan, see MIL-PRF-19500.
2/ For resubmission of failed subgroup A1, double the sample size of the failed test or sequence of tests.
3/ Separate samples may be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T01:46Z
Check the source to verify that this is the current version before use.

* TABLE II. Groups A, B, and C electrical end-point measurements. 1/ 2/

	Step	Inspection	MIL-STD-750		Symbol	Limits		Unit
			Method	Conditions		Min	Max	
*	1.	Reverse gate current	3411	Bias condition C: V_{GS} = -30 V dc; V_{DS} = 0	I_{GSS4}		-0.5	nA dc
	2.	Magnitude of small-signal common-source short-circuit forward transfer admittance	3455	V_{DS} = 15 V dc V_{GS} = 0; f = 1 kHz	$\|y_{fs}\|$	1.5	6.0	mmho
*	3.	Reverse gate current	3411	Bias condition C; V_{GS} = -30 V dc; V_{DS} = 0	I_{GSS5}		-1.0	nA dc
	4.	Small-signal common-source short-circuit forward transfer admittance	3455	V_{DS} = 15 V dc; V_{GS} = 0; f = 1 kHz	$\Delta\|y_{fs}\|$	±20		percent change from initial group A reading
*	5.	Gate-source voltage differential	3403	V_{DG} = 15 V dc; I_D = 200 µA dc	$|V_{GS1} - V_{GS2}|$3			
		2N5545					6	mV dc
		2N5546					12	mV dc
		2N5547					18	mV dc
	6.	Zero-gate-voltage drain current ratio	3413	Bias condition C; V_{DG} = 15 V dc; V_{GS} = 0	$\frac{I_{DSS1}}{I_{DSS2}}$			
		2N5545				0.95	1.05	
		2N5546				0.90	1.10	
		2N5547				0.90	1.10	

1/ The electrical measurements for table E-VIB (JAN, JANTX, JANTXV) of MIL-PRF-19500 are as follows:
a. Subgroup 2, see table II herein, steps 1 and 2.
b. Subgroups 3 and 6, see table II herein, steps 3, 4, 5, and 6.

2/ The electrical measurements for table E-V of MIL-PRF-19500 are as follows: Subgroups 2, 3, and 6, see table II herein, steps 3, 4, 5, and 6.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T01:46Z
Check the source to verify that this is the current version before use.

* TABLE III. Group E inspection (all quality levels) for qualification or re-qualification only.

Inspection	MIL-STD-750		Qualification and large lot quality conformance inspection
	Method	Conditions	
Subgroup 1			45 devices c = 0
Temperature cycling	1051	-55°C to +150°C, 500 cycles	
Hermetic seal Fine leak Gross leak	1071	As applicable	
Electrical measurements		See table I, subgroup 2 and table II, all steps	
Subgroup 2			45 devices c = 0
Blocking life	1048	1,000 hours minimum, T_A = +150°C, V_{DG} or V_{GS} = 80 percent of rated.	
Electrical measurements		See table I, subgroup 2 and table II, all steps	
Subgroups 4 and 5			
Not applicable			

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T01:46Z
Check the source to verify that this is the current version before use.

5. PACKAGING

* 5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the Military Service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

* (This section contains information of a general or explanatory nature that may be helpful, but is not mandatory. The notes specified in MIL-PRF-19500 are applicable to this specification.)

* 6.1 Intended use. Semiconductors conforming to this specification are intended for original equipment design applications and logistic support of existing equipment.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Packaging requirements (see 5.1).

c. Lead finish (see 3.4.1).

d. Product assurance level and type designator.

* 6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in Qualified Manufacturers List (QML 19500) whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from DLA Land and Maritime, ATTN: VQE, P.O. Box 3990, Columbus, OH 43218-3990 or e-mail vqe.chief@dla.mil. An online listing of products qualified to this specification may be found in the Qualified Products Database (QPD) at https://assist.daps.dla.mil .

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T01:46Z
Check the source to verify that this is the current version before use.

* 6.4 Changes from previous issue. The margins of this specification are marked with asterisks to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - CR
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5961-2011-045)

Review activities:
Army - MI
Air Force - 19, 99

* NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.daps.dla.mil/ .

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T01:46Z
Check the source to verify that this is the current version before use.