The documentation and process conversion measures necessary to comply with this amendment shall be completed by 30 January 2002.

INCH-POUND

MIL-PRF-19500/675A
AMENDMENT 1
30 October 2001

PERFORMANCE SPECIFICATION

SEMICONDUCTOR DEVICE, FIELD EFFECT RADIATION HARDENED
(TOTAL DOSE AND SINGLE EVENT EFFECTS)
TRANSISTORS, N-CHANNEL, SILICON TYPES 2N7463T2 AND 2N7464T2 AND U5 SUFFIXES
JANTXVR AND JANSR

This amendment forms a part of MIL-PRF-19500/675A, dated 30 August 2001, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

1.4, max $r_{DS(on)}$ (1) column, T_J = +25°C column, delete "1.2" and "1.6" respectively and substitute "1.39" and "1.77" respectively.

1.4, max $r_{DS(on)}$ (1) column, T_J = +150°C column, delete "2.7" and "3.6" respectively and substitute "3.0" and "3.9" respectively.

PAGE 11

TABLE I, subgroup 2, static drain to source on-state resistance test (first occurrence), limits max column, delete "1.2" and "1.6" respectively and substitute "1.39" and "1.77" respectively.

TABLE I, subgroup 2, static drain to source on-state resistance test (second occurrence), limits max column, delete "1.22" and "1.67" respectively and substitute "1.52" and "1.9" respectively.

TABLE I, subgroup 2, forward voltage test, delete "1.4" (two places) and substitute "1.2" (two places).

PAGE 12

TABLE I, subgroup 3, static drain to source on-state resistance, limits max column, delete "2.4" and "3.12" respectively and substitute "2.64" and "3.76" respectively.

TABLE I, subgroup 4, forward transconductance test, limits min column, delete "0.9" and "0.8" respectively and substitute "0.5" and "0.4" respectively.

TABLE I, subgroup 4, switching time test, turn-on delay time, 2N7464, limits max column, delete "30" substitute "35".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:42Z
Check the source to verify that this is the current version before use.

PAGE 13

TABLE I, subgroup 4, rise time, 2N7463, limits max column, delete "62" and substitute "78".

TABLE I, subgroup 4, turn-off delay time, limits max column, delete "58" and "65" respectively and substitute "65" and "67" respectively.

TABLE I, subgroup 4, fall time, limits max column, delete "58" and "45" respectively and substitute "66" and "52" respectively.

TABLE I, subgroup 7, on-state gate charge, 2N7463, limits max column, delete "41" and substitute "31".

TABLE I, subgroup 7, gate to source charge, 2N7463, limits max column, delete "7" and substitute "8.5".

TABLE I, subgroup 7, gate to source charge, 2N7464, limits max column, delete "7" and substitute "8".

PAGE 14

TABLE I, reverse recovery time, limits max column, delete "516" and "600" respectively and substitute "350" and "400" respectively.

PAGE 16

TABLE II, static drain to source on-state voltage, preirradiation limits, max column delete "2.28" and "2.56" respectively and substitute "2.641" and "2.832" respectively.

TABLE II, static drain to source on-state voltage, postirradiation limits, max column delete "2.28" and "2.56" respectively and substitute "2.641" and "2.832" respectively.

TABLE II, forward voltage source to drain diode, preirradiation limits, max column, delete "1.4" (two places) and substitute "1.2" (two places).

TABLE II, forward voltage source to drain diode, postirradiation limits, max column, delete "1.4" (two places) and substitute "1.2" (two places).

Custodians:
Army - CR
Navy - NW
Air Force - 11
NASA - NA
DLA - CC

Preparing activity:
DLA - CC

(Project 5961-2548)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:42Z
Check the source to verify that this is the current version before use.