MILITARY SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING

TYPE 9006

The complete requirements for procuring the electron tube described herein shall consist of this document and the latest issue of Specification MIL-E-1.

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

DESCRIPTION: Diode, miniature, rectifier

Outline	---	5-1 (EIA) Ⓑ
Base	---	E7-1
Envelope	---	T5-1/2
Cathode	---	Coated unipotential

Base connections:

Pin No.	---	1	2	3	4	5	6	7
Element	---	a	k	h	h	a	nc	k

ABSOLUTE-MAXIMUM RATINGS:

Parameter:	Ef	epy	Epp	ib	Io	Ehk	RL	CL	Zp	Ⓑ Alt
Unit:	V	v	Vac	ma	mAdc	v	Ohms	μF	Ohms	ft
Maximum:	6.9	825	---	16.5	5.5	100	---	---	---	(see note 1)
Minimum:	5.7 (see note 2)	---	---	---	---	---	45,000	---	---	
TEST CONDITIONS:	6.3	---	350	---	---	---	45,000	0.1	100	---

GENERAL:

Qualification - Not required

Ⓑ denotes changes

Source: https://assist.dla.mil -- Downloaded: 202610-15T13:22Z
Check the source to verify that this is the current version before use.

METHOD	REQUIREMENT OR TEST	CONDITIONS	AQL (PERCENT DEFECTIVE)	INSPECTION LEVEL OR CODE	SYMBOL	LIMITS MIN	LIMITS MAX	UNIT
	Quality conformance inspection, part 1							
1301	Heater current		0.65	II	If	140	160	mA
1231	Emission	Eb = 20 Vdc	0.65	II	Is	13	---	mAdc
1353	Operation of rectifiers	See note 3	0.65	II	Io	4.5	---	mAdc
1201	Short and discontinuity detection		0.4	II	---	---	---	---
	Quality conformance inspection, part 2							
1031	Low-frequency vibration	No voltages	6.5	S3	---	---	---	---
(B) 1336	Heater-cathode leakage		6.5	S3	Ihk	---	20	µAdc
1331	Direct-interelectrode capacitance	Without shield	6.5	Code E	Cpk	0.8	2.0	pF
		Without shield			Cph	0.05	0.6	pF
		Without shield			Chk	1.2	4.2	pF
2126	Glass strain		4.0	I	---	---	---	---
1121	Base strain		---	---	---	---	---	---
1211	Insulation of electrodes		4.0	S3	---	10	---	Meg
1105	Permanence of marking		---	---	---	---	---	---
	Quality conformance inspection, part 3							
1501	Intermittent life	Group A; Ehk = 100 Vdc	---	---	---	---	---	---
---	Life-test end point (intermittent) (500 hours)	Operation of rectifiers	---	---	Io	4.0	---	mAdc

NOTES:

1. See reduced pressure (altitude) rating, and for altitude, maximum peak voltage.
2. Operation of types 9001, 9002, 9003, and 9006 in series with other types on supply voltages exceeding 32 volts is not recommended due to the excessive filament surge voltages which will appear on tubes of this type.
3. This test to be performed at the conclusion of the holding period.

Source: https://assist.dla.mil -- Downloaded: 202610-15T13:22Z
Check the source to verify that this is the current version before use.

Custodians:
Army - EL
Navy - EC
Air Force - 85

Review activities:
Army - EL
Navy - SH
Air Force - 11, 17, 85
DSA - ES

User activities:
Army - MU
Navy - AS, OS, MC, CG
Air Force - 19

Preparing activity:
Navy - EC

(Project 5960-2211-17)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:22Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:22Z
Check the source to verify that this is the current version before use.