MILITARY SPECIFICATION SHEET

ELECTRON TUBE, KLYSTRON

TYPE 2K28

This amendment forms a part of Military Specification Sheet MIL-E-1/496C, dated 30 October 1969, and is mandatory for use by all Departments and Agencies of the Department of Defense.

Page 2

Add the following test methods and their associated columnar data as Qualification inspection tests, prior to Quality conformance inspection, part 1, and delete the Periodic-check test methods.

| METHOD | REQUIREMENT OR TEST | CONDITIONS | SYMBOL | LIMITS | | UNIT |
|---|---|---|---|---|---|---|
| | | | | MINIMUM | MAXIMUM | |
| | Qualification inspection | | | | | |
| 1031 | Low-frequency vibration | Er = -50 to -300 Vdc | ΔF | --- | 100 | kHz |
| 4004 | Temperature coefficient | 20°C range; t = 20 minutes (max) (see note 2) | ΔF/°C | --- | 3 | MHz/20°C |

Page 3

Concluding data: Delete and substitute:

Custodians:
Army - EL
Navy - EC
Air Force - 80

Review activities:
Army - EL
Navy -
Air Force - 11, 80
DSA - ES

User activities:
Army - WC, ME
Navy - AS, OS, MC, CG, SH
Air Force - 19

Preparing activity: Navy - EC

Agent: DSA - ES

(Project 5960-2425-95)



Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:23Z
Check the source to verify that this is the current version before use.