MILITARY SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING

TYPE 6BH6

The complete requirements for procuring the electron tube described herein shall consist of this document and the latest issue of Specification MIL-E-1.

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

DESCRIPTION: Pentode, RF sharp cutoff

Ⓐ Outline --- 5-2 (EIA)

Base --- E7-1

Envelope --- T5 1/2

Cathode --- Coated unipotential

Base connections:

Pin No.	---	1	2	3	4	5	6	7
Element	---	g1	k	h	h	a	g2	g3 internal shield

ABSOLUTE-MAXIMUM RATINGS:

Parameter:	Ef	Eb	Ec1	Ec2	Ec3	Pg2	Pp	Ⓐ Ehk	Rk	Ⓐ Alt
Unit:	V	Vdc	Vdc	Vdc	Vdc	W	W	v	Ohms	ft
Maximum:	6.9	330	---	150	---	0.6	3.3	100	---	(see note 1)
Minimum:	5.7	---	---	---	---	---	---	---	---	---
TEST CONDITIONS:	6.3	250	---	150	0	---	---	---	100	---

GENERAL:

Qualification - Required

Ⓐ denotes changes

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:25Z
Check the source to verify that this is the current version before use.

METHOD	REQUIREMENT OR TEST	CONDITIONS	AQL (PERCENT DEFECTIVE)	INSPECTION LEVEL OR CODE	SYMBOL	LIMITS MIN	LIMITS MAX	UNIT
	Quality conformance inspection, part 1							
1266	Total grid current	Ec1 = -1.0 Vdc; Rk = 0 (see note 2)	0.65	II	Ic1	0	-1.0	μAdc
1306	Transconductance (1)		0.65	II	Sm	3,500	5,700	μmhos
1231	Emission	Eb = Ec1 = Ec2 = Ec3 = 20 Vdc; Rk = 0 (see note 2)	0.65	II	Is	60	---	mAdc
(A) 1201	Short and discontinuity detection		0.40	II	---	---	---	---
1256	Electrode current (1) (anode)		0.65	II	Ib	5.4	9.4	mAdc
	Quality conformance inspection, part 2							
1301	Heater current		4.0	S3	If	138	162	mA
(A) 1336	Heater-cathode leakage		4.0	S3	Ihk	---	20	μAdc
1256	Electrode current (2) (anode)	Ec1 = -8.5 Vdc; Rk = 0; Rp = 0.25 Meg	4.0	S3	Ib	---	35	μAdc
1256	Electrode current (screen)		4.0	S3	Ic2	1.6	3.6	mAdc
1306	Transconductance (2)	Ef = 5.7 V	---	---	Sm	3,150	---	μmhos
(A) 1331	Direct-interelectrode capacitance	Without shield Without shield Without shield	---	---	Cg1p Cin Cout	--- 3.9 3.8	0.0035 6.1 6.2	pF pF pF
(A) 1211	Insulation of electrodes		---	---	---	---	---	---
1031	Low-frequency vibration	Rp = 2,000 ohms	---	---	Ep	---	400	mVac
(A) 1105	Permanence of marking		---	---	---	---	---	---
(A) 1121	Base strain		see note 3	---	---	---	---	---
(A) 2126	Glass strain		2.5	I	---	---	---	---
	Quality conformance inspection, part 3							
1501	Intermittent life	Group A, Ehk = 100 Vdc; Rg1 = 0.5 Meg	---	---	---	---	---	---
---	Intermittent life-test end points (500 hours)	Transconductance (1)	---	---	Sm	3,000	---	μmhos

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:25Z
Check the source to verify that this is the current version before use.

NOTES:

1. See "Reduced pressure (altitude) rating", and altitude, maximum peak voltage.
2. This test to be performed at the conclusion of the holding period.
3. The "Base-strain test, miniature tube, sampling" paragraph of MIL-E-1 and all subparagraphs thereto shall apply.

Custodians:
Army - EL
Navy - EC
Air Force - 80

Review activities:
Army - EL, MI
Navy -
Air Force - 11, 17, 85
DSA - ES

User activities:
Army - WC
Navy - AS, OS, MC, CG, SH
Air Force - 19

Preparing activity: Navy - EC

Agent: DSA - ES

(Project 5960-2401-82)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:25Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:25Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY
NAVAL ELECTRONIC SYSTEMS COMMAND
WASHINGTON, D. C. 20360

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

COMMANDER
NAVAL ELECTRONIC SYSTEMS COMMAND
DEFENSE STANDARDIZATION PROGRAM BRANCH
DEPARTMENT OF THE NAVY
WASHINGTON, D. C. 20360

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:25Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE | CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

   ☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)* | DATE

DD FORM 1 JAN 66 1426 REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

S/N-0102-014-1801 C-25254

Source: https://assist.dla.mil -- Downloaded: 202640-15T13:25Z
Check the source to verify that this is the current version before use.