MIL-E-1/519A
15 November 1968
SUPERSEDING
MIL-E-1/519
14 January 1954

MILITARY SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING

TYPE 6C5 1/

The complete requirements for procuring the electron tube described herein shall consist of this document and the latest issue of Specification MIL-E-1.

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

DESCRIPTION: Triode, medium Mu

Outline	---	8-1 (EIA)	Ⓐ
Base	---	B6-23	
Envelope	---	MT-8	
Cathode	---	Coated unipotential	

Base connections:

Pin No.	---	1	2	3	5	7	8
Element	---	sh	h	a	g	h	k

ABSOLUTE-MAXIMUM RATINGS:

Parameter:	Ef	Eb	Ec	Pp	Ehk	Alt	
Unit:	V	Vdc	Vdc	W	v	ft	
Maximum:	6.9	330	---	2.75	100	10,000	Ⓐ
Minimum:	5.7	---	---	---	---	---	
TEST CONDITIONS:	6.3	250	-8	---	---	---	

GENERAL:

Qualification - Required

1/ See note 2

Ⓐ denotes changes

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:25Z
Check the source to verify that this is the current version before use.

METHOD	REQUIREMENT OR TEST	CONDITIONS	AQL (PERCENT DEFECTIVE)	INSPECTION LEVEL OR CODE	SYMBOL	LIMITS MIN	LIMITS MAX	UNIT
	Quality conformance inspection, part 1							
1266	Total grid current	See note 1	0.65	II	Ic	0	-1.0	μAdc
1256	Electrode current (1) (anode)		0.65	II	Ib	5.0	11.0	mAdc
1306	Transconductance (1)		0.65	II	Sm	1,700	2,500	μmhos
1231	Emission	Eb = Ec = 30 Vdc (see note 1)	0.65	II	Is	40	---	mAdc
Ⓐ 1246	Audio frequency noise	Esig = 200 mVac; Rp = 10,000 ohms (see note 3)	0.65	II	---	---	---	---
1201	Short and discontinuity detection		0.4	II	---	---	---	---
	Quality conformance inspection, part 2							
1301	Heater current		6.5	S3	If	275	325	mA
Ⓐ 1336	Heater-cathode leakage		6.5	S3	Ihk	---	20	μAdc
1256	Electrode current (2) (anode)	Ec = -20 Vdc	6.5	S3	Ib	0	30	μAdc
1306	Transconductance (2)	Eb = 90 Vdc; Ec = 0	6.5	S3	Sm	1,800	2,800	μmhos
1316	Amplification factor		6.5	S3	Mu	18	22	---
1031	Low-frequency vibration	Rp = 2,000 ohms	6.5	S3	Ep	---	300	mVac
1331	Direct-interelectrode capacitance		6.5	Code F	Cgp	1.7	2.3	pF
					Cin	2.4	3.6	pF
					Cout	7.7	14.3	pF
1101	Secureness of base and base insert		6.5	S3	---	---	---	---
1111	Base pin solder	See note 4	6.5	S3	---	---	---	---
1211	Insulation of electrodes		4.0	S3	R	10	---	Meg
1105	Permanence of marking		---	---	---	---	---	---
	Quality conformance inspection, part 3							
1501	Intermittent life	Group A; Ehk = 100 V	---	---	---	---	---	---
---	Life-test end point (intermittent) (500 hours)	Transconductance (1)	---	---	Sm	1,320	---	μmhos

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:25Z
Check the source to verify that this is the current version before use.

NOTES:

1. This test to be performed at the conclusion of the holding period.
2. Tube type 6C5GT is hereby deleted from this specification sheet. Tubes for replacement purposes will be procured to EIA data, Release Number 190, Type 6C5GT.
3. The rejection level shall be set at the VU meter reading obtained during calibration. (A)
4. This test applies for flexible leads as well as for rigid leads.

Custodians:
Army - EL
Navy - EC
Air Force - 11

Review activities:
Army - EL
Navy - SH
Air Force - 11, 85
DSA - ES

User activities:
Army - ME
Navy - AS, OS, MC, CG
Air Force - 19

Preparing activity:
Navy - EC

(Project 5960-2247-70)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:25Z
Check the source to verify that this is the current version before use.