MILITARY SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING

TYPE 6K6GT

The complete requirements for procuring the electron tube described herein shall consist of this document and the latest issue of Specification MIL-E-1.

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

DESCRIPTION: Pentode, power amplifier

Outline	---	9-11 or 9-41 (EIA)
Base	---	See note 1
Envelope	---	T9
Cathode	---	Coated unipotential

Base connections:

Pin No.	---	1	2	3	4	5	7	8
Element	---	nc	h	a	g2	g1	h	g3, k

ABSOLUTE-MAXIMUM RATINGS:

Parameter:	Ef	Eb	Ec2	Ec1	Pp	Pg2	(B) Ehk	(B) Alt
Unit:	V	Vdc	Vdc	Vdc	W	W	v	ft
Maximum:	6.9	350	315	---	9.4	3.1	100	(See note 2)
Minimum:	5.7	---	---	---	---	---	---	---
TEST CONDITIONS:	6.3	250	250	-18	---	---	---	---

GENERAL:

Qualification - Not required

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:26Z
Check the source to verify that this is the current version before use.

METHOD	REQUIREMENT OR TEST	CONDITIONS	AQL (PERCENT DEFECTIVE)	INSPECTION LEVEL OR CODE	SYMBOL	LIMITS MIN	LIMITS MAX	UNIT
	Qualification inspection							
(B) 1216	Base material insulating quality		---	---	---	---	---	---
	Quality conformance inspection, part 1							
1266	Total grid current	See note 3	0.65	II	Ic1	0	-2.0	µAdc
1256	Electrode current (anode)		0.65	II	Ib	23	45	mAdc
1341	Power output	Esig = 12.7 Vac; Rp = 7,600 ohms (see note 3)	0.65	II	Po	2.7	---	W
1246	Audio frequency noise	Esig = 200 mVac; Rp = 2,000 ohms	0.65	II	EB	---	17	vu
1231	Emission	Eb = Ec1 = Ec2 = 30 Vdc	0.65	II	Is	40	---	mAdc
(B) 1201	Short and discontinuity detection		0.4	II	---	---	---	---
	Quality conformance inspection, part 2							
1031	Low-frequency vibration	Rp = 2,000 ohms Ec1 = -30 Vdc	---	---	Ep	---	300	mVac
1301	Heater current		---	---	If	370	430	mA
(B) 1336	Heater-cathode leakage		---	---	Ihk	---	20	µAdc
1256	Electrode current (screen)		---	---	Ic2	3.0	8.0	mAdc
1306	Transconductance		---	---	Sm	1,800	2,800	µmhos
(B) 1211	Insulation of electrodes		4.0	S3	---	---	---	---
(B) 1126	Glass envelope strain		4.0	I	---	---	---	---
(B) 1101	Secureness of base, cap, or insert		---	---	---	---	---	---
(B) 1105	Permanence of marking		---	---	---	---	---	---
	Quality conformance inspection, part 3							
---	Life-test provisions	Group A; Eb = Ec2 = 300 Vdc; Ec1 = -24 Vdc; Ehk = 100 V	---	---	---	---	---	---
---	Life-test end point (500 hours)	Power output or Transconductance	--- ---	--- ---	Po Sm	1.8 1,500	--- ---	W µmhos

NOTES:

1. The base shall be phenolic and one of the following:
   Intermediate shell octal 7-pin, B7-7
   Intermediate shell octal 6-pin, B6-81
   Short intermediate shell octal 7-pin, B7-59
   Short intermediate shell octal 6-pin, B6-94.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:26Z
Check the source to verify that this is the current version before use.

NOTES: - Continued

2. See "Reduced pressure (altitude) rating", and altitude, maximum peak voltage.

3. This test to be performed at the conclusion of the holding period.

Custodians:
Army - EL
Navy - EC
Air Force - 80

Review activities:
Army - EL
Navy -
Air Force - 11, 80
DSA - ES

User activities:
Army - WC
Navy - AS, OS, MC, CG, SH
Air Force - 19

Preparing activity: Navy - EC

Agent: DSA - ES

(Project 5960-2425-30)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:26Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:26Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY
NAVAL ELECTRONIC SYSTEMS COMMAND
WASHINGTON, D. C. 20360

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

COMMANDER
NAVAL ELECTRONIC SYSTEMS COMMAND
DEFENSE STANDARDIZATION PROGRAM BRANCH
DEPARTMENT OF THE NAVY
WASHINGTON, D. C. 20360

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:26Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

S/N-0102-014-1801 C-25254

Source: https://assist.dla.mil -- Downloaded: 20260-15T13:26Z
Check the source to verify that this is the current version before use.