INCH-POUND

MIL-PRF-83726M
SUPPLEMENT 1
31 March 2026

PERFORMANCE SPECIFICATION SHEET

RELAYS, HYBRID AND SOLID STATE, TIME DELAY,
GENERAL SPECIFICATION FOR

This supplement forms a part of Performance Specification MIL-PRF-83726M, dated 31 March 2026

SPECIFICATION SHEETS

MIL-PRF-83726/7	-	Relays, Hybrid, Time Delay, on Pickup, Type I, Class A, 2 Amperes, 2PDT, Fixed Time, 0.06 to 300 Seconds
MIL-PRF-83726/12	-	Relays, Hybrid, Time Delay (on Release), Type IIA, Class B, 10 Amperes, 4PDT, Hermetically Sealed, Fixed Time, 0.100 to 300 Seconds
MIL-R-83726/14	-	Relays, Hybrid, Time Delay, (on Operate), Type I, Class B, 10 Amperes, 4PDT, Hermetically Sealed, Fixed Time, 0.100 to 300 Seconds
MIL-PRF-83726/18	-	Relays, Hybrid, Time Delay (on Release), Track Mounted, Type IIA, Class B, 10 Amperes, 2PDT, Hermetically Sealed, Fixed Time, 0.1 to 300 Seconds
MIL-PRF-83726/19	-	Relays, Hybrid, Time Delay (on Operate), Track Mounted, Type I, Class B, 10 Amperes, 2PDT, Hermetically Sealed, Fixed Time, 0.1 to 300 Seconds
MIL-PRF-83726/20	-	Relay, Solid-State, Time Delay (on Operate), Type I, Class C, SPST, 250 Milliamperes, Fixed Time, 0.05 to 500 Seconds
MIL-PRF-83726/21	-	Relay, Solid-State, Time Delay (on Operate), Type I, Class C, SPST, 250 Milliamperes, Variable Time, 0.05 to 500 Seconds
MIL-R-83726/22	-	Relays, Solid State, Repeat Cycle Timer, Type IV, Class C, SPST, 250 Milliamperes
MIL-PRF-83726/23	-	Relays, Hybrid, Time Delay (on Release), Type IIB, Class B, 10 Amperes, 4PDT, Hermetically Sealed
MIL-PRF-83726/24	-	Relays, Solid State, Time Delay (on Operate), Track Mounted, Type I, Class C, SPST, 150 Milliamperes, Fixed Time, 50 Milliseconds to 500 Seconds
MIL-R-83726/25	-	Relays, Solid State, Time Delay (on Release), Track Mounted, Type IIA, Class C, SPST, 150 Milliamperes, Fixed Time, .050 to 500 Seconds
MIL-PRF-83726/28	-	Relays, Hybrid, Time Delay (on Operate), Class B, Type I, Hermetically Sealed, DPDT, 10 Amperes, Fixed Time, 0.1 to 500 Seconds
MIL-PRF-83726/29	-	Relay, Hybrid, Time Delay (on Release), Class B, Type IIA, Hermetically Sealed, DPDT, 10 Amperes, Fixed Time, 0.1 to 500 Seconds
MIL-PRF-83726/30	-	Relay, Hybrid, Time Delay (on Operate), Class B, Type I, Hermetically Sealed, DPDT, 10 Amperes, Adjustable Time Delay (External Resistor), 0.1 to 500 Seconds

AMSC N/A

FSC 5945

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:26Z
Check the source to verify that this is the current version before use.

MIL-PRF-83726/31	-	Relay, Hybrid, Time Delay (on Release), Class B, Type IIA, Hermetically Sealed, DPDT, 10 Amperes, Adjustable Time Delay (External Resistor), 0.1 to 500 Seconds

Custodians:
Army – CR
Navy – EC
Air Force - 85
DLA – CC

Preparing activity:
DLA - CC

Review activity:
Navy – AS

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:26Z
Check the source to verify that this is the current version before use.