INCH-POUND

MIL-R-83726/19F
AMENDMENT 1
15 February 2000

MILITARY SPECIFICATION SHEET

RELAYS, HYBRID, TIME DELAY (ON OPERATE), TRACK MOUNTED, TYPE I, CLASS B, 10 AMPERES, 2PDT, HERMETICALLY SEALED, FIXED TIME, 0.1 TO 300 SECONDS

Inactive for new design after 23 June 1995.
No superseding document.

This amendment forms a part of MIL-R-83726/19F, dated 23 June 1995, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

Notes 5.: delete “MIL-R-6106/3” and “MIL-PRF-6106/5” and substitute “MIL-PRF-12883/49” and “MIL-PRF-12883/51”, respectively.

PAGE 3

Footnote 2/, delete “, B, or C” and “, X, or Y”.

PAGE 5

Table III, in title, delete “, B, or C”.

Transient voltage limits (input), delete “, X, or Y” and “, B, or C”.

PAGE 6

PIN’s with a suffix letter W, X, or Y: delete “, X, or Y”.

PIN’s with a suffix letter A, B, or C: delete “, B, or C”.

PAGE 8

PIN: delete “, and a suffix letter from table V (indicating the extent of EMI requirements and quality level) as follows:” and substitute “and a suffix letter W for relays with less stringent EMI requirements and a suffix letter A for relays with more stringent EMI requirements.”

Suffix letter: delete “from table V.” and substitute “W or A.”

Table V title, delete “and quality levels”

Examples: delete and substitute:

“M83726/19-1000W - 100 millisecond time delay, with less stringent EMI requirements,
M83726/19-1001A - 1 second time delay with more stringent EMI requirements”.

Custodians:
Navy - EC
Air Force – 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5945-1077-06)

Review activities:
Air Force - 99

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:28Z
Check the source to verify that this is the current version before use.