INCH-POUND

MIL-PRF-83726/21J
09 September 2019

SUPERSEDING
MIL-PRF-83726/21H
17 December 2015

PERFORMANCE SPECIFICATION SHEET

RELAY, SOLID-STATE, TIME DELAY (ON OPERATE), TYPE I, CLASS C, SPST, 250 MILLIAMPERES, VARIABLE TIME, 0.05 TO 500 SECONDS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the relay described herein shall consist of this specification and MIL-PRF-83726.

INACTIVE FOR NEW DESIGN AFTER 15 NOVEMBER 2002.
No superseding document.





FIGURE 1. Outline drawing and dimensions.


AMSC N/A

FSC 5945

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:28Z
Check the source to verify that this is the current version before use.



CIRCUIT DIAGRAM
(SEE NOTE 4)



TIMING DIAGRAM

Ltr	Inches		mm	
	Min	Max	Min	Max
A	---	.810	---	20.57
B	---	.310	---	7.87
C	.182	.192	4.62	4.88
D	.028 DIA	.033 DIA	0.71 DIA	0.84 DIA
E	.010	.020	0.25	0.51
F	---	.190	---	4.83
G	.020	.030	0.51	0.76
H	---	.410	---	10.41
J	.088	.098	2.24	2.49
K	.195 TYP	.205 TYP	4.95 TYP	5.21 TYP
L	.095 REF	.105 REF	2.41 REF	2.67 REF
M	.118 DIA	.122 DIA	3.00 DIA	3.10 DIA
N	---	1.280	---	32.51
P	1.057	1.067	26.85	27.10

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ± .010 (0.25 mm) for three place decimals and ± .03 (0.76 mm) for two place decimals.
4. Spare terminals are connected internally. Do not use for external tie points or for terminals.

FIGURE 1. Outline drawing and dimensions - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:28Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

OPERATING REQUIREMENTS:

Timing action: Delay-on-operate.

Time delay 1/: Adjustable (see table I) with external resistor according to the following formula:

$$R_{ext} = 100\ k\Omega((T/ T_m) - 1)$$

where T = desired time, T_m = minimum time, and $(T/ T_m) \leq 10$.

Timing accuracy 2/: +10 percent of the nominal value.

Recycle time 3/: 10 milliseconds.

Power interrupt: The accuracy will not be affected by power interruptions up to 1 millisecond spaced at least 10 milliseconds apart.

_____

1/ External resistor in accordance with MIL-PRF-55182, RNC60HXXXXFS or equal.
2/ The accuracy requirement applies for any combination of operating temperature and voltage.
3/ Recycle time is defined as the maximum time that power must be removed from the input terminals to assure that the next timing cycle will be completed within the specified timing tolerance. (Units can be recycled during timing or after time-out.)

TABLE I. Available time delays. 1/

Dash number		Time delay (seconds)
Printed circuit type terminals	Flange mounting	±10%
-001	-005	0.05 – 0.5
-002	-006	0.5 – 5
-003	-007	5 – 50
-004	-008	50 – 500

1/ CAUTION: Relays supplied to this specification sheet are susceptible to damage from electrostatic discharge under class I devices as defined by MIL-STD-1686 (see ESDS requirements herein).

INPUT REQUIREMENTS:

Input voltage: 28 V dc nominal; range 18 V dc to 32 V dc.

Duty rating: Continuous.

Current drain: 5 milliamperes maximum plus load at 25°C.

Polarity protection: The timer shall be inoperative during, and undamaged by, reversal of the polarity of the operating voltage.

OUTPUT REQUIREMENTS:

Configuration: SPST; switch closure to +28 V dc.

Rating: 250 milliamperes maximum.

Suppression: Inductive suppression provided for output protection.

Voltage drop: 2 V dc maximum.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:28Z
Check the source to verify that this is the current version before use.

Leakage current: 1.0 microampere maximum at 28 V dc and 25°C; 10 microamperes maximum at 28 V dc and 125°C.

Endurance: 1,000,000 cycles minimum for test.

Qualification: 2,000 hours or 1,000,000 cycles, whichever is less.

Group B: 1,000 hours or 1,000,000 cycles, whichever is less.

ELECTRICAL REQUIREMENTS:

Transients: In accordance with MIL-STD-704 for 28 volts dc system (figure 11).

Radio noise: MIL-STD-461, class 1D.

Motor load: Not applicable.

Insulation resistance: 1,000 megohms at 500 V dc at sea level, and 100 V dc at 80,000 feet between each pin and case.

Dielectric strength: 1,000 V rms at 60 Hz at sea level, and 350 V rms at 80,000 feet between case and pins connected together.

ENVIRONMENTAL REQUIREMENTS:

Ambient temperature (operating or nonoperating): -55°C to +125°C.

Vibration (sinusoidal): 10 Hz to 100 Hz at 0.06 inch DA; 100 Hz to 3,000 Hz at 30 g's.

Vibration (random): MIL-STD-202-214, condition I, letter J, duration of 30 minutes.

Maximum altitude rating: 80,000 feet.

Shock: 1,100 g's for 0.5 millisecond.

Acceleration: 100 g's.

Seal: MIL-STD-883, method 1014, condition B and condition C.

Moisture resistance: MIL-STD-202-106.

PHYSICAL REQUIREMENTS:

Dimensions and configurations: See figure 1.

Terminations: See figure 1.

Terminal strength: 3 pounds pull.

Weight: 0.5 ounce.

Marking: Marking shall be in accordance with MIL-PRF-83726. In addition, relays shall be marked with the ESDS identifier as specified in MIL-STD-1285.

Part or Identifying Number (PIN): The PIN consists of the prefix M83726/21- and a three digit dash number. 4/ 5/

Example: M83726/21-001

Suspension of inspections: Group B and group C inspections may be suspended at the discretion of the qualifying activity.

4/ Relays numbered prior to the date of this specification shall be considered interchangeable (store and issue).

5/ For dash numbers refer to table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:28Z
Check the source to verify that this is the current version before use.

CONFORMANCE INSPECTION:

Performance of groups B and C tests are not applicable.

The Qualified Products List (QPL) associated with this inactive for new design specification will be maintained until acquisition of the product is no longer required, whereupon this specification and the QPL will be canceled.

NOTE: As of 15 June 1999, MIL-PRF-83726 no longer specifies Quality Levels, but existing order configurations may still include them. Relays with a "W" quality level indicator at the end are interchangeable with relays without a quality level letter.

Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Referenced documents. In addition to MIL-PRF-83726, this document references the following:

MIL-STD-202-214
MIL-STD-202-106
MIL-STD-883
MIL-STD-461
MIL-STD-1285
MIL-STD-704
MIL-PRF-55182
MIL-STD-1686

Custodians:
Air Force - 85
DLA – CC

Preparing activity:
DLA - CC

Review activity:
Air Force - 19

(Project 5945-2019-022)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:28Z
Check the source to verify that this is the current version before use.