INCH-POUND

MIL-R-83726/14C
AMENDMENT 1
15 February 2000

MILITARY SPECIFICATION SHEET

RELAYS, HYBRID, TIME DELAY (ON OPERATE), TYPE I, CLASS B, 10 AMPERES, 4PDT, HERMETICALLY SEALED, FIXED TIME, 0.100 TO 300 SECONDS

Inactive for new design after 25 June 1993.
For new design use MIL-R-83726/28.

This amendment forms a part of MIL-R-83726/14C, dated 25 June 1993, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

Table I heading, delete "2/".

Footnote 2/, delete.

PAGE 5

Transients: delete and substitute "In accordance with MIL-STD-704 for 28 volts dc system (figure 11)."

Spike, delete.

Footnote 3/ and 4/, delete.

PAGE 6

Part or Identifying Number (PIN): delete "a four-digit dash number (expressed in milliseconds), and a quality level indication" and substitute "and a four-digit dash number (expressed in milliseconds)".

Quality level indication, delete.

Examples: delete and substitute "M83726/14-1000 - 100 millisecond time delay
M83726/14-1001 - 1 second time delay".

Custodians:
Navy - EC
Air Force - 11
DLA - CC

Review activities:
Air Force - 99

Preparing activity:
DLA - CC

(Project 5945-1077-04)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:27Z
Check the source to verify that this is the current version before use.