INCH-POUND

MIL-R-83726/22D
AMENDMENT 1
15 February 2000

MILITARY SPECIFICATION SHEET

RELAYS, SOLID STATE, REPEAT CYCLE TIMER, TYPE IV, CLASS C, SPST, 250 MILLIAMPERES

Inactive for new design after 26 October 1993. No superseding document.

This amendment forms a part of MIL-R-83726/22D, dated 31 August 1994, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

Transients: delete and substitute “In accordance with MIL-STD-704 for 28 volts dc system (figure 11).”

Spike, delete.

PAGE 5

Part or Identifying Number (PIN): delete “a suffix letter from table I (indicating the extent of EMI requirements and quality level) as follows:” and substitute “a suffix letter W for relays with less stringent EMI requirements and a suffix letter A for relays with more stingent EMI requirements”.

Suffix letter, delete “from table I” and substitute “W or A.”

Examples: delete and substitute:

“M83726/22-1000W - Time delay repeat cycle 1 per 100 ms with printed-circuit type mounting.
M83726/22-2500A - Time delay repeat cycle 4 per second with flange mounting”.

Custodians:
Navy - EC
Air Force - 11
DLA - CC

Review activities:
Air Force - 99

Preparing activity:
DLA - CC

(Project 5945-1077-07)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:28Z
Check the source to verify that this is the current version before use.