MILITARY SPECIFICATION SHEET

RELAYS, SOLID STATE, TIME DELAY (ON RELEASE), TRACK MOUNTED TYPE IIA, CLASS C, SPST, 150 MILLIAMPERES, FIXED TIME, .050 TO 500 SECONDS

This amendment forms a part of Military Specification Sheet MIL-R-83726/25E(USAF), dated 24 May 1985, and is approved for use by the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

TITLE: Delete and substitute as printed above.

PAGE 4

Part number, delete and substitute:

"Part number: Consists of the prefix M83726/25-, a four digit dash number (expressed in milliseconds), and a quality level indicator as follows:

M 83726/25 - 0500 W

Military designator

Specification sheet number

The first three digits are significant:
The four digit is the number of zeros to follow the first three digits. (The time is expressed in milliseconds and converted to seconds). See examples.

Quality level indicator (W, Y, or X) 6/
(See MIL-R-83726).

Examples: M83726/25-0500W 50 millisecond time delay W level.
M83726/25-2503X 250 second time delay X level.
M83726/25-5003Y 500 second time delay Y level."

FOOTNOTES, after 5/, add:

"6/ Any relays numbered prior to the date of this specification without a quality level indication shall be considered interchangeable (store and issue) with the "W" quality level."

Custodian:
Air Force - 85

Review activities:
Air Force - 99
DLA - ES

Agent:
DLA - ES

Preparing activity:
Air Force - 85

(Project 5945-F602-11)


FSC 5945

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:29Z
Check the source to verify that this is the current version before use.