INCH-POUND

MIL-R-83726/25G
AMENDMENT 1
15 February 2000

MILITARY SPECIFICATION SHEET

RELAYS, SOLID STATE, TIME DELAY (ON RELEASE) TRACK MOUNTED, TYPE IIA, CLASS C, SPST, 150 MILLIAMPERES, FIXED TIME, .050 SECONDS TO 500 SECONDS

Inactive for new design after 23 June 1995.
No superseding document.

This amendment forms a part of MIL-R-83726/25G, dated 23 June 1995, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

FIGURE 1. Dimensions and configuration of relay. Delete "CIRCUIT DIAGRAM (NEAR SIDE) NAMEPLATE (FAR SIDE)" and substitute "CIRCUIT DIAGRAM NAME PLATE (ONE ON NEARSIDE, ONE ON FARSIDE, LOCATION OPTIONAL)".

PAGE 4

Transients: delete and substitute "In accordance with MIL-STD-704 for 28 volts dc system (figure 11)."

Footnote 3/, delete.

PAGE 5

Part or Identifying Number: Delete "a four-digit dash number (expressed in milliseconds), and a quality level indicator" and substitute "and a four-digit dash number (expressed in milliseconds)'.

Quality level indicator, delete.

Examples: delete and substitute "M83726/25-0500 - 50 millisecond time delay,
M83726/25-2503 - 250 second time delay".

Custodians:
Navy - EC
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5945-1077-10)

Review activities:
Air Force - 99

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:29Z
Check the source to verify that this is the current version before use.