MILITARY SPECIFICATION

BRIDGE, ARMORED VEHICLE LAUNCHED, SCISSORING TYPE

CLASS 60, ALUMINUM, 60-FOOT SPAN

This amendment forms a part of Military Specification MIL-B-52088E(ME), dated 13 February 1978, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1, under SPECIFICATIONS, FEDERAL, delete:

"PPP-C-650 - Crates, Wood, Open and Covered."

2.1, under SPECIFICATIONS, FEDERAL add:

"UU-T-81 - Tag, Shipping and Stock."

2.1, under SPECIFICATIONS, MILITARY, delete: "Packaging" from title of MIL-P-116.

2.1, under SPECIFICATIONS, MILITARY, add:

"MIL-C-52950 - Crates, Wood, Open and Covered."

2.1, under SPECIFICATIONS, MILITARY, delete:

"MIL-H-6083 - Hydraulic Fluid, Petroleum Base, for Preservation and Operation."

And substitute:

"MIL-H-46170 - Hydraulic Fluid Rust Inhibited, Fire Resistant Synthetic Hydrocarbon Base".

2.1, under STANDARDS, FEDERAL, add:

"FED-STD-H28 - Screw Thread Standards"

FSC 5420

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-22T21:07Z
Check the source to verify that this is the current version before use.

PAGE 3

2.2, delete "NATIONAL BUREAU OF STANDARDS", in its entirety.

2.2, delete, "NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT" in its entirety.

* 2.2, Add:

"AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging.

(Applications for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103)."

PAGE 4

2.2, delete, "UNIFORM CLASSIFICATION COMMITTEE AGENT" in its entirety.

3.6, line 6, delete "MIL-H-6083" and substitute "MIL-H-46170".

PAGE 7

3.9, line 2, delete, "Handbook H28" and substitute "FED-STD-H28".

Add new paragraph 3.10.3 as follows:

"3.10.3 Tags. A cloth tag conforming to UU-T-81, type A, shall be wired, in a conspicuous location, to each hydraulic cylinder, ramp section, center section, and separate hose and pipe assemblies. The wire shall be corrosion resistant. The following information will be printed on the tag with waterproof ink: "THIS BRIDGE EQUIPPED WITH MIL-H-46170 (FRH OIL) USE ONLY WITH COMPATIBLE LAUNCHER."

* 3.11, line 2, delete, "Type B" and substitute "Type F for use on ferrous metals and Type G for use on non-ferrous metals".

PAGE 11

4.1.3, line 2, delete "Supplementary".

4.1.3, line 3, delete "(SQAP)" and substitute "(QAP)".

4.1.3, line 6, delete "SQAP" and substitute "QAP".

PAGE 13

4.6.1, lines 6 and 8, delete "SQAP" and substitute "QAP".

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:07Z
Check the source to verify that this is the currentversion before use.

PAGE 14

4.6.2.1, line 4 delete, "MIL-H-6083" and substitute "MIL-H-46170".

4.6.2.2, line 19, delete, "MIL-H-6083" and substitute "MIL-H-46170".

PAGE 16

* 4.7.1, line 2, delete, "Test Plan VII" and substitute "Test Plan 30-5".

PAGE 17

* 4.9.1, delete, "preproduction" and substitute "first article".

* 4.9.1.1, line 1, delete, "preproduction" and substitute "first article".

* 4.9.1.2, delete entirely and substitute:

*"4.9.1.2 Test. The first article pack of crated or boxed components for level A or B shall be subjected to the rail-impact test in accordance with MIL-STD-1186, appendix A. At the conclusion of the test, the first article pack shall be examined in accordance with the failure criteria of MIL-STD-1186; any non-compliance shall be cause for rejection of the pack."

PAGE 19

* 5.1, at six places, delete "preproduction" and substitute "first article".

PAGE 20

5.2.1.1.4, line 2, delete, "MIL-H-6083" and substitute MIL-H-46170".

PAGE 21

5.2.2, delete in its entirety and substitute:

"5.2.2 Commercial. The components of the bridge shall be preserved in accordance with ASTM D 3951. Additionally, all hydraulic cylinders shall be shipped fully charged with hydraulic fluid conforming to MIL-H-46170, and dust caps shall be placed on all hydraulic hoses."

5.3.1.1(a), line 4, delete "PPP-C-650, Style A, Type V, Class 1" and substitute "MIL-C-52950, style A, type V, non-demountable".

PAGE 22

5.3.3, delete in its entirety and substitute:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:07Z
Check the source to verify that this is the current version before use.

"5.3.3 Commercial. The components of the bridge shall be packed in containers in accordance with ASTM D 3951."

* 5.4.1, line 1, after "protection" add "levels A and B".

5.4.2, delete in its entirety and substitute:

"5.4.2 Commercial. Marking for commercial packaging shall be in accordance with ASTM D 3951. In addition, each shipping container shall display its gross weight and cube."

PAGE 23

* 6.2(g), delete "preproduction" and substitute "first article".

6.6, line 1, delete "Supplementary".

6.6, line 1, delete "(SQAP)" and substitute "(QAP)".

6.6, line 2 and 5, delete, "SQAP" and substitute "QAP".

* 6.7.1, delete entirely and substitute:

"6.7.1 Quality assurance provisions (QAP). QAP's are the documented requirements, procedures, and criteria necessary for demonstrating that designs conform to user requirements and that materiel and associated services conform to approved designs. QAP's provide a quality baseline and the means of auditing the product to assure user satisfaction."

* 6.8, delete "preproduction" in three places and substitute "first article."

Custodian:
Army - ME

Preparing activity:
Army - ME

Project 5420-A348

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:07Z
Check the source to verify that this is the current version before use.