MILITARY SPECIFICATION

COLLIMATOR, INFINITY AIMING REFERENCE: XM2

This amendment forms a part of Military Specification MIL-C-60159(MU), dated 20 November 1964.

Paragraph 3.7.1: Delete in its entirety and substitute the following:

"3.7.1 Elevation travel.- The collimator shall provide a minimum of minus (-) 800 mils for depression of the line of sight and plus (+) 655 mils for elevation of the line of sight, when the tripod legs are fully extended and resting on a horizontal surface."

Paragraph 3.7.2: Delete in its entirety and substitute the following:

"3.7.2 Azimuth travel.- The collimator shall provide unrestricted azimuth rotation of 6400 mils in either direction when the line of sight is parallel with a horizontal surface."

Paragraph 3.8 Operability.- Delete second sentence and substitute:

"The torque required to close and open the leg assemblies shall be 21 ± 3 inch-pounds."

Paragraph 3.8.2, sub-paragraph (a) Rotating collimator in azimuth on tripod.- Delete "50 pound-inches" and substitute "35 pound-inches".

Paragraph 3.8.2, sub-paragraph (c) Elevating the collimator.- Delete "8 pound-feet" and substitute "6 pound-feet minimum".

Paragraph 3.8.3 Scope alinement.- Delete "shall not be less than 5 pound-inches nor more than 15 pound-inches" and substitute "shall not exceed 15 pound-inches".

Paragraph 4.5.5.1: Delete in its entirety and substitute the following:

"4.5.5.1 Elevation travel.- Perform this test with the tripod legs fully extended and resting on a horizontal surface. A calibrated wall target capable of measuring the elevation travel of the collimator as specified in 3.7.1 shall be utilized with this test. Construction of the wall target shall contain an established level line of sight mark and a plumb line. Establish coincidence of the vertical and horizontal reticle lines of the collimator with respect to the plumb line and the established level line of sight. A calibrated auxiliary telescope of at least three power (3X), containing a vertical and horizontal reticle line shall be attached to the collimator. Establish coincidence of the vertical and horizontal reticle lines of the auxiliary telescope with respect to the plumb line

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:13Z
Check the source to verify that this is the current version before use.

and the established level line of sight. Release the elevation clamping mechanism. Direct a line of sight through the auxiliary telescope to the target. While observing the horizontal reticle line of the telescope, actuate the collimator the maximum elevation, then to maximum depression. The limit of elevation and depression shall meet the minimum values specified in 3.7.1, as measured on the target."

Paragraph 4.5.5.2: Delete in its entirety and substitute the following:

"4.5.5.2 Azimuth travel.- Perform this test in sequence with 4.5.5.1. Establish the collimator line of sight parallel with the horizontal surface by means of the auxiliary telescope. With the vertical reticle line of the auxiliary telescope alined to the plumbed line of the wall chart, and the azimuth clamping mechanism released, the collimator shall be rotated clockwise 6400 mils, then rotated counterclockwise 6400 mils. The collimator shall meet the requirements of 3.7.2."

Paragraph 4.5.6.1: Delete in its entirety and substitute the following:

"4.5.6.1 Operability.- Standard torque measuring equipment capable of measuring the torque values specified in 3.8 shall be utilized for this test. An appropriate adapter to accommodate the leg assemblies shall be used with the torque measuring equipment. Torque shall be measured while opening and closing each leg assembly through their full range of travel. The running torque required to open and close the leg assemblies shall conform to the applicable requirements of 3.8. The collimator shall also be subjected to a visual and tactile examination when manually set up in the operational position from the carrying position to determine overall compliance with 3.8."

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1240-A538Y

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:13Z
Check the source to verify that this is the current version before use.