MIL-C-60262 (MU)
1 April 1966
SUPERSEDING
FA-PD-MI-2476, Rev 1
14 January 1963

MILITARY SPECIFICATION
CUTTER, POWDER ACTUATED, REEFING LINE, M9, ASSEMBLY

1. SCOPE

1.1 This specification covers Cutter, Powder Actuated, Reefing Line, M9, Assembly, loaded with Cartridge, Powder Actuated Cutter, M129 for use in connection with cargo parachute controlled airdrops.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS
Military
- MIL-A-2550 - Ammunition and Special Weapons, General Specification For
- MIL-W-5625 - Webbing; Nylon Tubular

STANDARDS
Military
- MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
- MIL-STD-109 - Quality Assurance Terms and Definitions
- MIL-STD-1167 - Ammunition Data Card

DRAWINGS
Munitions Command
- D10520535 - Cutter, Powder Actuated, Reefing Line, M9, Assembly
- C8864327 - Carton, Packing, Ammunition for Cutters, Powder Actuated, Reefing Line, M9, XM10, XM11, XM12 or M13 with Cartridge
- C8864326 - Box, Packing, Ammunition for Cutter, Powder Actuated, Reefing Line, M9, XM10, XM11, XM12 or M13 with Cartridge
- IEL-10520535 - Index to Inspection Equipment List for Cutter, Powder Actuated, Reefing Line, M9, Assembly

FSC 1377

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:24Z
Check the source to verify that this is the current version before use.

2.1 (cont)

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 General.- Materials, parts and assemblies shall comply with the requirements specified on the applicable drawings and referenced specifications.

3.2 Functional.

3.2.1 The cutter shall not fail to fire.

3.2.2 The cutter shall function without mechanical failure (see 6.1).

3.2.3 Ballistics.- The cutter loaded with an accepted M129 Cartridge, temperature conditioned as required in Table I, shall completely sever two lines of 1/2 inch, 1000-pound tubular nylon webbing fabricated in accordance with MIL-W-5625, within the Delay Time specified in Table I.

Table I

Temperature	Delay Time, Seconds (see 6.2)
- 65° to - 70° F	2.4 max
65° to 75° F	1.8 min to 2.2 max
160° to 165° F	1.6 min

3.3 Workmanship.- The requirements for workmanship are as specified on the applicable drawings, referenced specifications and the following:

3.3.1 Metal defects.- The part shall be free from cracks, splits, cold shuts, inclusions, porosity or other metal defects.

3.3.2 Burr.- The part shall not have a burr which might interfere with the assembly or function of the item or which might be injurious to personnel handling the item.

3.3.3 Foreign matter.- The part or assembly shall not contain chips, dirt, grease, rust, corrosion or other foreign matter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:24Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Quality assurance terms and definitions.- Reference shall be made to MIL-STD-109 to define the quality assurance terms used.

4.1.2 Inspection.- Inspection shall be in accordance with MIL-A-2550.

4.2 Inspection provisions.

4.2.1 Lot.

4.2.1.1 Submission of product.- The product shall be submitted in accordance with MIL-STD-105.

4.2.1.2 Size of lot.- A lot shall consist of an identifiable group of assembled units containing metal parts assemblies produced by a homogeneous process and loaded with a single lot of cartridges.

4.2.2 Examination.- One hundred percent examination shall be performed for all critical defects. Examination for major and minor defects shall be performed on a defect basis in accordance with the classification of defects contained herein, using the sampling plan and associated criteria in Table II. All nonconforming material shall be rejected. The total number of allowable defects per class for either the major or minor classification shall not exceed the acceptance number of Table II. Four power magnification may be used in performing visual examination for such defects as burr and foreign matter.

Table II

Lot Size	Sample Size	Major		Minor	
		Accept	Reject	Accept	Reject
1- 300	100% examination	-	-	-	-
301- 800	50	0	1	1	2
301-1800	90	1	2	2	3

4.2.2.1 Cartridge, Reefing Line Cutter, M129, Drawing D10520297.

Defect	Method of Inspection
CRITICAL	
1. Mixed cartridges	Visual
2. Metal defective	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:24Z
Check the source to verify that this is the current version before use.

4.2.2.1 (cont) CRITICAL

Defect	Method of Inspection
3. "O" ring missing	Visual
4. Marking missing, incorrect or illegible	Visual
MAJOR	
101. "O" ring split, cut or cracked	Visual
102. Foreign matter	Visual
MINOR	
201. Case scratched or dented	Visual

4.2.2.2 Cutter, Powder Actuated, Reefing Line, M9, Assembly, Drawing D10520535.

CRITICAL	
1. Firing pin not cocked	X-ray - Manual 1/
2. Any part missing	X-ray - Visual 1/
3. Improper assembly	X-ray - Visual 1/
4. Mixed reefing line cutters	Visual
5. Marking missing, incorrect or illegible	Visual
MAJOR	
101. Front of anvil not flush or slightly below reefing line holes	Visual
102. Metal defective	Visual
103. Security of assembly	Manual
MINOR	
201. Reefing line holes obstructed	Visual
202. Protective finish inadequate or defective	Visual
203. Burr	Visual
204. Foreign matter	Visual

Note.- 1/ The cutter shall be X-rayed with the long axis of the reefing line cutter perpendicular to the rays of the X-ray machine.

4.2.2.3 Carton, Packing, Ammunition for Cutter, Powder Actuated, Reefing Line M9, XM10, XM11, XM12 and M13 with Cartridge, Drawing C8864327.

CRITICAL
None defined.

MAJOR
None defined.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:24Z
Check the source to verify that this is the current version before use.

4.2.2.3 (cont)

Defect	Method of Inspection
MINOR	
201. Contents loose	Manual and Visual
202. Quantity of contents incorrect	Visual
203. Separator or filler missing	Visual
204. Cut or damaged through all carton layers	Visual
205. Marking missing, incorrect or illegible	Visual
206. Carton sealing defective, improper or missing	Visual

4.2.2.4 Box, Packing, Ammunition for Cutter, Powder Actuated, Reefing Line, M9, XM10, XM11, XM12 and M13 with Cartridge, Drawing C8864326.

CRITICAL
None defined.

MAJOR
None defined.

MINOR	
201. Contents loose	Manual and Visual
202. Quantity of contents incorrect	Visual
203. Contents of box exposed	Visual
204. Box damaged	Visual
205. Strapping missing, loose, broken or improperly applied	Visual
206. Marking missing, incorrect or illegible	Visual
207. Car seal missing, unsealed or improperly positioned	Visual

4.2.3 Inspection testing.- The following tests shall be performed in accordance with the provisions of 4.3:

4.2.3.1 Function.- The following tests shall be performed by the Government:

4.2.3.1.1 Ballistics.- Thirty assembled reefing line cutters of each lot shall be grouped, temperature conditioned as specified in Table III and 4.3.1.2, and then tested in accordance with 4.3.1.1. Failure of any reefing line cutter to comply with the requirements of 3.2 shall be cause for rejection of the lot.

Table III

Temperature	Sample Size
-65° to -70° F	10
65° to 75° F	10
160° to 165° F	10

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:24Z
Check the source to verify that this is the current version before use.

4.2.4 Inspection equipment.- The examination and tests shall be made using the equipment listed on IEL-10520535.

4.3 Test method and procedures.

4.3.1 Function.

4.3.1.1 Ballistics.- The test sample shall be rigidly supported in the test fixture. The sample shall be tested within five minutes after removal from the conditioning chamber. When this time limit is exceeded, the sample shall be reconditioned in accordance with 4.3.1.2.

4.3.1.2 Temperature conditioning.- A standard M9 Reefing Line Cutter, loaded with a dummy M129 Cartridge, containing a temperature sensitive element, shall be placed in the conditioning chamber at the same time as the samples. The conditioning time shall be a minimum of one hour longer than the time necessary to bring the element contained in the dummy cartridge to the required temperature.

5. PREPARATION FOR DELIVERY

5.1 Packing and marking.- Packing and marking shall be in accordance with Drawings C8864326 and C8864327.

5.2 Data card.- Data card information shall be as specified in MIL-STD-1167.

6. NOTES

6.1 A mechanical failure is defined as any deformation or breakage of a part, the occurrence of which is other than a design function.

6.2 Delay time is defined as the time elapsed between initiation of the cable withdrawal and the complete severing of the reefing line.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1377-A012

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:24Z
Check the source to verify that this is the current version before use.

To detach this form, cut along this line

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

ORGANIZATION | CITY AND STATE

CONTRACT NO. | QUANTITY OF ITEMS PROCURED | DOLLAR AMOUNT $

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)* | DATE

DD FORM 1 OCT 64 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:24Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

POSTAGE AND FEES PAI

DEPARTMENT OF THE AR

Frankford Arsenal
Philadelphia, Pa. 19137

OFFICIAL BUSINESS

Commanding Officer
Frankford Arsenal
ATTN: SMUFA-N1100
Philadelphia, Pa. 19137

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:24Z
Check the source to verify that this is the current version before use.