INCH-POUND

MIL-M-49239A(CR)
AMENDMENT 1
30 June 1992

MILITARY SPECIFICATION

MULTIPLEXER-COMBINER, TD-1234(P)/TTC

This amendment forms part of MIL-M-49239A(CR), dated 30 October 1986, is approved for use by the Communication-Electronics Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 8

3.7.4.6: Delete and substitute:

"3.7.4.6 Transmit Level - (See 4.7.4.6) For an input at either group of + 1 1/2 dBm, the output at the other group shall be +5 dBm ±1/2dB measured into a 58 Ohm resistive load. For an input at the passive interface of +21.3 dBm, the output at the appropriate group shall be -11.5dBm ±1.5dB measured into a 600 ohm resistive load."

PAGE 13

3.7.11: Delete "(See 4.7.11.1)" and substitute "(See 4.7.11)"

PAGE 14

3.7.13.1: Delete and substitute:

"3.7.13.1 Digital Channel Check - There shall be no errors for a period of 30 seconds with the orderwires on."

PAGE 23

Replace note identified by double asterisk (**) by the following:

"** One time only first article test not to be performed during Group C production lot testing."

PAGE 26

On Table II Group A Inspections: Change the following:

Under Visual-Mechanical requirements for the Analog Applique Unit and Group Modem, change the requirement paragraph from "3.14" to "3.15". For Group Modem change inspection paragraph from "4.14" to "4.13".

AMSC No. N/A FSC 5820
Distribution Statement A. Approved for public release; Distribution is unlimited.

Source: https://assist.dla.mil - Downloaded: 2026-10-22T19:56Z
Check the source to verify that this is the current version before use.

On Table II Group A Inspections: Add the following:

Under Visual-Mechanical requirements add "3.14" in the requirement paragraph column for each circuit card listed.

PAGE 29

On Table IV Group C Inspections: Change the following:

Subgroup 4, Dust inspection paragraph from "5.8.4" to "4.8.4".

PAGE 32

On Table VII Special Test Equipments: Add the following:

Under Timing Source Drawing Number column "A305166" and under functional description: "The timing source provides four independent group outputs, switch selectable to positions between 72 and 4608 kb/s. Also, provided are four independent Station Clock/ Telemetry Clock outputs, switch selectable to 2, 16 or 32 kHz."

PAGE 33

On Table VIII Government Furnished Equipment: Add the following:

Under equipment column "Remote Loop Group Multiplexer-TD-1233(P)/TTC" and under description column "The Remote Loop Group Multiplexer time division multiplexes/ demultiplexes up to 4 analog or conditioned diphase loops into/from a 4 1/2 channel group. The group input/output is a conditioned diphase signal. This equipment must be configured with Loop Modem CCAs or Analog Applique Unit CCAs in all channel slots."

PAGE 37

4.7.1.3b,j: line 1: Delete "A10" and substitute "A15".

4.7.1.3.e: Delete"VL" and substitute "VI" in the impedance formula.

PAGE 39

4.7.2.1.d: line 2: Delete "300 Hz" and substitute "300kHz".

4.7.2.1.c,f: Delete "VL" and substitute "VI" in the impedance formula.

PAGE 40

4.7.3.2: Delete paragraph's title "Input Impedance" and substitute "Input Load Impedance".

PAGE 41

4.7.3.3.d: Delete I/O pin number "23" and substitute "21".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:56Z
Check the source to verify that this is the current version before use.

PAGE 44

4.7.4.6i: Delete "58 ohms" and substitute "600 ohms".

PAGE 46

4.7.5.3.i: Delete "Zout=124 V1/V2-1 ohms" and substitute "Zout=125 [(V1/V2)-1] ohms".

PAGE 47

4.7.5.5.c: line 2: Delete "figure 28" and substitute "figure 31".

PAGE 48

4.7.6.j: Delete "3.7.4" and substitute "3.7.6".

PAGE 50

4.7.7.8.1.a: Delete the word "no" and substitute "the".

PAGE 50

4.7.7.8.2: Delete "4 Analog Channels" and substitute "4 Analog Circuit Cards".

4.7.7.8.2.c,h: line 3: Delete "+6 dBm" and substitute "+6dB".

PAGE 51

4.7.7.9.c: line 2: Delete "+10 dBm" and substitute "+10 dB".

PAGE 63

4.7.13.3: line 3: Delete "3.7.13.2" and substitute "3.7.13.3".

PAGE 64

4.7.13.7.c: line 2: Delete "3.7.13.5" and substitute "3.7.13.7".

PAGE 66

4.8.3: Add the following after Altitude: "(See 3.8.3)"

PAGE 67

4.8.8.1: Delete and substitute:

"4.8.8.1 Vibration - The equipment shall be subjected to test of MIL-STD-810C, Method 514.2, Procedure X (Curve AW), Part II, as specified below. Perform a Unit Performance Electrical Test and Visual Inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-05-24T19:56Z
Check the source to verify that this is the current version before use.

Vibration in each of the three (3) principal axes shall be performed in the following sequence.

Install the unit equipment mounting brackets on the UUT and install the unit on the vibration exciter in the vertical axis (top to bottom). Install the control accelerometers on the vibration fixture.

SINUSOIDAL VIBRATION PROFILE

TEST LEVEL:	1.5g
FREQUENCY RANGE:	5.0 Hz to 200 Hz to 5.0 Hz
SWEEP RATE:	5.0 hZ TO 200 hZ TO 5.0 Hz in twelve (12) minutes.
TIME DURATION:	84 Minutes per axis

Subject the unit to the vibration levels specified in the vibration profile from 5Hz to 200 Hz over a period of six (6) minutes, while monitoring the control accelerometer(s). Verify that the monitored response of the control accelerometer(s) is within 10 percent of the specified 1.5g input thru the entire frequency range of 5.0 Hz to 200 Hz.

Cycle the unit in accordance with the vibration profile. Vary the frequency at the sinusoidal rate from 5.0 Hz to 200 Hz to 5.0 Hz within 12 minutes. (This constitutes one (1) cycle.) Subject the unit to 7 cycles of vibration for a total test time of 84 minutes. (This includes the 6 minutes recorded previously).

Repeat Steps with the unit oriented in side-to-side and front-to-back axes.

Perform a Unit Electrical Performance Test and Visual Inspection."

PAGE 92

On Figure 17 Input and Output Impedance: Delete "DIGITAL CHANNELS 9-16" on UUT.

PAGE 96

On Figure 21 Loop Power Feed Load:In the NOTE: Delete the value of R1 "11.2K ± 1% O.5W" and replace with "680±1% Ohms 5W" and delete the value of R2 "680±1% Ohms 5W" and replace with "11.2k±1% Ohms 0.5W."

Custodian:
Army - CR

PREPARING ACTIVITY
Army - CR
Project 5820-A946

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:56Z
Check the source to verify that this is the current version before use.