MIL-T-52518B(ME)
25 August 1981
SUPERSEDING
MIL-T-52518A
14 November 1975

MILITARY SPECIFICATION

TRAINING AID, SCALE, DECLINATION, MAP READING

This specification is approved for use by the Mobility Equipment Research and Development Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a 12-3/4-inch by 26-inch panel, with angle graduations from zero to 15 degrees, mounted on a hinged hanging bracket.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

QQ-S-781	- Strapping, Steel, and Seals.
PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-636	- Boxes, Shipping, Fiberboard.
PPP-B-640	- Boxes, Fiberboard, Corrugated, Triple-Wall.

MILITARY

MIL-P-116	- Preservation, Methods of.

FSC 6910

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Mobility Equipment Research and Development Command, ATTN: DRDME-DS, Fort Belvoir, VA 22060 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:21Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-130	- Identification Marking of US Military Property.
MIL-STD-1188	- Commercial Packaging of Supplies and Equipment.

DRAWINGS

ME

D13211E7410	- Scale, Declination.

(Copies of specifications, standards, and drawing required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Description. The declination scale shall conform to Drawing D13211E7410 and as specified herein.

3.1.1 Drawing. The drawing forming a part of this specification is an end product drawing. No deviation from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. Where tolerances could cumulatively result in incorrect fits, the contractor shall provide tolerances within those prescribed on the drawing to insure correct fit, assembly, and operation of the declination scale. Any data (e.g., shop drawings, layouts, flow sheets, processing procedures, etc.) prepared by the contractor or obtained from a vendor to support fabrication and manufacture of the production item shall be made available, upon request, for inspection by the contracting officer or his designated representative.

3.2 Material. Material shall be as specified herein and on the applicable drawing. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification (see 6.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:21Z
Check the source to verify that this is the current version before use.

3.3 Identification marking. The declination scale shall be identified in accordance with MIL-STD-130.

3.4 Workmanship. The declination scale shall be uniform in quality and texture with no evidence of cracks or blisters. Corners, edges, and adjacent surfaces shall be free of loose or peeled fibers. Metal components shall be free of sharp edges and burrs.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. The contractor is responsible for insuring that components and materials used are manufactured, examined, and tested in accordance with referenced specifications, standards, and drawing, as applicable.

4.2 Classification of inspections. Inspection requirements specified herein are classified as follows:

(a) Quality conformance inspection (see 4.3).
(b) Inspection of packaging (see 4.5).

4.3 Quality conformance inspection.

4.3.1 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.3.2 Examination. Samples selected in accordance with 4.3.1 shall be examined as specified in 4.4.1. AQL shall be 2.5 percent defective.

4.4 Inspection procedure.

4.4.1 Examination. The scales shall be examined as specified herein for the following defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:21Z
Check the source to verify that this is the current version before use.

101. Dimensions not as specified.
102. Materials not as specified.
103. Paint not as specified.
104. Marking not as specified.
105. Components missing or not properly assembled.
106. Welded or brazed joints not as specified.
107. Identification marking not as specified.
108. Workmanship not as specified.

4.5 Inspection of packaging.

4.5.1 Quality conformance inspection of pack.

4.5.1.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.5.1.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.5.1.3 Examination. Samples selected in accordance with 4.5.1.2 shall be examined for the following major defects. AQL shall be 2.5 percent defective.

109. Materials, methods, or containers not as specified for Level A or Level B. Each incorrect material, method, or container shall constitute one defect.
110. Consolidation not as specified for Level A.
111. Gross weight exceeds the limitations of the box specification for Level A or Level B.
112. Marking missing, illegible, incorrect, or incomplete.

5. PACKAGING

5.1 Preservation. Preservation shall be Level A or Commercial, as specified (see 6.2).

5.1.1 Level A. Each scale shall be preserved in accordance with MIL-P-116, Method IC-1 or IC-3. Bending of the scale shall not be permitted. The bracket on the scale shall be secured and cushioned to prevent damage to the bag or graduations and painted surfaces.

5.1.1.1 Consolidation. The preserved scales shall be consolidated in a close-fitting box conforming to PPP-B-636, W5c, style optional, in quantities not to exceed the weight limitation of the box specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:21Z
Check the source to verify that this is the current version before use.

5.1.2 Commercial. Commercial preservation shall be in accordance with MIL-STD-1188.

5.2 Packing. Packing shall be Level A, Level B, or Commercial, as specified (see 6.2).

5.2.1 Level A. Scales, preserved and consolidated as specified above shall be packed in a close-fitting box conforming to PPP-B-601, Overseas Type, Grade B, style optional, in quantities not to exceed the weight limitation of the box. Box closure and strapping shall be in accordance with the appendix to the box specification. Strapping shall conform to QQ-S-781, Class 1, Type I or IV, size as applicable; and, unless otherwise specified herein, shall be Finish B. When specified (see 6.2), Finish A strapping shall be used.

5.2.2 Level B. Scales, preserved and consolidated as specified above shall be packed in close-fitting boxes conforming to PPP-B-636, V3c, style optional, or PPP-B-640, Class 2, style optional. The gross weight shall not exceed the limitations of the box specification.

5.2.3 Commercial. Commercial packing shall be in accordance with MIL-STD-1188.

5.3 Marking. Marking for military levels of protection shall be in accordance with MIL-STD-129. Commercial marking shall be in accordance with MIL-STD-1188.

6. NOTES

6.1 Intended use. The scale is a component of a map reading set and is intended to be used to illustrate declination of magnetic and grid north from true north.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Degree of preservation and degree of packing required (see 5.1 and 5.2).
(c) When Finish A strapping is required (see 5.2.1).

6.3 Recycled material. It is encouraged that recycled material be used, when practical, as long as it meets the requirements of this specification (see 3.2).

Custodian:
Army - ME

Preparing activity:
Army - ME

Project 6910-0413

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:21Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Mobility Equipment Research and
Development Command
ATTN: DRDME-DS
Fort Belvoir, VA 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:21Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-T-52518B(ME) Training Aid, Scale, Declination, Map Reading

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:21Z
Check the source to verify that this is the current version before use.