MILITARY SPECIFICATION

VALVE, ANTIBACK DRAFT, PROTECTIVE SHELTER, M2

This amendment forms a part of MIL-V-0050010A(MU), dated 18 March 1969, and is approved for use within the Chemical Research, Development and Engineering Center, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1: Under "SPECIFICATIONS" "FEDERAL" delete "TT-W-00572" and its title.

PAGE 2

2.1: Under "DRAWINGS" delete "D150-2-1" and its title.

2.2: Delete "Uniform Classification Committee" and the next 8 lines and substitute the following:

"ASTM STANDARDS

D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to ASTM, 1916 Race Street, Philadelphia, PA 19103.)"

PAGE 4

4.4.3.1, line 2: Change "preparation for delivery" to "packaging".

PAGE 6

4.4.3.2(c): Change title to read "Packaging inspection (section 5)".

Section 5: Change title to read "Packaging".

AMSC N/A FSC 4240

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:13Z
Check the source to verify that this is the current version before use.

5.2: Change to read "Preservation and unit packing. Levels shall be as specified (see 6.2)."

5.2.1:

Delete paragraph in its entirety.

Add title "Level A."

Add new paragraph 5.2.1.1 as follows:

"5.2.1.1 Repainting. Damaged portions of painted areas of the antiback-draft valve shall be treated and repainted in accordance with MIL-T-704, type G for exterior surfaces and type C for interior surfaces, using the same kind of paint and color of paint as specified on the drawing."

Add new paragraph 5.2.1.2 as follows:

"5.2.1.2 Unpainted metal surfaces. Such areas including exposed threaded areas shall be coated with type P-2 preservative compound conforming to MIL-P-116."

Add new paragraph 5.2.1.3 as follows:

"5.2.1.3 Antiback-draft valve assembly (D5-65-32). The valve cover shall be secured in the closed position by taping around the cover seam with type IV pressure sensitive tape conforming to PPP-T-60. The adjustable flange shall be secured to the flange as follows: Insert one end of the threaded shaft approximately 1-1/2 inches through the center hole in one end of the mounting flange and screw the counterweight down tightly against the mounting flange surface. Install two of the nuts on the portion of the threaded shaft protruding through the mounting flange tightly securing the shaft in place. Install the third nut on the opposite end of the shaft screwing it down tightly against the counterweight to prevent it from working loose (see Dwg D5-65-126). To prevent movement of the counterweight arm, apply a piece of type IV tape conforming to PPP-T-60 around the arm drawing the ends of the tape tight and securing these ends to the outside of the valve body."

5.2.2: Delete paragraph in its entirety and substitute the following:

"5.2.2 Industrial. The antiback-draft valve (D5-65-32) shall be cleaned, preserved and unit packed in accordance with ASTM D 3951."

5.3.1: Delete paragraph in its entirety and substitute the following:

"5.3.1 Level A. The antiback-draft valve, preserved and unit packed as specified in 5.2.1, shall be packed in an overseas type, style A, weight of contents 0-100 pounds, type 2 load, cleated plywood box conforming to PPP-B-601.

Source: https://assist.dla.mil Downloaded: 2026-10-22T20:13Z
Check the source to verify that this is the current version before use.

The box shall be of minimum cube required to contain the valve. The box shall be closed and strapped in accordance with the appendix of the box specification. Strapping and seals shall conform to QQ-S-781 (strapping - type I regular duty, finish B, grade 2, and seals - type D, style I or IV, zinc coated, class R, grade 2)."

5.3.2, line 1: Change "packaged" to "unit packed".

PAGE 9

5.3.3: Delete paragraph in its entirety and substitute the following:

"5.3.3 Industrial. The antiback-draft valve (D5-65-32), preserved and unit packed as specified in 5.2.2, shall be packed in accordance with ASTM D 3951."

5.4: Delete paragraph in its entirety and substitute the following:

"5.4 Marking. In addition to any special markings required by the contract or order, level A unit packs (5.2.1) and level A and B packs (5.3.1 and 5.3.2) shall be marked in accordance with MIL-STD-129. The industrial unit packs (5.2.2) and packs (5.3.3) shall be marked in accordance with ASTM D 3951."

6.2(b): Change "packing" to "unit packing".

Custodian:

Army - MU

Preparing activity:

Army - MU(EA)

(Project No. 4240-A922)

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:13Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:13Z
Check the source to verify that this is the current version before use.