
MILITARY SPECIFICATION SHEET

POWER DIVIDER/COMBINERS, N-WAY, 0 DEGREES, TNC CONNECTORS

This specification sheet is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the power divider/combiners described herein shall consist of this document and the latest issue of specification MIL-P-23971.




INCHES	MM	INCHES	MM
.01	3	.44	11.2
.02	5	.49	12 4
.04	1.0	.56	14.2
.05	1 3	85	21 6
.14	3 6	94	23 9
.16	4 1	1 01	25 7
.38	9.7	1.23	31 2
41	10 4	1 44	36 6
		1 75	44 4

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only and are based upon 1.00 inch = 25 4 mm.

FIGURE 1 Dimensions and configuration, 2-way, dash number 01

FSC 5985

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:38Z
Check the source to verify that this is the current version before use.




INCHES	MM	INCHES	MM
.01	.3	.48	12.2
.02	.5	.56	14.2
.03	.8	.75	19.0
.08	2.0	.85	21.6
.23	5 8	1.12	28.4
.25	6 4	1.24	31.5
29	7.4	1 70	43.2
.40	10.2		

NOTES:
1. Dimensions are in inches
2. Metric equivalents are given for general information only and are based upon 1.00 inch = 25 4 mm.

FIGURE 2 Dimensions and configuration, 2-way, dash number 02

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:38Z
Check the source to verify that this is the current version before use.



INCHES	MM	INCHES	MM
.01	3	.50	12.7
.02	.5	.56	14 2
.04	1 0	73	18.5
.05	1 3	.94	23 9
14	3 6	1 01	25.7
.35	8.9	1 23	31 2
.37	9.4	1.44	36.6
.49	12 4	1.75	44 4

NOTES:
1. Dimensions are in inches
2. Metric equivalents are given for general information only and are based upon 1 00 inch = 25 4 mm

FIGURE 3 Dimensions and configuration, 3-way, dash number 03

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:38Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical performance characteristics and physical requirements.

M23971 17	Impedance (ohms)	Frequency range MHz	Average coupling (dB)	VSWR max	Insertion loss max (dB)	Isolation min (dB)	Phase balance max (degree)	Amplitude balance (dB) max	Power level avg (W)	Power level pk (W)	Weight pounds (grams)	Ambient temperature Operating	Ambient temperature Storage	Figure
01	50	.05-20	3. +.2 -.0	1.3:1	0.5	30	±1.0	±0.2	-	2	.14 (64)	55° to +85°C	-65° to +100°C	1
02	50	1-100	3. +.2 -.0	1.3:1	0.5	30	±1.0	±0.2	-	5	.16 (73)	0° to +40°C	-40° to +500°C	2
03	50	200-400	4.8 +.3 -.0	1.3:1	0.75	25	±2.0	±0.2	-	5	.15 (70)	55° to +85°C	-65° to +100°C	3

TABLE II. Environmental tests, In accordance with MIL-P-23971 except

M23971/17-	Thermal Shock	Terminal strength	Vibration, high frequency	Shock
01, 03	test condition A	test condition C 1 pound load 1/	test condition D	test condition A

1/ This test shall be performed in addition to the terminal strength test in accordance with 4.7.13.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:38Z
Check the source to verify that this is the current version before use.

REQUIREMENTS

Design and construction See figures 1 through 3

Case. O-ring seal.

Electrical characteristics. See table I.

Weight See table I

Ambient temperature See table I.

Environmental requirements. See table II.

Part number M23971/17-(dash number from table I).

Note: Power dividers covered by this specification sheet are substituted for the following manufacturer's part number. This information in no way implies that the manufacturer's part is suitable as a substitute for the military part number

Dash number	Manufacturer's code	Manufacturer's part number	FSN
01	13499 12457	277-0431 PD-20-10 MOD3	
02	52151 12457	320-0035 PD-20-50-TNC-MOD-2	
03	13499 12457	277-0430-010 PD-30-300	

Custodians
Army - ER
Navy - EC
Air Force - 85

Review activities
Army -
Navy -
Air Force -
DLA - ES

User activities
Army -
Navy - AS, OS, MC
Air Force -

Preparing activity
Navy - EC

Agent
DLA - ES

(Project 5985-0903)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:38Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY
NAVAL ELECTRONIC SYSTEMS COMMAND
WASHINGTON, D.C. 20360

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $100

POSTAGE AND FEES PAID
NAVY DEPARTMENT
DOD 316

COMMANDER
NAVAL ELECTRONIC SYSTEMS COMMAND
DEFENSE STANDARDIZATION PROGRAM BRANCH
DEPARTMENT OF THE NAVY
WASHINGTON, D.C. 20360

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:38Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No 22-R255

INSTRUCTIONS The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay or will otherwise enhance use of the document DoD contractors government activities or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government Fold on lines on reverse side, staple in corner, and send to preparing activity Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements Attach any pertinent data which may be of use in improving this document If there are additional papers, attach to form and place both in an envelope addressed to preparing activity

DOCUMENT IDENTIFIER AND TITLE
MIL-P-23421/17

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1 HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
A GIVE PARAGRAPH NUMBER AND WORDING

B RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2 COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3 IS THE DOCUMENT RESTRICTIVE?
☐ YES ☐ NO (If "Yes" in what way?)

4 REMARKS

SUBMITTED BY (Printed or typed name and address - Optional)

TELEPHONE NO

DATE

DD FORM 1 JAN 73 1426

REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED

S/N 0102-014-1802

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:38Z
Check the source to verify that this is the current version before use.