NOTE: The document identifier and heading has been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.

MIL-PRF-24002(Wep)
6 January 1964
SUPERSEDING
WS 2959A
9 December 1963

PERFORMANCE SPECIFICATION

PARACHUTE PACKS; GENERAL SPECIFICATION FOR

This specification has been approved by the Bureau of Naval Weapons, Department of the Navy.

1. SCOPE

1.1 This specification covers parachute packs for use with underwater mines. These packs consist of aluminum alloy housings and covers in which ring slot type parachutes are stowed and retained in ready condition by ball-lock type pack openers.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, form a part of this specification to the extent specified herein.

STANDARDS

MILITARY

MIL-STD-129	Marking for Shipment and Storage

PUBLICATIONS

BUREAU OF NAVAL WEAPONS

OD 9687	Packing of Mine Parachutes With Deployment Sleeves

(Copies of specifications, standards, drawings, classification of defects, and publications required by contractors in connection with specific procurement functions should be obtained by the procuring activity of as directed by the contracting officer.)

FSC 1350

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:41Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 General requirements.

3.1.1 The parachute packs shall be manufactured in accordance with applicable LD's and all documents listed thereon, and as specified herein.

3.1.2 Preproduction sample. - Unless otherwise specified in the contract or order, a preproduction sample of the parachute packs shall be manufactured using the methods and procedures and at the same location as proposed for full production. This sample shall be tested as specified in Section 4 herein and is for the purpose of determining that the contractor, prior to starting production, is capable of producing units which comply with the technical requirements of the contract including the drawings and this specification.

3.1.3 Inspection requirements. - The parachute packs, prior to and after assembly, shall be inspected to determine conformance with the requirements of this specification, applicable LD's and all drawings and documents listed thereon. Inspection shall be in accordance with 4.5.

3.1.4 Conflicting requirements. - Conflicting requirements arising between this specification and any specifications, publications, or drawings listed herein shall be referred in writing to the procuring agency or appointed agent for interpretation, clarification, and resolution.

3.2 Performance requirements and product characteristics.

3.2.1 Packing of parachute into housing. - The parachute and its deployment sleeve shall be packed into the parachute housing as specified in 4.6.1.1.

3.3 Environmental requirements.

3.3.1 Vibration, low frequency. - The parachute packs shall withstand the vibration test specified in 4.6.2.1 and thereafter shall show no damage.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:41Z
Check the source to verify that this is the current version before use.

3.4 Workmanship. - The equipment, including all parts and accessories, shall be constructed and finished in a manner to assure compliance with all requirements of this specification. Particular attention shall be paid to neatness and thoroughness of assemblage, and freedom of parts from foreign materials, burrs and sharp edges. The workmanship exhibited in the preproduction samples will be evaluated to determine acceptability. The approved standards of workmanship will thereby become a minimum production requirement for all units offered for acceptance.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. - Unless otherwise specified in the contract or purchase order, the supplier is responsible for performance of all inspection requirements as specified herein or on applicable drawings. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the drawings or specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Preproduction sampling. - Unless otherwise specified for each contract or order, a representative sample of 8 parachute packs shall be manufactured using the methods and procedures proposed for the production material. This sample of parachute packs shall be tested as specified herein for the purpose of determining compliance with the requirements of the contract, specifications and drawings. The contractor shall submit a complete report on the inspections performed with the required parachute packs for the tests specified herein which are performed by a designated Government activity. Further production of the parachute packs by the contractor prior to approval of the preproduction sample by the contracting activity shall be at the contractor's risk. Unless otherwise specified, preproduction samples shall be furnished in addition to the number required by the contract.

4.3 Test conditions. - Unless otherwise specified, the parachute packs shall be subjected to acceptance tests under the following conditions:

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:41Z
Check the source to verify that this is the current version before use.

4.3.1 Temperature: Ambient room temperature, 65 to 95 degrees Fahrenheit.

4.3.2 Altitude: At test site.

4.3.3 Humidity: Ambient, to 95 percent relative maximum.

4.4 Inspection equipment and facilities. - The contractor shall furnish and maintain all necessary equipment, facilities, and personnel for performing all inspection tests. The test equipment shall be adequate in quantity, and, when definite requirements are not specified, of sufficient accuracy and quality to permit performance of the required acceptance tests.

4.5 Acceptance inspection. - Each parachute pack shall be inspected to determine conformance to this specification, applicable LD's and drawings and documents listed thereon, and classification of defects, as applicable.

4.6 Test procedures.

4.6.1 Performance tests.

4.6.1.1 Packing of parachute into housing. - The parachute with its deployment sleeve shall be packed into its housing in accordance with OD 9687. The cover attachment lines shall be secured to the sleeve attaching tape and cover in accordance with applicable drawings and OD 9687.

4.6.2 Environmental tests. - Unless otherwise specified, the environmental test of 4.6.2.1 shall be performed only on the preproduction sample and at a designated Government activity.

4.6.2.1 Vibration test. - Eight parachute packs shall be rigidly attached to the vibration table by means of a fixture which simulates actual service conditions. Simple harmonic vibration excitation shall be applied along each of three mutually perpendicular axes for equal time intervals of four (4) hours. The frequency range of 10 to 60 cps shall be covered either by cycling at a logarithmic rate between the limits or by at least 24 discrete steps which have a logarithmic distribution. The amplitude shall be maintained at 0.1 inch peak-to-peak or 2.0 g's, whichever is the lesser value. The

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:41Z
Check the source to verify that this is the current version before use.

duration of the test in each orientation shall be four hours. The total test duration shall be 12 hours. After this test, the 8 parachute packs shall be subjected to visual examination. Any deviation from the applicable drawings due to the above test, or cracked or faulty welds or other parts shall result in the unit being declared defective and the preproduction sample rejected.

4.7 Acceptance tests.

4.7.1 Preproduction. - Failure of a parachute pack to meet any of the requirements and tests of this specification shall be cause for classifying the parachute pack as defective and shall result in rejection of the sample.

4.7.2 Production. - Failure of a parachute pack to meet any of the requirements and tests of this specification and the applicable classification of defects shall be cause for regarding the pack as defective.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.

5.1.1 Level A.

5.1.1.1 Cleaning, drying and preservative application. - (Not applicable)

5.1.1.2 Unit packaging. - Each parachute pack assembly shall be individually packaged in accordance with the applicable container drawings. Applicable container drawings are referenced on the list of drawings for a specific parachute pack.

5.1.2 Level B. (Not applicable)

5.1.3 Level C.

5.1.3.1 Unit packaging. - Unit packaging, when required, shall be accomplished in a manner which will afford adequate protection from deterioration and physical damage during direct shipments from the contractor or supply source to the first receiving activity for immediate use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:41Z
Check the source to verify that this is the current version before use.

5.2 Packing.

5.2.1 Level A.

5.2.1.1 Exterior containers. - A multiple of unit packaged parachute packs, packaged as specified in 5.1.1.2, shall be packed in accordance with the applicable container drawings. Applicable container drawings are referenced on the list of drawings for a specific parachute pack.

5.2.2 Level B. (Not applicable)

5.2.3 Level C.

5.2.3.1 Exterior containers. - Parachute packs, packaged in accordance with 5.1.3.1, shall be packed in a manner which will provide protection from damage during direct shipments from the contractor or supply source to the first receiving activity for immediate use. Containers shall comply with common carrier regulations applicable to the mode of transportation.

5.3 Marking.

5.3.1 Special markings. - Unless otherwise specified in the contract or order, no special markings are required.

5.3.2 Normal markings. - In addition to any special markings required by the contract or order, all markings shall be in accordance with Military Standard MIL-STD-129.

6. NOTES

6.1 Intended use. - These parachute packs are intended for use on aircraft-launched mines.

6.2 Ordering data. - Unless otherwise specified by the contract or order, procurement documents shall specify Level A packaging and packing requirements for all shipments. Level C requirements shall be employed only when immediate use is known. Procurement documents should specify the title, number and date of this specification, applicable drawings and other documents. In addition, the location for preproduction testing shall be specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:41Z
Check the source to verify that this is the current version before use.

NOTICE. - When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:41Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET
NAVWEPS FORM 4121/8 (6-62)

FORM APPROVED
BUDGET BUREAU NO. 49-R000

INSTRUCTIONS

This sheet is to be filled out by Government or contractor personnel involved in the use of this specification in procurement of products for ultimate use by the activity shown on the reverse of this sheet.

This sheet is provided for obtaining information which will aid the activity shown in insuring that through use of this specification suitable products can be procured with a minimum amount of delay and at the least cost.

Comments and the return of this sheet will be appreciated.

Fold on dotted lines on reverse side, staple in corner, and send to the activity shown.

SPECIFICATION *(No. and abbrev. title)*

ORGANIZATION	CITY	STATE

CONTRACT NUMBER	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A DIRECT GOVERNMENT CONTRACT ☐ OR A SUBCONTRACT ☐

1. HAS ANY PART OF THIS SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
(If so, give paragraph number and wording, and recommendations for correcting the deficiencies.)

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?
☐ YES ☐ NO IF YES, IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If additional papers are attached, send this form and papers in an envelope. This form is addressed for use in window envelope when appropriate.)*

SUBMITTED BY *(Printed name and title)* DATE

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:41Z
Check the source to verify that this is the current version before use.