NOTE: The document identifier and heading has been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.

MIL-PRF-24003(Wep)
6 January 1964
SUPERSEDING
WS 2463A
9 December 1963

PERFORMANCE SPECIFICATION

PARACHUTE RELEASE MECHANISMS; GENERAL SPECIFICATION FOR

This specification has been approved by the Bureau of Naval Weapons, Department of the Navy.

1. SCOPE

1.1 This specification covers parachute release mechanisms. These mechanisms are inteded to provide an automatically released attachment for a parachute pack to an underwater mine or other weapon.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-R-11468(ORD)	Radiographic Inspection; Soundness Requirement for Arc and Gas welds in Steel

STANDARDS

MILITARY

MIL-STD-129	Marking for Shipment and Storage
MIL-STD-271 (SHIPS)	Nondestructive Testing Requirements for Metals

FSC 1350

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:42Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings, classification of defects, and publications required by contractors in connection with specific procurement functions should be obtained by the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 General requirements.

3.1.1 The parachute release mechanisms shall be manufactured in accordance with applicable lists of drawings, all documents listed thereon, and as specified herein.

3.1.2 Preproduction sample. - Unless otherwise specified in the contract or order, a preproduction sample of the parachute release mechanisms shall be manufactured using the methods and procedures and at the same location as proposed for full production. This sample shall be tested as specified in Section 4 herein and is for the purpose of determining that the contractor, prior to starting production is capable of producing units which comply with the technical requirements of the contract including the drawings and this specification.

3.1.3 Inspection requirements. - The parachute release mechanisms prior to and after assembly, shall be inspected to determine conformance with the requirements of this specification, applicable lists of drawings and all drawings and documents listed thereon. Inspection shall be in accordance with applicable classification of defects.

3.1.4 Conflicting requirements. - Conflicting requirements arising between this specification and any specifications, publications, or drawings referenced herein shall be referred in writing to the procuring agency or appointed agent for interpretation, clarification, and resolution.

3.2 Performance requirements. (Not applicable)

3.3 Preproduction requirements.

3.3.1 Radiographic examination. - The welds used on the parachute release mechanisms shall pass the soundness requirements for arc and gas welds in steel as defined in MIL-R-11468(ORD), Standard I. Test procedures shall be in accordance with 4.4.2.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:42Z
Check the source to verify that this is the current version before use.

3.4 Workmanship. - The equipment, including all parts and accessories, shall be constructed and finished in a manner to assure compliance with all requirements of this specification. Particular attention shall be paid to neatness and thoroughness of assemblage, and freedom of parts from foreign materials, burrs and sharp edges. The workmanship exhibited in the preproduction samples will be evaluated to determine acceptability. The approved standards of workmanship will thereby become a minimum production requirement for all units offered for acceptance.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. - Unless otherwise specified in the contract or purchase order, the supplier is responsible for performance of all inspection requirements as specified herein, or on the drawings. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the drawings or specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Preproduction sampling. - Unless otherwise specified for each contract or order, a representative sample of 8 parachute release mechanisms shall be manufactured using the methods and procedures proposed for the production material. This sample of parachute release mechanisms shall be tested as specified herein for the purpose of determining compliance with the requirements of the contract, specifications and drawings. The contractor shall submit a report on the inspection performed with the required parachute release mechanisms for the tests herein which are performed by a designated Government activity. Further production of the parachute release mechanism by the contractor prior to approval of the preproduction sample by the contracting activity shall be at the contractor's risk. Unless otherwise specified, preproduction samples shall be furnished in addition to the number required by the contract.

4.3 Inspection equipment and facilities. - The contractor shall furnish and maintain all necessary equipment facilities, and personnel for performing all inspection tests. The test equipment shall be adequate in quantity and, when definite requirements are not specified, of sufficient accuracy and quality to permit performance of the required inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:42Z
Check the source to verify that this is the current version before use.

4.4 Acceptance inspection. - Each parachute release mechanism shall be inspected to determine conformance to this specification, applicable LD's and drawings and documents listed thereon, and classification of defects, as applicable.

4.5 Test procedures.

4.5.1 Performance tests. (Not applicable)

4.5.2 Preproduction tests.

4.5.2.1 Radiographic examination test. - The procedure used for radiographic examination of the welds of the parachute release mechanisms shall be in accordance with paragraph 4 of MIL-STD-271 (SHIPS).

4.6 Acceptance criteria.

4.6.1 Preproduction sample. - Failure of a parachute release mechanism to meet any of the requirements and tests of this specification shall be cause for classifying the particular parachute release mechanism as defective and shall result in rejection of the preproduction sample.

4.6.2 Production. - Failure of a parachute release mechanism to meet any of the requirements and tests of this specification and the applicable classification of defects shall be cause for regarding the mechanism as defective.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.

5.1.1 Level A.

5.1.1.1 Cleaning, drying and preservative application. - (Not applicable)

5.1.1.2 Unit packaging. - Each release mechanism assembly shall be individually packaged in accordance with the applicable container drawings. Applicable container drawings are referenced on the list of drawings for a specific release mechanism.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:42Z
Check the source to verify that this is the current version before use.

5.1.2 Level B. (Not applicable)

5.1.3 Level C.

5.1.3.1 Unit packaging. - Unit packaging, when required, shall be accomplished in a manner which will afford adequate protection from deterioration and physical damage during direct shipments from the contractor or supply source to the first receiving activity for immediate use.

5.2 Packing.

5.2.1 Level A.

5.2.1.1 Exterior containers. - A multiple of unit packaged release mechanisms, packaged as specified in 5.1.1.2, shall be packed in accordance with the applicable container drawings. Applicable container drawings are referenced on thelist of drawings for a specific release mechanism.

5.2.2 Level B. (Not applicable)

5.2.3 Level C.

5.2.3.1 Exterior containers. - Release mechanisms, packaged in accordance with 5.1.3.1, shall be packed in a manner which will provide protection from damage during direct shipments from the contractor or supply source to the first receiving activity for immediate use. Containers shall comply with common carrier regulations applicable to the mode of transportation.

5.3 Marking.

5.3.1 Special markings. - Unless otherwise specified in the contract or order, no special markings are required.

5.3.2 Normal markings. - In addition to any special markings required by the contract or order, all markings shall be in accordance with Military Standard MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:42Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Ordering data. - Procurement documents should specify the title, number, and date of this specification, and exceptions to this specification, applicable drawings, and other documents. Unless otherwise specified by the contract or order, procurement documents shall specify Level A packaging and packing requirements for all shipments. Level C requirements shall be employed only when immediate use in known.

Notice. - When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:42Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET
NAVWEPS FORM 4121/8 (6-62)

FORM APPROVED
BUDGET BUREAU NO. 48-R300

INSTRUCTIONS

This sheet is to be filled out by Government or contractor personnel involved in the use of this specification in procurement of products for ultimate use by the activity shown on the reverse of this sheet.

This sheet is provided for obtaining information which will aid the activity shown in insuring that through use of this specification suitable products can be procured with a minimum amount of delay and at the least cost.

Comments and the return of this sheet will be appreciated.

Fold on dotted lines on reverse side, staple in corner, and send to the activity shown.

SPECIFICATION *(No. and abbrev. title)*

ORGANIZATION	CITY	STATE

CONTRACT NUMBER	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A DIRECT GOVERNMENT CONTRACT ☐ OR A SUBCONTRACT ☐

1. HAS ANY PART OF THIS SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
(If so, give paragraph number and wording, and recommendations for correcting the deficiencies.)

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?
☐ YES ☐ NO IF YES, IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If additional papers are attached, send this form and papers in an envelope. This form is addressed for use in window envelope when appropriate.)*

SUBMITTED BY *(Print name and title)*	DATE

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:42Z
Check the source to verify that this is the current version before use.