RR-B-623D
April 2, 1969
SUPERSEDING
Fed. Spec. RR-B-623C
November 3, 1965

FEDERAL SPECIFICATION

BREADBOX, PANTRY; DREDGERS, KITCHEN; AND CANISTERS, FOOD STORAGE

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers a pantry breadbox, a kitchen dredger, and food storage canisters.

1.2 Classification. Items covered by this specification shall be of the following types, classes, and grades as specified (see 6.2).

Type I. Breadbox, pantry - 11 inches high by 17-1/2 inches wide by 12-1/2 inches deep.

Type II. Dredger, kitchen -3-7/8 inches high by 2-7/8 inches diameter.

Grade A - Aluminum.
Grade B - Corrosion-resisting steel.

Type III. Canister, food storage.

Class A - Tea (1-1/2 lbs.) 5-3/4 inches high by 6 inches diameter.
Class B - Coffee (2 lbs.) 5-3/4 inches high by 6 inches diameter.
Class C - Flour (6 lbs.) 8 inches high by 7-5/8 inches diameter.
Class D - Sugar (10 lbs.) 8 inches high by 7-5/8 inches diameter.

2. APPLICABLE DOCUMENTS

2.1 Specifications and standards. The following specifications and standards, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

FSC 7330

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

Federal Specifications:

QQ-A-250/2	-	Aluminum Alloy 3003, Plate and Sheet.
QQ-S-766	-	Steel Plates, Sheets, and Strip - Corrosion-Resisting.
PPP-B-566	-	Boxes, Folding, Paperboard.
PPP-B-636	-	Box, Fiberboard.
PPP-B-676	-	Boxes, Set-Up, Paperboard.
PPP-F-320	-	Fiberboard, Corrugated and Solid Sheet Stock (Container Grade) and Cut Shapes.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C. 20402.)

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington D. C., Atlanta, Chicago, Kansas City Mo., Ft. Worth, Denver, San Francisco, Los Angeles, and Seattle Wash.)

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	-	Marking for Shipment and Storage.
MIL-STD-147	-	Palletized and Containerized Unit Loads, 40" x 48" Pallets, Skids, Runners, or Pallet-Type Base.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

National Sanitation Foundation (NSF) Publications:

Standard No. 2-Food Service Equipment.

Approval Listing of Food Service Equipment.

(Application for copies should be addressed to the National Sanitation Foundation, P.O. Box 1468, Ann Arbor, Michigan 48106)

National Classification Board.

National Motor Freight Classification.

(Application for copies should be addressed to the National Classification Board, 1616 P Street, N.W. Washington, D.C. 20036.)

Uniform Classification Committee.

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, 202 Union Station, Chicago, Ill. 60606.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), before production is commenced, a sample finished item shall be made available to the contracting officer or his authorized representative for approval in accordance with 4.2. The approval of the preproduction sample authorizes the commencement of production, but does not relieve the supplier of responsibility for compliance with all applicable provisions of this specification. The preproduction sample shall be manufactured in the same facilities to be used for the manufacture of the production items.

3.2 Standard product. The breadbox, dredger, and canisters delivered under this specification shall be the manufacturer's current standard product, except for any changes necessary to comply with specification requirements.

3.3 NSF standard. The breadbox, dredger, and canisters shall conform to the applicable requirements of NSF Standard No. 2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

3.3.1 NSF certification. The supplier shall submit satisfactory evidence to the contracting officer or his authorized representative that the breadbox, dredger, and canisters he proposes to furnish under this specification meet the applicable requirements of NSF Standard No. 2 as follows:

(1) A listing in the current edition of the NSF "Listing of Food Service Equipment" or display of the NSF seal on the finished breadbox, dredger, and canisters, shall be submitted prior to approval of the preproduction sample, if one is submittted, or prior to approval of the first shipment, or:

(2) A certified test report from a recognized independent testing laboratory acceptable to the medical authority functioning in advisory capacity to the preparing agency of the specification indicating that the breadbox, dredger, and canisters, have been tested and conform to NSF Standard No. 2 shall be submitted prior to the approval of the preproduction sample, if one is submitted, or prior to commencing production.

3.4 Materials. Materials not definitely specified shall be of the quality normally used by the manufacturer for breadboxes provided the completed item complies with all provisions of this specification.

3.4.1 Aluminum plate and sheet. Aluminum plate and sheet shall be Alloy 3003 conforming to QQ-A-250/2.

3.4.2 Corrosion-resisting steel plate, sheet, and strip. Corrosion-resisting steel plate, sheet, and strip shall conform to class 302 or 304 of QQ-S-766.

3.5 Construction. Type I and III items shall be fabricated of aluminum alloy specified in 3.4.1, and shall have a minimum finished thickness of 0.037 inch. The type II grade A item shall be fabricated from aluminum alloy specified in 3.4.1 having a minimum finished thickness of 0.029 inch and the type II, grade B item shall be fabricated from corrosion-resisting steel specified in 3.4.2 having a minimum finished thickness of 0.022 inch. Covers may be two gages thinner than the body thickness specified for the applicable item.

3.5.1 Type I. Pantry breadbox.

3.5.1.1 Overall dimensions. The breadbox shall be 11 inches high by 17-1/2 inches wide by 12-1/2 inches deep with a plus or minus 1/8 inch tolerance applicable to all dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

3.5.1.2 Body. The body shall be fabricated from a single piece of metal. A metal staple sized to fit the cover hasp shall be securely fastened on the front of the body. The upper edge of the body shall be reinforced by folding inside to form a hem and flattened tightly. The vertical seam joining the ends of the body shall be flat and shall be centrally located in the back of the body. Ventilation holes shall be provided at the ends.

3.5.1.3 Bottom. The bottom shall be fabricated from a single piece of metal. The bottom shall be attached to the body, and joints and seams shall be sealed and shall be smooth as the surfaces being joined.

3.5.1.4 Cover. The cover shall be fabricated from a single piece of metal. The cover shall be hinged at the back with two hinges specified in 3.5.1.5 and shall have a metal hinged hasp at the front. The cover shall be reinforced by folding the edges to form a hem and flattened tightly. The cover shall close over the rim of the body with the hinged hasp fitting over the hasp staple on the body.

3.5.1.5 Hinges. The upper and lower halves of the hinges shall be fabricated from separate pieces of metal and shall be joined by a removable pin.

3.5.1.6 Marking. Breadboxes shall be legibly marked with the word "Bread".

3.5.2 Type II, kitchen dredger.

3.5.2.1 Shape and size. Dredgers shall be 2-7/8 inches in diameter by 3-7/8 inches in height with a plus or minus 1/8 inch tolerance applicable with flat top and bottom.

3.5.2.2 Body. Body of the dredger shall be formed seamlessly. The top edge of the body shall be formed with a bayonet-type lock to attach the cover or shall be roll-threaded to provide for fit of a screw-on cover.

3.5.2.3 Cover. Cover shall be seamless formed with either a bayonet-type lock to attach cover to body or with rolled threads to fit the screw-on body, as applicable (see 3.5.2.2). The cover shall be provided with approximately one hundred and fifty 0.070 inch nominal diameter holes.

3.5.2.4 Handle. The dredger shall include a handle of the same thickness as the body. The handle shall be formed into a loop and shall be fastened in a vertical position by riveting or spot welding to the body.

3.5.3 Type III. Food storage canister.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

3.5.3.1 Shape and overall dimensions. Canisters shall be round and loose-top type. Classes A and B canisters shall be 5-3/4 inches high by 6 inches in diameter with a plus or minus 1/8 inch tolerance applicable. Classes C and D canisters shall be 8 inches high by 7-5/8 inches in diameter with a plus or minus 1/8 inch tolerance applicable.

3.5.3.2 Body and cover. The body and cover each shall be seamless drawn from a single piece of aluminum alloy, specified in 3.4.1. The top edge of the body shall be formed to fit the cover. The cover shall be a loose-top type and shall fit on the body.

3.5.3.3 Marking. Canisters shall be legibly marked as follows:

(a) Class A - marked "TEA"
(b) Class B - marked "COFFEE"
(c) Class C - marked "FLOUR"
(d) Class D - marked "SUGAR"

3.6 Finish. All items covered herein shall be finished to meet the requirements of NSF Standard No. 2, and in addition interior and exterior surfaces of items fabricated of aluminum alloy shall be given an anodized finish. The anodized finish shall be hard, white, and lustrous.

3.7 Marking for identification. Each item shall be marked in a plain and permanent manner with the name, tradename, or trademark of the manufacturer of such known character that the source of manufacture can be readily identified.

3.8 Workmanship. Finished items shall be free from rough or sharp edges, burrs, and slivers. All interior and exterior surfaces shall be free from nicks, gouges, scratches, or abrasions.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 First article inspection. When a preproduction sample is required it shall be examined for defects in table I and dimensions specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

4.3 Inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated hereinafter.

4.3.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.3.2 End item inspection. The lot shall consist of all the items of one type, grade, and class submitted for inspection at one time. The sample unit shall be one completely fabricated item.

4.3.2.1 Visual examination. Examination shall be made of the end item for the defects listed in table I. The inspection level shall be II with an acceptable quality level (AQL) of 4.0 for major defects and 10.0 for total defects, expressed in terms of defects per hundred units.

TABLE I. Classification of defects

Examine	Defect	Classification Major	Classification Minor
Finish: Aluminum (all surfaces)	Not anodized finish	X	
	Not hard white lustrous film		X
Construction and workmanship (general)	Sharp edge, burr, or sliver	X	
	Nick, gouge, scratch, or abrasion	X	
Breadbox			
Body	Body fabricated from more than one piece of metal	X	
	Metal staple missing on front of body	X	
	Upper edges of body not folded inside and flattened tightly		X
	Vertical joint not flat-seamed or not centrally located in the back of body		X
	Ventilation holes at the ends missing	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects (con.)

Examine	Defect	Classification Major	Minor
Breadbox (con.)			
Bottom	Bottom fabricated from more than one piece of metal	X	
	Bottom not attached to the body as specified		X
Cover	Not fabricated from a single piece of metal and as specified	X	
	Hinges on cover not as specified	X	
	Cover not reinforced by hem and flattened tightly	X	
	Cover does not close over hem of body	X	
	Hinged hasp does not fit over staple	X	
Hinge	Upper and lower halves of hinges not fabricated from separate pieces of metal	X	
	Hinge not connected by removable pin	X	
Dredger			
Body	Shape of top and bottom not flat		X
	Body not formed seamless		X
	Top edge of body not formed with bayonet-type lock or with rolled threads for screw type cover, as applicable	X	
Cover	Cover not formed seamless		X
	Cover not formed with a bayonet-type lock for fit with body or with rolled threads for fit with screw type body (as applicable)	X	
	Holes in cover missing	X	
Handle	Handle missing	X	
	Handle not formed into a loop		X
	Handle not fastened to body of dredger as specified, such as not in a vertical position or not riveted or spot welded		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects (con.)

Examine	Defects	Classification Major	Minor
Canister			
Body	Not round in shape or loose-top type		X
	Body not seamless formed	X	
	Top edge of body not formed to provide fit of cover		X
Bottom	Bottom fabricated from more than one piece of metal	X	
	Bottom not attached to the body by double-lock seaming		X
Cover	Cover not loose-top type as specified		X
	Cover not seamless formed	X	
	Cover does not fit on body	X	
Marking (including identification)	Missing, illegible, or misspelled		X

4.3.2.2 Dimensional examination. Examination shall be made of the items for defects in dimensions. Any dimension that is not within the specified tolerance shall be classified as a defect. The inspection level shall be S-1 with an AQL of 6.5 expressed in terms of defects per hundred units.

4.3.3 Examination of preparation for delivery. An examination shall be made to determine that packaging, packing, and marking are in compliance with section 5. Defects shall be scored as specified in table II. The sample unit shall be one shipping container fully prepared for delivery except that it need not be sealed. The lot shall be the number of containers offered for inspection at one time. The inspection level shall be S-2 and the AQL shall be 4.0 expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

TABLE II. Examination of preparation for delivery

Examine	Defect
Markings (exterior and interior)	Incorrect; illegible; omitted; of improper size, location, sequence, or method or application.
Materials	Component missing, damaged, or otherwise defective.
Contents	Content is more or less than required. Arrangement in shipping container not as specified.

4.3.3.1 Examination of shipping container. When shipping containers are required to be in accordance with PPP-B-636, examination for defects in closure, waterproofing, and strapping shall be in accordance with PPP-B-636.

4.3.4 Code and standard compliance. Proof of compliance with the requirements of NSF, as applicable to 3.3 shall be available to the Government representative.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A. The items shall be individually packaged in paperboard or fiberboard boxes conforming to PPP-B-566, PPP-B-676, or class domestic of PPP-B-636. Closure of the box shall be in accordance with appendix of the applicable box specification.

5.1.2 Level C. The items shall be packaged to afford adequate protection against damage during shipment from the supply source to the first receiving activity. The supplier may use his standard practice when it meets this requirement.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. The items packaged as specified in 5.1, shall be packed in the quantities specified in table III in snug-fitting fiberboard shipping containers conforming to V2s of PPP-B-636. Each shipping container shall be closed, waterproofed by means of tape, and reinforced with flat strapping or tape banding in accordance with the appendix of PPP-B-636.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

TABLE III. Packing

Commodity	Quantity per shipping container	Arrangement in shipping container
Breadbox, pantry	4	2 by 2 by 1
Dredger, kitchen	48	4 by 6 by 2
Canister, food storage	24	3 by 2 by 4

5.2.2 Level B. The items packaged as specified in 5.1, shall be packed in the quantities specified in table III in snug-fitting fiberboard shipping containers conforming to type CF, variety SW, or type SF, class domestic of PPP-B-636. Closure shall be in accordance with method II requirements in the appendix of the container specification.

5.2.2.1 When specified (see 6.2) the shipping container shall be V3c or V3s, fabricated and closed in accordance with PPP-B-636. The shipping container material may also be grade V4s of PPP-F-320.

5.2.3 Level C. The items packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with Uniform Freight Classification rules or National Motor Freight rules, as applicable.

5.3 Palletization. Unless otherwise specified (see 6.2) the items packed as specified shall be palletized in accordance with Load Type I of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern used shall be approved by the contracting officer.

5.4 Marking.

5.4.1 Civil agencies. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

5.4.2 Military requirements. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The breadbox, dredgers, and canisters covered by this specification are intended to be used as containers for baked foods and staples.

6.2 Ordering data. Purchasers should exercise any desired options offered herein and procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Type, class, and grade required (see 1.2).
(c) First article. When a preproduction sample is required (see 3.1).
(d) Selection of the applicable levels of packaging and packing (see 5.1 and 5.2).
(e) When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
(f) When palletization is not required (see 5.3).

6.3 Level B civil agency packaging. When level B packaging is specified for civil agency procurement, the requirements of 5.1.1 level A packaging shall apply.

MILITARY CUSTODIANS:

Army - GL
Navy - SA
Air Force - 84

Preparing activity:

Army - CL

Review activities:

Army - MD
Navy - SA, MC, MS
Air Force - 84, 85

User activity:

Navy - CG

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See Section 2 of this specification to obtain extra copies and other documents referenced herein. Price 15 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
U. S. Army Natick Laboratories
Natick, Massachusetts 01760

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS

Commanding General
U. S. Army Natick Laboratories
ATTN: AMXRES-EOS
Natick, Massachusetts 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

RR-B-623D Breadbox, Pantry; Dredgers, Kitchen; and Canisters, Food Storage

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.