RR-B-623D
AMENDMENT-1
June 22, 1973

FEDERAL SPECIFICATION

BREADBOX, PANTRY; DREDGER, KITCHEN: AND CANISTER, FOOD STORAGE

This amendment, which forms part of Federal Specification RR-B-623D, dated April 2, 1969, was approved by the Commissioner, Federal Supply Service, General Service Administration, for the use of all Federal agencies.

PAGE 1

1.2, under type II. Delete "Grade A - Aluminum. Grade B - Corrosion-resisting steel."

PAGE 2

2.1, under Federal Specifications. Delete "PPP-F-320 - Fiberboard, Corrugated and Solid Sheet Stock (Container Grade) and Cut Shapes."

PAGE 3

2.2, under "National Sanitation Foundation (NSF) Publications:". Delete "P.O. Box 1468" and substitute "NSF Building", delete "48106" and substitute "48105".

2.2 Change "National Classification Board." to "National Motor Freight Traffic Association, Inc., Agent." and change addressee from "National Classification Board" to "American Trucking Association, Inc.,".

2.2, after "Uniform Classification Committee", add ", Agent". Delete "202 Union Station," and substitute "Room 1106, 222 South Riverside Plaza,".

3.1 Delete in its entirety and substitute the following:

"3.1 First article. When specified (see 6.2), the supplier shall furnish a sample of the item to be procured under this specification for first article inspection and approval (see 4.2)."

PAGE 4

3.5 Delete in its entirety and substitute the following:

FSC 7330

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:10Z
Check the source to verify that this is the current version before use.

PAGE 4 (con.)

"3.5 Construction. The type I and III items shall be fabricated of aluminum alloy specified in 3.4.1 of not less than 18 gauge (0.040 inch nominal) thickness or of corrosion-resisting steel specified in 3.4.2 of not less than 25 gauge (0.0218 inch nominal) thickness. The type II item shall be fabricated from aluminum alloy specified in 3.4.1 of not less than 21 gauge (0.0284 inch nominal) thickness or of corrosion-resisting steel specified in 3.4.2 of not less than 25 gauge (0.0218 inch nominal) thickness. Covers may be two gauges thinner than the body thickness specified for the applicable item."

PAGE 5

3.5.1.2 Delete first and fourth sentences.

3.5.1.3 Delete in its entirety.

3.5.1.4, first sentence. Delete and substitute: "The cover shall be fabricated from a single piece of the same metal as the body."

PAGE 6

3.5.3.2, line 2. Delete period at end of first sentence and add ", or of corrosion-resisting steel specified in 3.4.2."

4.2 Delete in its entirety and substitute the following:

4.2 First article inspection. When a first article is required, the breadbox, dredger, or canister shall be examined as specified in 4.3.2.1 and 4.3.2.2. The presence of any defect shall be cause for rejection of the first article.

PAGE 7

Table I.

Under "Breadbox Body", delete the following defect: "Body fabricated from more than one piece of metal."

PAGE 8

Under "Breadbox" delete "Bottom" and all defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:10Z
Check the source to verify that this is the current version before use.

PAGE 9

Under "Canister Body", add "Not one piece" as a major defect.

Under "Canister", delete "Bottom" and all defects.

PAGE 11

5.2.2.1 Delete and substitute: "When specified (see 6.2) the shipping container shall be V3c, V3s, or V4s, fabricated and closed in accordance with PPP-B-636."

5.2.3 line 4. Delete "National Motor Freight Rules," and substitute "National Motor Freight Classification Rules."

PAGE 12

6.2 (b) Delete "and grade".

6.2 (c) Delete and substitute: "(c) When a first article is required (see 3.1, 4.2 and 6.3.1)."

After 6.3, add new paragraph 6.3.1 as follows: "6.3.1 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of ASPR 7-104.55. The first article should be a pre-production sample, initial production item or other specific item described under the definition of a First Article in the ASPR. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all procurement instruments regarding arrangements for inspection and approval of the first article."

6.4 Supersession data. The type II dredger, kitchen, grades A and B are deleted from this specification and are superseded by a dredger, kitchen, aluminum or corrosion-resisting steel at the manufacturer's option.

MILITARY INTERESTS:

Custodians:

Army - GL
Navy - SA
Air Force - 84

Preparing activity:

Army - GL

Project No. 7330-0376

Civil Agency Coordinating Activities:

GSA-FSS
VA-DMS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:10Z
Check the source to verify that this is the current version before use.