RR-B-628B
July 9, 1975
SUPERSEDING
Int. Fed. Spec. RR-B-00628A(GSA-FSS)
December 31, 1970

FEDERAL SPECIFICATION

BOX, DOCUMENT, STEEL

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE

1.1 This specification covers the requirements for a portable steel document box.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

QQ-S-698 - Steel, Sheet and Strip, Low-Carbon.
TT-C-490 - Cleaning Methods and Pretreatment of Ferrous Surfaces for Organic Coatings.
PPP-B-566 - Boxes, Shipping, Paperboard.
PPP-B-636 - Boxes, Shipping, Fiberboard.
PPP-B-676 - Boxes, Setup.

Federal Standards:

Fed. Std. No. 123 - Marking for Shipment (Civil Agencies).
Fed. Test Method Std. No. 141 - Paint, Varnish, Lacquer, and Related Materials; Methods of Inspection, Sampling and Testing.
Fed. Std. No. 187 - Identification of Pressed Bends, Forms, Seams, and Joints (Sheet Metal).
Fed. Std. No. 595 - Colors.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection and Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

*US GOVERNMENT PRINTING OFFICE 1981—703-023/2725

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

3. REQUIREMENTS

3.1 Materials. Materials used in the manufacturer of the document box shall be as specified. Material not definitely specified shall be suitable for the intended purposes, and of a quality normally used in commercial practice.

3.1.1 Sheet steel. The base, cover, and partition shall be hot or cold rolled commercial quality sheet steel conforming to QQ-S-698. The average thickness of the sheet steel shall be not less than 24 gauge (0.0239 inch, nominal).

3.1.2 Steel wire. The handle shall be made of carbon steel wire not less than 0.1719 inch in diameter.

3.2 Design and construction. The document box shall consist of a base section, cover, hinge, handle, flat plate, and lock with two keys. The outside dimensions of the document box shall be 10 inches high, 13 inches wide, and 10 inches deep (front to rear). A plus or minus tolerance of 0.5 inch will be permitted. The document box cover shall be 3 ± 1 inches high.

3.2.1 Base section and cover. The base section shall have an offset to serve as a stop for the cover. The underside of the bottom of the base section shall have four protuberances. The base section shall have a removable or permanently attached partition, located approximately in the center of the base. The partition shall extend the full width of the box, and shall be not less than 6-1/2 inches high. The box cover shall have a front and rear radius not less than 0.0625 inch. The base section and cover shall be of seamweld, or lap and spot-weld construction. Bends, forms, seams, and joints shall conform to Fed. Std. No. 187. Spot-welds shall be of sufficient numbers to assure a strong document box.

3.2.2 Hinge. The base section and cover shall be connected by a continuous piano-type hinge. The hinge shall be securely spot-welded to the base section and cover, and shall extend the full width of the document box with a minus tolerance of 1 inch. The hinge shall permit the cover to be opened beyond the vertical position, but the box shall not tilt over when empty.

3.2.3 Handle and flat plate. The handle shall have a hand hold not less than 1 inch high, and not less than 3-1/2 inches wide. The handle shall be held in place by a flat plate, and the handle and flat plate shall be of such design to permit the handle to pivot 180 degrees. The handle and flat plate shall be located in the center of the box cover. The flat plate shall be riveted to the box cover and it shall securely hold the handle in place, when tested as specified in 4.4.1.1.

3.2.4 Lock and keys. A tumbler hook(s) type lock shall be securely attached to the inside of the document box. While in an unlocked position the lock shall remain latched, when tested as specified in 4.4.1.1. The two keys shall be taped to the inside of the box.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:11Z
Check the source to verify that this is the current version before use.

3.3 Finish. All interior and exterior surfaces, except plated hardware, shall be pretreated for final finishing in accordance with TT-C-490. Enamel or lacquer, or enamel with a top coat of lacquer shall be used for the final coating of the surfaces. The material and application of the finish shall be in accordance with standard commercial practice. The minimum total dry finished film thickness shall be not less than 1.0 mil, when tested as specified in 4.4.1.2. The finish shall be smooth and uniform without runs, wrinkles, blisters, grit, or foreign materials, lumpy areas, areas of thin or no film, or separation of color. The box handle and flat plate shall have a chromium or nickel plated finish.

3.4 Color. The color of the finish shall be gray, conforming to color chip No. 26134 of Fed. Std. No. 595.

3.5 Identification marking. The document box shall be legibly and permanently marked with the name or trademark of the manufacturer.

3.6 Workmanship. The document box shall be free from defects and imperfections which may affect appearance or serviceability, or may constitute a hazard to the users. The document box shall be free from faulty construction, sharp corners or edges, burrs, dents, cracks, chips, blisters, or rust.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling.

4.2.1 Size of lot. A lot shall consist of all document boxes offered for delivery at one time.

4.2.2 Sampling for inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise specified.

4.2.3 Sampling for visual and dimensional examination. Document boxes shall be taken at random from each lot in accordance with MIL-STD-105. The sample unit shall be one document box, and each box shall be examined for defects listed in table I. The Inspection Level shall be S-2, and the Acceptable Quality Level (AQL) shall be 4.0 percent defective.

4.2.4 Sampling for preparation for delivery examination. Sampling shall be in accordance with MIL-STD-105. The lot size shall be the number shipping containers offered at one time. For examination of interior packaging, the sample unit shall be one shipping container fully prepared for delivery and selected at random prior to closing operation. Defects of closure shall be examined on shipping containers fully prepared for delivery. The Inspection Level shall be S-2, and the AQL shall be 4.0 defect per hundred units.

4.2.5 Sampling for tests. For each test, three document boxes shall be taken from each lot and tested as specified in 4.4.

4.3 Examination.

4.3.1 Visual and dimensional examination. Samples taken in accordance with 4.3.1 shall be examined for defects listed in table I. Any document box having one or more defects shall be rejected. If the number of defective units in the sample exceeds the acceptance number for the sample, the entire lot represented by the sample shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

effect on the date of the solicitation for offers or request for

TABLE I. Classification of defects

Examine	Defects
Material	Material not as specified (see 3.1, 3.1.1, and 3.1.2).
Design and construction	Design and construction not as specified (see 3.2, 3.2.1, 3.2.2, 3.2.3, and 3.2.4).
Finish	Finish not as specified (see 3.3).
Color	Color not as specified (see 3.4).
Identification marking	Identification marking not as specified (see 3.5).
Workmanship	Workmanship not in accordance with 3.6.

4.3.2 Examination of preparation for delivery requirements. Samples selected in accordance with 4.2.4 shall be examined for defects listed in table II to determine whether packaging, packing, and marking comply with the requirements in section 5 of this specification.

TABLE II. Classification of preparation for delivery defects

Examine	Defects
Marking (exterior and interior)	Omitted, incorrect, illegible, or improper size, location, sequence or method of application.
Materials	Any components missing, damaged, or not conforming to the applicable specification requirements stated herein.
Workmanship	Inadequate application of components, such as incomplete closure of container flaps, loose strapping, improper taping, inadequate stapling, bulging or distortion of containers.
Contents (exterior and interior container)	Number per container is more or less than required. Gross weight exceeds requirements.

4.4 Test.

4.4.1 End item tests. Samples selected in accordance with 4.2.5 shall be subjected to the following tests. If more than two document boxes do not meet the test requirements, the entire lot shall be rejected.

4.4.1.1 Handle and lock test. Load document box with 35 pounds of filing material and latch the lock. Hold handle and in quick succession lift up box 25 times to an approximate height of 2 feet. Then attach a rope to the handle and suspend the document box in mid-air for 15 minutes. Examine the document boxes to assure compliance with the requirements stated in 3.2.3 and 3.2.4.

4.4.1.2 Thickness test. The thickness of the coating of the document boxes shall be determined to the nearest 0.0001 inch by Test Method 6183 of Fed. Test Method Std. No. 141, for compliance with 3.3.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C, as specified (see 6.2).

5.1.1 Level A. Each document box shall be packaged in a close fitting box conforming to PPP-B-636, class domestic. Close box in accordance with the appendix to PPP-B-636.

5.1.2 Level B. Each document box shall be packaged in a box conforming to PPP-B-566, PPP-B-636, or PPP-B-676. The boxes shall be secured to prevent accidental opening.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

5.1.3 Level C. Document boxes shall be packaged in accordance with the suppliers commercial practice providing that this insures protection for the box during shipment and provides for safe delivery to its destination.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

5.2.1 Level A. Document boxes in quantities as specified (see 6.2) shall be packed in a close fitting box conforming to PPP-B-636, class weather-resistant. The box shall be closed, reinforced and waterproofed in accordance with the appendix to the box specification.

5.2.2 Level B. Four unit packages shall be packed in a close-fitting box conforming to PPP-B-636, class domestic. The box shall be closed in accordance with Method II of the appendix to the box specification.

5.2.3 Level C. Document boxes packaged as specified in 5.1.3 shall be packed in containers that will insure carrier acceptance and safe arrival at destination in compliance with the Uniform Freight Classification Rules, or the National Motor Freight Classification Rules.

5.3 Marking.

5.3.1 Civil agencies. In addition to marking required by the contract or order, the unit and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.3.2 Military agencies. In addition to markings required by the contract or order, the unit and shipping container shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The document box is primarily intended to be used as a portable receptacle for filing papers. The document box does not provide protection against unauthorized entry or theft.

6.2 Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Select applicable level of packaging and packing required (see 5.1 and 5.2).
(c) Quantity of boxes per level A shipping container (see 5.2.1).
(d) Specify whether civil or military marking is required (see 5.3).

DOD INTEREST

Custodians:

Army - GL (MCA)
Navy - SA
Air Force - 84

User Interest:

Navy - MC

Preparing Activity:

GSA - FSS

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See Section 2 of this specification to obtain extra copies and other documents referenced herein. Price 30 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.