INCH-POUND

RR-C-550D
8 April 1991
SUPERSEDING
RR-C-550C
28 January 1990

FEDERAL SPECIFICATION

CONTAINERS, FLUID, FOR PAINT SPRAY EQUIPMENT

This specification is approved by the Assistant Administrator, Office of Federal Supply and Services, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers siphon-feed cups and pressure-feed containers used with paint spray equipment.

1.2 Classification.

1.2.1 Types and sizes. Fluid containers covered by this specification shall be of the following types and sizes, as specified (see 6.2).

Type I - Siphon cup, one quart capacity.

Type II - Pressure tank.

Size 1 - Two gallon minimum capacity.
Size 2 - Five gallon minimum capacity.
Size 3 - Thirty gallon minimum capacity.

2. APPLICABLE DOCUMENTS

2.1 Government publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bid or solicitation for offers, shall apply.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research, Development and Engineering Center, ATTN: SMCAR-EST-S, Rock Island, IL 61299-7300 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 4940

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:10Z
Check the source to verify that this is the current version before use.

Federal Specification

QQ-B-637	-	Brass, Naval: Rod Wire, Shapes, Forgings, and Flat Products With Finished Edges (Bar, Flat Wire, and Strip)
QQ-C-390	-	Copper Alloy Castings (Including Cast Bar)
QQ-Z-363	-	Zinc-Base Alloys; Die Castings
PPP-B-601	-	Box, Wood, Cleated-Plywood
PPP-B-621	-	Box, Wood, Nailer and Lock-Corner
PPP-B-636	-	Boxes, Shipping, Fiberboard
PPP-C-1797	-	Cushioning Material, Resilient, Low Density, Unicellular, Polypropylene Foam
PPP-T-60	-	Tape, Packaging, Waterproof

Federal Standards

FED-STD-H28	-	Screw-Thread Standards for Federal Services
FED-STD-376	-	Preferred Metric Units for General Use by the Federal Government

(Activities outside the Federal Government may obtain copies of Federal specifications, standards, and commercial item descriptions as outlined under General Information in the Index of Federal Specifications, Standards and Commercial Item Descriptions. The Index, which includes cumulative bimonthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

(Single copies of this specification, and other Federal specifications and commercial item descriptions required by activities outside the Federal Government for bidding purposes, are available without charge from General Services Administration Business Service Centers in Boston, MA; New York, NY; Philadelphia, PA; Washington, DC; Atlanta, GA; Chicago, IL; Kansas City, MO; Fort Worth, TX; Houston, TX; Denver, CO; San Francisco, CA; Los Angeles, CA; and Seattle, WA.)

(Federal Government activities may obtain copies of Federal standardization documents and the Index of Federal Specifications, Standards, and Commercial Item Descriptions from established distribution points in their agencies.)

Military Specifications

MIL-P-116	-	Preservation, Methods of
MIL-B-121	-	Barrier Material, Greaseproofed, Waterproofed, Flexible
MIL-C-5501	-	Caps and Plugs, Protective, Dust and Moisture Seal, General Specification for
MIL-S-12928	-	Separators, Oil and Water, Compressed Air

Military Standards

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:10Z
Check the source to verify that this is the current version before use.

MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-130 - Identification of US Military Property
MIL-STD-889 - Dissimilar Metals
MIL-STD-1190 - Minimum Guidelines for Level C Preservation, Packing and Marking

(Copies of military specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Federal Regulation:

Occupational Health and Safety Administration (OSHA) 29 CFR 1910. 107 General Industrial Safety and Health Standards

(The Code of Federal Regulations (CFR) and the Federal Register (FR) are for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402. When indicated, reprints of certain regulations may be obtained from the Federal agency responsible for issuance thereof.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

American Society of Mechanical Engineers (ASME)

ASME - Boiler and Pressure Vessel Codes

(Application for copies should be addressed to the American Society of Mechanical Engineers, 345 East 47th Street, New York, NY 10017.)

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

3. REQUIREMENTS

3.1 First article. When specified (see 4.3 and 6.2), the contractor shall furnish one or more containers for first article inspection. The first article may be either a preproduction model or an initial production item which conforms to the requirements of this specification. In either case, the approved first article and the production items shall be identical and in

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:10Z
Check the source to verify that this is the current version before use.

accordance with the terms of the contract. Approval of the first article shall not relieve the contractor of the responsibility to furnish equipment in accordance with the requirements of this specification.

3.2 Design. The containers shall be new and of the manufacturer's latest design that shall meet the requirements specified herein. The containers shall be designed for convenience and ease of operation. The design shall be such that parts subject to wear, breakage, or distortion shall be accessible for adjustment, replacement, or repair without modification, distortion, or damage to the containers or any part or component of the containers.

3.2.1 Measurement system. The US Customary System of Units (US) or the International System of Units (SI) may be used in the design and construction of the containers. In this specification, all measurements, dimensions, sizes, and capacities are given in the US system. These measurements may be converted to the SI system by using the conversion factors and methods specified in FED-STD-376.

3.2.2 Threads. Threads shall conform to FED-STD-H28 and the applicable Detailed Standard section referenced therein.

3.2.3 Interchangeability. All parts shall be manufactured to definite standards, clearances, and tolerances in order that any such parts of a particular type or model may be replaced, interchanged, and adjusted without modification of the replacement parts or any other parts of the unit. When practical, all parts shall be permanently and legibly marked in accordance with MIL-STD-130.

3.2.4 Safety devices. Safety devices shall be provided for parts that present safety hazards to personnel. Safety devices shall not interfere with the operation of the containers or with the operator's performance.

3.2.4.1 Occupational safety standards. The product shall comply with OSHA standards set forth in 29 CFR 1910.107 that are applicable to paint containers.

3.3 Material. Material shall be as specified herein and as shown on the applicable drawings. Materials not specified shall be selected by the contractor and shall be subject to all provisions specified herein. Materials shall be free from defects which would adversely affect the performance, reliability, durability, longevity, or maintainability of the individual components or overall assembly. When dissimilar metals are used in contact with each other, suitable protection against galvanic corrosion shall be applied in accordance with MIL-STD-889.

3.3.1 Reclaimed materials. The manufacturer may use reclaimed materials for fabricating new parts. Reclaimed materials shall be reprocessed, remanufactured, or recycled in a manner that restores them to the same chemical

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:10Z
Check the source to verify that this is the current version before use.

composition and physical properties as the raw materials originally selected for use. Use of reclaimed parts as is or rebuilt from scrap or other used equipment shall not be permitted.

3.4 Construction. The containers shall be furnished complete so they can be used for the operations specified herein.

3.4.1 Castings and forgings. Castings shall be free from visible blowholes, porosity, hard spots, shrinkage defects, cracks, or other defects. Forgings shall be free from visible scale, inclusions, cold shuts, mismatching, sharp edges, or other defects. Castings and forgings shall be free from any properties adversely affecting their strength, durability, or suitability. Reclaiming or repair of major castings and forgings shall be permitted if the repair is not on a critical surface.

3.4.2 Welding, brazing, and soldering. Welding, Brazing, and soldering shall be of a quality which shall sustain all requirements of the welded, brazed or soldered parts. These operations shall not be employed as repair measures for defective parts.

3.4.3 Fastening devices. Screws, pins, bolts, and similar parts shall be installed with means for adjustment and for preventing loss of tightness. The methods for adjustment and for preventing loss of tightness shall be in accordance with accepted engineering standards and practices. All such parts when subject to renewal or adjustment shall not be swaged, peened, staked, or otherwise deformed.

3.5 Performance. The containers shall be capable of being used with sprayable materials such as enamels, lacquers, primers, shellac, varnishes, stains, oil-based paints, surfacers, and related fluids within a similar viscosity range, including the solvents contained in those materials. The solvents shall include ketones, aromatics, and aliphatics.

3.6 Type I - siphon cup. Type I, siphon cup, shall consist of the major components covered in 3.6.1 through 3.6.4.

3.6.1 Cup. The siphon cup shall be equipped with a cover and cover attachments for use in spraying the materials specified in 3.5. The cup shall have a capacity of not less than one quart and shall be cylindrical in shape. The cup shall be of seamless metal construction, having a minimum thickness of 0.040 inch, and shall be resistant to the sprayable materials specified in 3.5. The outside diameter shall be less than 4 5/8 inches and the throat diameter shall be at least 3 1/4 inches. The bottom of the cup shall be reinforced to provide support, and prevent undue wear and injury to the cup bottom. The top of the cup shall be smooth and wide enough to seal without cutting the gasket.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:10Z
Check the source to verify that this is the current version before use.

3.6.2 Cover. Unless otherwise specified (see 6.2), a matching cover of metal which is resistant to the sprayable materials specified in 3.5 shall be provided. The cover shall contain a leather or impregnated leather gasket which shall form a liquid-tight seal between the cup and cover when using the materials specified in 3.5 (see 3.6.4). The cover shall be attached to the cup by means of external lugs and a steel yoke, or other suitable clamping arrangements. The clamping arrangement shall not distort or loosen in normal use, shall hold an air-tight and liquid-tight seal between cover and cup, and shall permit separation, by hand, of the cover from the cup after the unit has been left standing while containing paint. The cover shall have a vent hole not less than 1/16 inch in diameter for the admission of air into the cup. Near the vent hole the words "KEEP OPEN" or "KEEP CLEAN" shall be permanently marked.

3.6.3 Cover attachments. The cover shall have a swivel nut with 3/8 inch National Pipe Straight Mechanical (NPSM) threads and a nipple with a 60 degree included external bevel taper seat connection for attaching a cup to the material connection of the spray gun. The cover shall be compatible with the material of the shell. The material tube shall be of adequate size to handle the sprayable materials specified in 3.5. The tube shall extend as near to the bottom of the cup as possible, without impairing the flow of material, so that proper feed shall be maintained until less than 3 1/2 fluid ounces remain in the cup.

3.6.4 Spare gaskets. A sealed packet of five of the leather or impregnated leather gaskets specified in 3.6.2 shall be supplied with each Type I (siphon) cup. The packet shall include instructions for the care, cleaning, use, and maintenance of the siphon cup and cup gaskets.

3.7 Type II - pressure tanks. Type II, pressure tanks, shall consist of the major components covered in 3.7.1 through 3.7.9.

3.7.1 Tanks. The Type II pressure tanks shall be of the sizes and minimum capacities specified in 1.2.1. The pressure tanks shall be suitable for storing and feeding, under air pressure, the sprayable materials specified in 3.5. The tanks shall comply with the requirements of the ASME Boiler and Pressure Vessel Codes (See 2.2), with a maximum working pressure of 110 pounds per square inch gage (psig). The label required by the ASME code shall be permanently attached to the tanks.

3.7.2 Shell. The shell shall be a seamless one piece, or a fabricated tube constructed of metal, or coated metal, that is resistant to corrosion and the action of the sprayable materials specified in 3.5. The tank shall be cylindrical in shape with a full open top and with a concave bottom as viewed from the inside. The bottom shall be reinforced to provide a solid support and protection against damage. Two handles or cover clamps shall be located on the side diametrically opposite each other, near the top of the tank. The handles or clamps shall have sufficient strength for lifting the tank when filled with

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:10Z
Check the source to verify that this is the current version before use.

paint. clamps and permanent brackets, or other suitable means, shall be provided for fastening the cover at the top of the shell so that the cover may be easily removed and yet maintain an air-tight seal, when secured to the tank, under 90 psig regulated pressure.

3.7.3 Cover. Unless otherwise specified (see 6.2), the cover shall be made of aluminum or pressed steel. The steel shall be cadmium or zinc plated to a minimum thickness of 0.0003 inch. The cover assembly shall include all necessary equipment for the operation and control of the tank, and the control and supply of the atomizing air to the gun. Centering pads of suitable reinforcement shall be provided for the cover holding devices.

3.7.4 Agitator. Unless otherwise specified (see 6.2), the agitator shall be air motor driven and shall mix the sprayable materials specified in 3.5 to prevent settlement of any pigments. The air motor drive shall be equipped with a speed adjustment and shut-off valve. The air consumption shall not exceed 8 cubic feet per minute (cfm) under normal operating conditions. The agitator shall be part of the cover assembly with the air motor being detachable.

3.7.5 Controls. The controls shall be part of the cover and shall consist of a paint strainer; brass shut-off valves for air inlet, air outlet, and fluid outlet; one regulator with outlet gage reading 0 to 100 psig; an air pressure release valve; and a safety valve set for 110 + 0 - 2 psig.

3.7.6 Connections. Material hose connections of the tank shall have 3/8 inch male NPSM threads, with a 60 degree included angle internal bevel taper seat. Air inlet and outlet connections shall have 1/4 inch standard straight pipe threads, with a 60 degree included angle internal bevel taper seat.

3.7.7 Insert container. When specified (see 6.2), a removable type container of suitable size for insertion into the pressure container shall be provided. The insert container shall be made of galvanized, or cadmium plated steel, or of steel which is corrosion resistant and resistant to the sprayable materials specified in 3.5. The insert container shall be constructed so that it can be removed from the pressure container by use of a bail, handles, or other suitable means.

3.7.8 Regulator. The regulator shall be of the conventional hand screw type for adjusting air pressure, and shall be capable of passing not less than 15 cfm of air at 80 to 100 psig supply line pressure, with a maximum of an eight pound pressure drop. The outlet pressure shall be adjustable from 5 to 90 psig and shall be held at the set pressure until changed by the operator. The regulator shall be of durable construction capable of withstanding 250 psig pressure. A diaphragm with an adequate diameter and a valve mechanism enclosed within the body shall be operated by a handle for ease of adjustment.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:10Z
Check the source to verify that this is the current version before use.

3.7.8.1 Regulator body material. Material for the regulator body shall be brass conforming to QQ-C-390 or QQ-B-637, or a zinc die casting conforming to Composition AG40A of QQ-Z-363. The body material shall have a minimum tensile strength of 30,000 pounds per square inch (psi).

3.7.9 Pressure gage. The pressure gage shall be of the Bourdon tube geared type with a 1/4 inch male National Pipe thread stem extending from the bottom. The case shall be drawn steel with a black or gray enameled finish. The bezel ring shall match the case and shall be attached to the case. The dial shall be not less than two inches in diameter, and shall have black lines and figures on a light background. The gage shall be calibrated to an accuracy of three percent of the maximum pressure capacity on the upper third and lower third of the scale, and to two percent of the maximum capacity in the middle portion of the scale. The gage shall be graduated to a maximum range of 100 psig, with scale divisions of two pound increments and figure intervals no greater than 20 pounds.

3.8 Oil and water separator. When specified (see 6.2), an inlet air, oil, and water separator conforming to class I of MIL-S-12928 shall be provided with each unit.

3.9 Product identification. The containers shall be marked for product identification in accordance with MIL-STD-130 and, unless otherwise specified (see 6.2), shall include the National Stock Number.

3.10 Workmanship. Standards of workmanship shall assure that the containers shall have the stability, strength, durability, safety, and efficient operating characteristics found in the best commercial units and as specified in Section 3.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspections set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:10Z
Check the source to verify that this is the current version before use.

requirements of the contract. Sampling in quality conformance does not authorize submission of known defective materiel, either indicated or actual nor does it commit the Government to acceptance of defective materiel.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

(a) First article inspection (see 4.3 and 6.2).
(b) Quality conformance inspection (see 4.4).

4.3 First article inspection. First article inspection shall be applied to the preproduction model or initial production item (see 3.1). unless otherwise specified (see 6.2), first article inspection shall consist of the examination in 4.5 and all tests under 4.6. Failure of the first article to pass the examination or any of the tests shall be cause for rejection.

4.4 Quality conformance inspection. Quality conformance inspection shall be applied to production items offered for acceptance under the contract. Quality conformance inspection shall consist of (a) through (g) as follows. Failure of any item to pass the examination or any of the tests shall be cause for rejection.

(a) Product examination (see 4.5)
(b) Operational test (see 4.6.1.1 or 4.6.2.1)
(c) Leakage test (4.6.1.2 or 4.6.2.2)
(d) Safety valves test (4.6.3)
(e) Regulator test (4.6.4)
(f) Gage test (4.6.5)
(g) Packaging inspection (see 4.7)

4.4.1 Sampling. Sampling for quality conformance inspection shall be performed as listed with all samples selected randomly.

Inspection of Test	Lot or Batch Size	Sample Size
Product examination (See 4.5)	—	100 percent
Operational test (see 4.6.1.1 or 4.6.2.1)	280	3
Leakage test (see 4.6.1.2 or 4.6.2.2)	280	13
Safety valve test (see 4.6.3)	—	100 percent
Regulator test (see 4.6.4)	280	13
Gage test (4.6.5)	280	13
Packaging inspection (see 4.7)	280	3

The lots shall not exceed the maximum sizes indicated above. If lot size is less than or equal to sample size, 100 percent inspection is required. Each lot shall be accepted with no defects and rejected if one or more defects are found.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:10Z
Check the source to verify that this is the currentversion before use.

4.5 Product examination. Visually, dimensionally, and manually examine each container to determine conformance with the requirements of 3.2 through 3.4.3, 3.6.4, and 3.8 through 3.10. Visual examination shall include verification of completeness of manufacture and assembly, conformance to specified standards, adequacy of markings, proper cleaning and freedom from the identified defects. Dimensional examination includes measuring dimensions as specified. Manual examination shall include the operation of movable parts by hand to assure proper functioning. The examination provisions may be applied at the earliest practical point in manufacturing at which it is feasible to inspect for acceptance without risk of change in the characteristic by subsequent operation. Failure of the contractor to provide objective evidence that the item and its components have passed the examinations prescribed for them by the contractor's inspection system shall be cause for rejection. In addition, failure of the contractor to provide objective evidence that all parts are manufactured to definite standards, clearances, and tolerances so that no replacement part will degrade the form, fit, or function of the end item (see 3.2.3), shall be cause for rejection.

4.5.1 Evidence of compliance with OSHA standards. Evidence of compliance with applicable safety and health requirements shall be reviewed (see 3.2.4.1 and 6.4).

4.6 Tests.

4.6.1 Type I - siphon cup.

4.6.1.1 Cup operation. The siphon cup, containing eight fluid ounces of oil-based paint, shall be attached to the fluid inlet of a suction feed spray gun. The gun shall be operated in a horizontal position until a steady spray pattern is not maintained. The paint remaining in the cup shall be measured. In the event that the amount remaining is in excess of 3-1/2 fluid ounces, the cup shall be rejected (see 3.6.3).

4.6.1.2 Leakage. The cup, completely filled with water and with the air vent hole plugged, shall be attached to a suitable device which shall fit the swivel nut, seal off the nipple, and support the cup. The device shall then be rotated in a manner to turn the cup upside down three times. The appearance of water at the seal between the cup and lid or at the swivel nut shall be cause for rejection.

4.6.2 Type II - pressure tanks.

4.6.2.1 Tank operation. The tank shall be filled with water to the applicable capacity. With the lid assembly clamped in position, and with all outlet valves closed, connect the tank to a 125 psig air supply line. With the regulated pressure in the tank set at 90 psig, the agitator in the tank shall

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:10Z
Check the source to verify that this is the current version before use.

be run at not less than 40 revolutions per minute. An air consumption of more than eight cfm, failure of the regulator to hold the 90 psig without creep, or failure of any part shall be cause for rejection.

4.6.2.2 Leakage. The tank shall be completely filled with water and the lid assembly clamped in position. With all outlet valves closed, the tank shall be connected to a 125 psig air supply line. With regulated pressure in the tank set at 90 psig, rotate the tank in a manner to turn it upside down three times. The tank shall then be observed for five minutes for leakage. Any leakage shall be cause for rejection.

4.6.3 Safety valve test. The air outlet shall be blocked and the outlet gage replaced with a test gage having an accuracy within one percent of measured valve. Gradually increase air pressure above 100 psig until the safety valve opens. Failure of the valve to open in a range of 108 to 110 psig, or leakage of the air pressure release valve, shall be cause for rejection (see 3.7.5).

4.6.4 Regulator test. A flow meter having a capacity of at least 20 cfm and an accuracy of two percent of measured valve shall be used. Test pressure gages having an accuracy within one percent of measured valve shall be installed on each side of the regulator. A valve to control outlet pressure shall also be installed. Tests shall be conducted as follows:

(a) Capacity test. At 80 +5 -0 psig supply pressure, adjust the outlet valve so that maximum differential pressure across the regulator is eight psi, or until flow through the regulator exceeds 15 cfm. If the flow is low, repeat the test at 100 +0 -5 psi. Failure of the regulator to pass a minimum of 15 cfm at a maximum pressure drop of eight psi, shall be cause for rejection (see 3.7.8).

(b) Regulation test. With supply pressure of 80 to 100 psig, set the output pressure at 5 psig. Flow air for five minutes. Repeat the test at 45 psig and 90 psig. Failure of the output pressure to remain at set pressure shall be cause for rejection (see 3.7.8).

4.6.5 Gage test. Using a gage tester or a calibrated test gage for comparison, pressures of 10, 30, 35, 65, 70, and 100 psig shall be applied. Gage readings shall be 9.7 to 10.3, 29.1 to 30.9, 34.3 to 35.7, 64.6 to 66.4, 67.9 to 72.1, and 97 to 103 psig. Failure to meet the pressure range at any of the six test pressures shall be cause for rejection (see 3.7.9).

4.7 Packaging inspection. Packaging inspection shall be conducted before and after packaging to determine compliance with the requirements of Section 5.

5. PACKAGING

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:10Z
Check the source to verify that this is the current version before use.

5.1 Disassembly. When practical, items shall be disassembled to afford protection of components, attachments, and accessories against damage and pilferage and to reduce cubage. Disassembled parts shall be preserved, anchored, braced, blocked, and cushioned to prevent damage. Disassembled parts shall be clearly and legibly marked as to identity and location of the assembled item. All fasteners removed during disassembly shall be secured in one of the mating parts. A part shall not be removed from an assembly unless it can be reassembled readily in the field without special skills or tools.

5.2 Preservation and packaging. Preservation and packaging shall be Level A or Level C, as specified (see 6.2).

5.2.1 Level A.

5.2.1.1 Cleaning and drying. The containers shall be cleaned in accordance with process C-1 and dried in accordance with any applicable procedures of MIL-P-116.

5.2.1.2 Preservation application. Unless otherwise specified herein, all bare, exterior, ferrous metal surfaces shall be coated with type P-2 preservative, in accordance with MIL-P-116, immediately following cleaning and drying.

5.2.1.2.1 Air motor. Interior surfaces of air motors and air lines shall be coated a preservative oil conforming to P-10, Type I, grade 30 by injecting oil into the air stream while operating the machine until the oil appears at the exhaust ports. Air inlets and outlets shall be sealed with plastic caps, plugs or tape conforming to MIL-C-5501 or PPP-T-60, type IV respectively. Air cylinders shall not be disassembled from the machine unless parts are vulnerable to damage during shipment and storage.

5.2.1.3 Type I - siphon cup. Siphon cups shall be packaged method III of MIL-P-116. Projections and sharp edges shall be cushioned with material conforming to PPP-C-1797. Secure cushioning material in place with tape conforming to PPP-T-60, type optional. In the event the cap and attachment are removed to conserve cubage, each item shall be cushioned as specified herein. Each siphon cup, cover, and attachment shall be placed in a fiberboard box conforming to PPP-B-636, grade W6C. Closure shall be in accordance with the appendix to the box specification.

5.2.1.4 Type II - pressure tanks. Pressure tanks shall be individually packaged method I of MIL-P-116. Preserved surfaces shall be covered or wrapped with barrier material conforming to MIL-B-121, type 1, grade A, class optional. Projections and protruding parts that are subject to damage, or which are capable of damaging the barrier material, shall be cushioned with material conforming to PPP-C-1797. Secure cushioning material in place with tape conforming to PPP-T-60, type optional. All openings for hose connections shall be sealed with tape conforming to PPP-T-60, type IV, class 1, or cap or

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:10Z
Check the source to verify that this is the current version before use.

plugs of MIL-C-5501. Tanks shall be individually packaged in fiberboard boxes conforming to PPP-B-636, class weather-resistant, grade optional. Closure shall be in accordance with the appendix to the box specification.

5.2.1.5 Technical data. Publications issued with the containers lifts shall be preserved in accordance with method IC-1 of MIL-P-116.

5.2.2 Level C. Level C preservation shall be as specified in MIL-STD-1190.

5.3 Packing. Packing shall be Level A or Level C, as specified (see 6.2).

5.3.1 Level A.

5.3.1.1 Type I - siphon cup. Siphon cups, preserved as specified herein, shall be packed in quantities not to exceed a maximum weight of approximately 200 pounds. Shipping containers shall conform to PPP-B-601, overseas type, or PPP-B-621, class 2.

5.3.1.2 Type II - pressure tanks. Pressure tanks, preserved as specified herein, shall be packed according to size (see 1.2). Size 1 tanks shall be packed four each, Size 2 two each and Size 3 one each in shipping containers conforming to PPP-B-601, overseas type, or PPP-B-621, class 2.

5.3.2 Level C. Level C packing shall be as specified in MIL-STD-1190.

5.4 Marking. Marking shall be as specified in MIL-STD-129.

6. NOTES

6.1 Intended use. The containers covered by this specification are intended to be used with paint spray equipment. Type I, the siphon cup, is attached directly to a spray gun. Type II, a pressure feed tank, is used to hold fluid under pressure until released through a remote-operated spray gun. Both types are used for spraying materials such as enamel, lacquer, varnish, and fluids of similar viscosity range (see 3.5).

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Type and size required (see 1.2.1).
(c) First article, when required (see 3.1).
(d) Covers if different (see 3.6.2 and 3.7.3).
(e) Agitator if different (see 3.7.4).
(f) Insert container when required (see 3.7.7).
(g) Oil and water separator when required (see 3.8).

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:10Z
Check the source to verify that this is the current version before use.

(h) Product identification if different (see 3.9).
(i) First article inspection if different (see 4.3).
(j) Level of preservation, packing, and marking if different (see 5.2, 5.3, and 5.4).

6.3 Contract data requirements. Required technical data such as operator's manuals, parts lists, and other instructions for operation and maintenance, as identified on a numbered DD Form 1664, should be specified on a DD Form 1423 incorporated in the contract.

6.4 OSHA standards. Products which meet all requirements of this specification comply with the OSHA standards published prior to the date of this specification and identified in Section 3 (see 3.2.4.1).

6.5 Subject term key word listing.

Siphon-feed
Pressure-feed
Agitator
Regulator

MILITARY INTERESTS:

Custodians

Army - AL
Navy - YD
Air Force - 99

Review Activities

Navy - MC
Air Force - 82

CIVIL AGENCY COORDINATING ACTIVITY:

GSA-FSS

PREPARING ACTIVITY:

Army - AL

DoD Project 4940-0621

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:10Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS. The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

RR-C-550, Rev D, Containers, Fluid, for Paint Spray Equipment

NAME OF ORGANIZATION AND ADDRESS	CONTRACT NUMBER
	MATERIAL PROCURED UNDER A ☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO (If "Yes", in what way?)

4. REMARKS

SUBMITTED BY (Printed or typed name and address - Optional)	TELEPHONE NO
	DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:10Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

U.S. MAIL

OFFICIAL BUSINESS

Commander
US Army Armament Research Development
and Engineering Center
ATTN: SMCAR-EST-S
Rock Island, IL 61299-7300

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:10Z
Check the source to verify that this is the current version before use.