RR-D-500C
March 16, 1973
SUPERSEDING
Int. Fed. Spec. RR-D-00500B(GSA-FSS)
March 26, 1971 and
Fed. Spec. RR-D-500A
August 15, 1962

FEDERAL SPECIFICATION

DISPENSER, PAPER NAPKIN

This specification was approved by the Commissioner, Federal Supply Services, General Services Administration, for use of all Federal agencies.

1. SCOPE

1.1 This specification covers one type and size of paper napkin dispenser (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

L-P-378 - Plastic Sheet and Strip, Thin Gauge, Polyolefin.
QQ-Z-325 - Zinc Coating, Electrodeposited Requirements for.
PPP-B-566 - Boxes, Folding, Paperboard.
PPP-B-636 - Box, Fiberboard.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedures and Table for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.



Source: https://assist.dla.mil -- Downloaded: 202640-26T12:10Z
Check the source to verify that this is the current version before use.

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Association, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Preproduction sample. When specified (see 6.2), before production is commenced, a sample of the napkin dispenser shall be submitted or made available to the contracting officer or his authorized representative for approval in accordance with 4.2. The approval of the preproduction sample authorizes the commencement of production, but does not relieve the supplier of responsibility for compliance with all applicable provisions of this specification. The preproduction sample shall be manufactured in the same facilities to be used for the manufacture of the production items.

3.2 Standard product. The paper napkin dispenser provided under this specification shall be the manufacturer's standard commercial product, except for any design modifications and additional requirements specified herein.

3.3 Materials. The material specified shall conform to the requirements specified hereinafter. Materials not definitely specified shall be of the quality normally used for the purpose in commercial practice.

3.4 Design and construction. The dispenser shall consist of a body and base joined together by spotwelding; two pressure plates which shall be proportionate in size to be retained in the body of the dispenser when empty; springs and four rubber feet securely held to the base of the dispenser by rivets, or by using an inner holddown plate. The dispenser shall have an overall height of 7 inches by an overall width of 3-3/4 inches. A tolerance of plus or minus 1/8 inch shall apply on each dimension. The dispenser shall be capable of holding 125 embossed paper napkins, 13 inches by 13-1/2 inches when folded to a nominal size of 3-1/2 by 6-3/4 inches. The dispenser shall be designed so that napkins can be withdrawn from either the front or rear opening of the dispenser without tearing or any injury to the fingers (see 4.4.1).

3.4.1 Body and base. The body and base of the dispenser shall be fabricated from commerical corrosion-resisting steel sheet of the 400 series, with a nominal thickness of not less than 24 gauge (0.0239 inch). The edges of the body shall be finished smooth and those edges in contact with the napkins shall be flared slightly outward to facilitate removal of each napkin. The body of the dispenser shall be plain or with a diamond shape or rectangular embossing.

3.4.2 Feet. The feet of the dispenser shall be made of black or gray non-marking rubber 1/2 inch in diameter by 1/4 inch high. When riveted to the base of the dispenser, a metal insert washer shall be provided under the rivet heads.

3.4.3 Pressure plates. The pressure plates shall be fabricated of commercial cold-rolled steel sheet with a nominal thickness of not less than 24 gauge (0.0239 inch). The pressure plates shall be assembled with springs made of strip steel or coil steel. When the spring is made of strip steel, it shall be securely attached to both the pressure plates and to the base of the dispenser. When the spring is made of steel wire, it shall be securely attached to the pressure plates only.

3.4.3.1 Springs. The springs shall be made either of spring-steel wire in the quality normally used for the purpose in commercial practice with a nominal diameter of not less than 16 gauge (0.0625 inch), or of commercial high-carbon steel strip of spring temper with a nominal thickness of not less than 30 gauge (0.012 inch) and width of 7/8 inch plus or minus 1/8 inch.



Source: https://assist.dla.mil -- Downloaded: 202610-26T12:10Z
Check the source to verify that this is the current version before use.

3.5 Finish.

3.5.1 Body and base. The outside surfaces of both the body and base, except the bottom of the base, shall have a commerical No. 7 high luster finish.

3.5.2 Pressure plates and springs. The pressure plates and springs shall be zinc coated in accordance with type I of QQ-Z-325. The minimum thickness of zinc coating shall be:

| | |
|---|---|
| Pressure Plate | 0.000085 inch |
| Spring | 0.00005 inch |

3.6 Marking for identfication. The bottom of each dispenser shall be marked in a plain and permanent manner with the manufacturer's name, trade name or trademark of such known character that the source of manufacture may be readily identified.

3.7 Workmanship. The finished dispenser shall be clean, well made, and free from any defects which may affect appearance or serviceability. There shall be no sharp edges on any part of the dispensers.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Preproduction sample inspection. Testing of the preproduction sample shall be made on a completely fabricated item for all provisions of this specification applicable to end product testing.

4.3 Sampling for inspection and acceptance. Sampling for inspection and acceptance shall be performed in accordance with the provisions set forth in MIL-STD-105, except where otherwise indicated.

4.3.1 Inspection of components and materials. In accordance with 4.1 above, the supplier is responsible for insuring that components and materials used are manufactured, tested and inspected in accordance with the requirements of referenced subsidiary specifications to the extent specified, or, if none, in accordance with this specification.

4.3.2 End item inspection.

4.3.2.1 Visual examination. Examination of the dispenser shall be in accordance with the classification of defects listed in table I and acceptable quality levels (AQL's) set forth in 4.3.2.3. The lot size shall be expressed in units of dispensers for the purpose of determining the sample size in accordance with MIL-STD-105. The sample unit for this examination shall be one completely fabricated dispenser.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:10Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects

| Examine | Defect | Classification Major | Minor |
|---|---|---|---|
| Finish | Outside of surface of housing not commercial No, 7 high luster finish or has scratches or abrasions..... | | X |
| | Discolored or stained..... | | X |
| | Pressure plate and spring not zinc coated or area of no coating..... | | X |
| Construction, assembly and workmanship | Foot missing..... | X | |
| | Feet not black or gray rubber..... | | X |
| | Feet not secured to base as specified... | | X |
| | Feet not made of nonmarking rubber (slide dispenser across test surface)..... | | X |
| | Body not joined to base by spot-welding. | | X |
| | Spot-welds not fused or are burnt through, cracked, or fractured..... | X | |
| | Spot-weld not smooth..... | | X |
| | Housing edges contacting or surrounding napkins, not flared out..... | X | |
| | Edges not smoothly finished..... | X | |
| | Steel strip spring not securely attached to pressure plate and base..... | X | |
| | Steel wire spring not securely attached to pressure plate only..... | X | |
| | Pressure plate not retained in housing when dispenser is empty..... | X | |
| | Any sharp edges or any part of dispenser that may cause injury..... | X | |
| Marking | Not stamped or embossed, missing, incomplete, illegible, wrong location.. | | X |

4.3.2.2 Dimensional examination. Inspection will be made of dispensers for compliance with dimensions specified. Any dimension not within specified tolerances shall constitute a defect.

4.3.2.3 Inspeciton levels and AQL's. The acceptable quality levels (AQL's) expressed in defects per hundred units, and inspection levels shall be as follows:

| For Examination in | Defect | Inspection level | AQL |
|---|---|---|---|
| 4.3.2.1 | Major | II | 2.5 |
| 4.3.2.1 | Total | II | 6.5 |
| 4.3.2.2 | Total | S-2 | 6.5 |

4.3.2.4 Testing of the end item. Testing shall be performed on each sample unit of dispensers for functioning as specified in 4.4.1. The inspection level shall be S-2 and acceptable quality level (AQL) 6.5 defects per hundred units.

4.3.3 Examination of preparation for delivery. An examination will be made to determine that packaging, packing and marking as required by section 5 of this specification are complied with. Defects will be scored as specified below. For examination of interior packages the sample unit shall be one shipping container fully prepared for delivery selected at random just prior to the closing operations. Defects of closure listed shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of containers in the inspection lot. The inspection level shall be level S-2 of MIL-STD-105 and the acceptable quality level shall be 4.0 defects per hundred units.



Source: https://assist.dla.mil -- Downloaded: 202610-26T12:10Z
Check the source to verify that this is the current version before use.

| Examination | Defects |
|---|---|
| Marking | Omitted; incorrect; illegible; of improper size, location, sequence or method of application. |
| Materials | Component missing, damaged or otherwise defective.<br>Incomplete sealing of corners and joints or closure of container flaps, inadequate stapling; bulging or distortion of containers. |
| Contents | Number per container is more or less than required or packages not snug fitting in container. |

4.4 Tests.

4.4.1 Functioning. The dispenser shall be loaded with 125, 13 by 13-1/2 inch embossed paper napkins folded to 3-1/2 by 6-3/4 inches nominal size. The dispenser shall be tested for conformance to ease of removal specified in 3.4 by removal of the napkins one at a time.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C as specified (see 6.2).

5.1.1 Level A. Each dispenser shall be packaged in a close fitting, gusseted, polyethylene bag. The bag opening shall be located at the smallest dimension. The polyethylene, flexible film shall be minimum 0.003-inch thick conforming to type II, grade A, B or C, finish 1 of L-P-378. All seams shall be heat-sealed. Bag closure shall be effected by heat-sealing or double-folding the plastic material at the mouth and taping it to the bag body with minimum 1-inch width tape. All seams and closures effected by heat-sealing shall conform to the heat-seal strength requirements of L-P-378. Prior to or during the final closure operation, excess air within the bag shall be expelled.

5.1.2 Level B. Each dispenser shall be packaged in a box conforming to PPP-B-566, variety 1, style II, Type A, class A. Closure shall be in accordance with the appendix to the box specification.

5.1.3 Level C. Each dispenser shall be packaged in accordance with the industry's practice.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. Twelve dispensers packaged as specified in 5.1, shall be packed two in length, three in width, and two in depth in a snug-fitting, fiberboard shipping container conforming to V3c or V3s, style RSC of PPP-B-636. The dispensers shall be positioned base to base, with one of the openings facing down and the tops facing the end panels of the shipping container. A separator pad made of the same material as the shipping container, with length and width dimensions one-eight of an inch less than the inside length and width of the shipping container, shall be placed between each tier. Each fiberboard shipping container shall be closed and reinforced with flat steel strapping or tape banding in accordance with the appendix of PPP-B-636.

5.2.2 Level B. Twelve dispensers, packaged as specified in 5.1.2, shall be packed in a box conforming to PPP-B-636, class domestic. The box shall be closed in accordance with the appendix to PPP-B-636.

5.2.3 Level C. The dispensers packaged as specified in 5.1, shall be packed in containers to assure carrier acceptance and safe arrival at destination in compliance with National Motor Freight Classification rules or Uniform Freight Classification rules, as applicable.

5.3 Marking. In addition to any special markings required by the contract or order, all marking shall be in accordance with 5.3.1 or 5.3.2, as specified (see 6.2).

5.3.1 Civil agencies. All marking shall be in accordance with Fed. Std. No. 123.

5.3.2 Military agencies. All marking shall be in accordance with MIL-STD-129.



Source: https://assist.dla.mil -- Downloaded: 202640-26T12:10Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. Paper napkin dispenser covered by this specification is intended for the storage and easy dispensing of napkins folded to a 3-1/2 inch by 6-3/4 inch size.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following in procurement documents:

(a) Title, number, and date of this specification.
(b) Whether preproduction is required (see 3.1).
(c) Selection of the applicable levels of packaging and packing (see 5.1 and 5.2).
(d) Marking required (see 5.3).

Preparing activity:

GSA-FSS

Civil Agency Coordinating Activities:

GSA-FSS
VA-DMS

Orders for this publication are to be placed with the General Services Adminstration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 10 cents each.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:10Z
Check the source to verify that this is the current version before use.