RR-D-527a
October 21, 1966
SUPERSEDING
Int. Fed. Spec. RR-D-00527 (GSA-FSS)
April 20, 1964

FEDERAL SPECIFICATION

DISPENSER, TOOTHPICK

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 This specification covers one type of dispenser suitable for dispensing toothpicks, one at a time.

2. APPLICABLE DOCUMENTS

2.1 The following specifications and standards, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

L-P-349—Plastic Compounds, Molding, Cellulose Acetate Butyrate; and Molded or Extruded Parts.
L-P-396—Plastic Molding, Polystyrene.
PPP-B-566—Boxes, Folding, Paperboard.
PPP-B-585—Boxes, Wood, Wirebound.
PPP-B-591—Boxes, Fiberboard, Wood-Cleated.
PPP-B-601—Boxes, Wood, Cleated-Plywood.
PPP-B-621—Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636—Box, Fiberboard.
PPP-B-640—Boxes, Fiberboard, Corrugated, Triple-Wall.
PPP-B-665—Boxes; Paperboard, Metal Stayed (Including Stay Material).
PPP-B-676—Boxes, Setup.

Federal Standard:

Fed. Std. No. 123—Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Dallas Denver, San Francisco, Los Angeles, and Seattle, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105—Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129—Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 **Material.** The material shall conform to the requirements specified hereinafter. Materials not definitely specified shall be of the quality normally used for the purpose in commerical practice.

Source: https://assist.dla.mil -- Downloaded: 2015-08-19T15:00Z
Check the source to verify that this is the current version before use.
Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:10Z
Check the source to verify that this is the current version before use.

3.1.1 *Dispenser body.* The dispenser body shall be formed of stainless steel, wood, or plastic, as specified (see 6.2).

3.1.1.1 *Metal.* The metal dispenser body shall be formed of stainless steel and shall be of sufficient thickness to assure adequate strength.

3.1.1.2 *Wood.* The wooden dispenser body shall be made of the best grade of hardwood.

3.1.1.3 *Plastic.* The plastic dispenser body shall be formed of molded cellulose actetate plastic conforming to L-P-349 or molded polystyrene plastic conforming to L-P-396 and of sufficient thickness to assure adequate strength.

3.1.2 *Dispenser base.* The dispenser base shall have four nonskid pads of a nonmetallic material.

3.1.3 *Delivery mechanism.* The delivery mechanism of the dispenser shall be of either metal or plastic composition.

3.2 **Color.** The plastic composition dispenser shall be made in three colors: red, black, or white, as specified (see 6.2). Wood and stainless steel dispensers shall be in natural color.

3.3 **Refill opening.** Adequate and simple means shall be provided for cleaning and refilling the dispensers.

3.4 **Exposed or visible parts.** All exposed or visible parts of stainless steel shall have a polished finish. All exposed or visible parts of wood shall have a lacquer finish. All exposed or visible parts of plastic shall be uniform in gloss.

3.5 **Stability.** The dispenser shall remain stable and shall not slip or scuff when tested in accordance with 4.4.3.

3.6 **Jamming.** The dispenser shall not jam when tested in accordance with 4.4.2.

3.7 **Design.** The dispenser shall be designed to have a minimum capacity of 300 round hardwood toothpicks, approximately 2-5/8 inches in length. The dispenser shall deliver one round toothpick at a time. The delivery mechanism shall be constructed to be actuated by dial or lever action. The dispenser shall have four cushion nonmetallic pads to prevent slipping and scuffing.

3.8 **Workmanship.** The dispensers shall be free of pits, warpage, sharp projections and edges, and defects which might impair the serviceability or appearance.

4. QUALITY ASSURANCE PROVISIONS

4.1 **Responsibility for inspection.** Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Governement. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 **Sampling.**

4.2.1 *Lot.* Unless otherwise specified (see 6.2), a lot shall consist of all dispensers submitted for inspection at the same time.

4.2.2 *Visual and workmaship examination of end item.* Sampling for these characteristics shall be in accordance with level S-3 in MIL-STD-105.

4.2.3 *Sampling for test.* Sampling for tests shall be in accordance with level S-2 of MIL-STD-105.

4.3 **Inspection.**

4.3.1 *End item.* Dispensers shall be examined for defects listed in table I. The acceptable quality level (AQL's) for defects listed in table I, shall be 2.5 percent de-

Source: https://assist.dla.mil -- Downloaded: 2015-08-19T15:00Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:10Z
Check the source to verify that this is the current version before use.

fective for major defects and 4.0 percent defective for minor defects.

TABLE I. *Classification of defects, end item*

Defect	Major	Minor
Pits, sharp projections, or edges	X	
Warpage	X	
Finish not uniform in gloss	X	
Pads missing		X
Damage or defects affecting function or serviceability	X	
Damage or defects not affecting function or serviceability		X

4.3.2 *Inspection of preparation for delivery requirements.* An inspection shall be made to determine that packaging, packing, and marking requirements comply with section 5. Defects shall be scored in accordance with table II. For examination of contents, the sample unit shall be one shipping container fully prepared for delivery selected just prior to the closing operations. Sampling shall be in accordance with MIL-STD-105. Defects of closure listed shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be II and the AQL shall be 6 defects per hundred units.

TABLE *II. Classification of preparation for deivery defects*

Examine	Defects
Markings (exterior and interior)	Omitted; incorrect; illegible; improper size, location, sequence, or method of application.
Materials	Any component missing or damaged.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping, or inadequate stapling.
	Bulging or distortion of container.

4.4 Tests.

4.4.1 *AQL.* The AQL for tests shall be 6.5 on the basis of percent defective.

4.4.2 *Operation.* The dispenser shall be filled with 300 round hardwood toothpicks, 2-5/8 inches maximum length. The delivery mechanism shall be actuated for 25 consecutive times. The dispenser shall deliver a minimum of 23 toothpicks, one at a time during this cycle (see 3.6).

4.4.3 *Stability.* The dispenser shall be placed on a smooth surface, such as glass or plastic, and actuated for 10 times (see 3.5).

5. PREPARATION FOR DELIVERY

5.1 **Packaging.** Packaging shall be level A, B or C, as specified (see 6.2).

5.1.1 *Level A.*

5.1.1.1 *Unit packaging.* Each dispenser shall be packaged in a close-fittting box conforming to PPP-B-566, style X; PPP-B-665, style C; or PPP-B-676, type 1. Cushioning shall be provided. The box shall be closed in accordance with the appendix of the box specification.

5.1.1.2 *Intermediate packaging.* Twelve unit packages of like description shall be packaged together in a close-fitting box conforming to PPP-B-636, class weather-resistant, style RSC. The box shall be closed in accordance with the appendix to the box specification.

5.1.2 *Level B.*

5.1.2.1 *Unit packaging.* Each dispenser shall be packaged in a close-fitting box conforming to PPP-B-566, style X; PPP-B-665, stye C; or PPP-B-676, type 1. Cushioning shall be provided. The box shall be closed in accordance with the appendix to the box specification.

5.1.2.2 *Intermediate packaging.* Twelve unit packages of like description shall be packaged together in a close-fitting box conforming to PPP-B-636, class domestic. The box shall be closed in accordance with the appendix to the box specification.

5.1.3 *Level C.* The dispensers shall be packaged in accordance with the supplier's commercial practice.

Source: https://assist.dla.mil -- Downloaded: 2015-08-19T15:00Z
Check the source to verify that this is the current version before use.
Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:10Z
Check the source to verify that this is the current version before use.

5.2 **Packing.** Packing shall be level A, B, or C, as specified (see 6.2).

5.2.1 *Level A.* Dispensers of like description shall be packed together in close-fitting boxes conforming to PPP-B-585, class 3; PPP-B-591, class II; PPP-B-601, type II, class 2; PPP-B-621, class 2; PPP-B-636, class weather-resistant, or PPP-B-640, class 2, grade A. The fiberboard boxes shall be closed in accordance with the appendix to the box specification. The gross weight of the triple-wall fiberboard box and the wood boxes shall not exceed approximately 200 pounds. The gross weight of the PPP-B-636 fiberboard box shall not exceed the weight limitations of the box specification. Strapping shall be in accordance with the appendix to the applicable box specification.

5.2.2 *Level B.* Five intermediate packages of like description shall be packaged together in a close-fitting box conforming to PPP-B-636, class domestic. The box shall be closed in accordance with the appendix to the box specification.

5.2.3 *Level C.* The dispenser shall be packed to insure carrier acceptance and safe delivery to destination in containers complying with the rules and regulations applicable to the mode of transportation.

5.2.4 *Standard pack (civil agency procurements).* The standard pack for civil agency procurements shall be as specified in 5.1.2. and 5.2.2.

5.3 **Marking.**

5.3.1 *Civil agencies.* In addition to markings required by the contract or order, the packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.3.2 *Military agencies.* In addition to markings required by the contract or order, the packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 **Intended use.** *Toothpick* dispensers covered by this specification are intended for *single delivery of round wooden toothpicks.*

6.2 **Ordering data.** Purchases should select the preferred options permitted herein and include the following information in procurement documents:

(*a*) Title, number, and date of this specification.
(*b*) Material required (see 3.1.1).
(*c*) Color desired (see 3.2).
(*d*) Size of lot, if different from 4.2.1.
(*e*) Selection of applicable levels of packaging and packing required (see 5.1 and 5.2).

MILITARY INTEREST:

Army—GL

Navy—S and A

Air Force—67

4

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 5 cents each.

Source: https://assist.dla.mil -- Downloaded: 2015-08-19T15:00Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:10Z
Check the source to verify that this is the current version before use.