RR-I-660B
June 23, 1970
SUPERSEDING
Fed. Spec. RR-I-660A
August 6, 1968

FEDERAL SPECIFICATION

IRONING BOARD, PADS AND COVERS; (HOUSEHOLD)

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers household metal ironing boards, and pads and covers used on ironing boards.

1.2 Classification.

1.2.1 The ironing boards, pads, and covers shall be of the following types and classes, as specified (see 6.2).

Type I - Ironing board with pad and cover.
Type II - Ironing board without pad and cover.
Type III - Pads.
  Class A - Blend (cellulosic and synthetic).
  Class B - Blend (cellulosic and synthetic) with foamed plastic base.
Type IV - Covers.
  Class A - Cotton.
  Class B - Silicone-aluminum treated.
  Class C - Polytetrafluoroethylene (TFE).
  Class D - Acetylated cotton.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issues in effect on the invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

V-T-276 - Thread, Cotton.
CCC-C-426 - Cloth, Drill, Cotton.
CCC-C-430 - Cloth, Sheeting, Cotton.
PPP-B-585 - Boxes, Wood, Wirebound.
PPP-B-591 - Boxes, Fiberboard, Wood Cleated.
PPP-B-601 - Boxes, Wood, Cleated-Plywood.
PPP-B-621 - Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636 - Box, Fiberboard.
PPP-B-640 - Boxes, Fiberboard, Corrugated, Triple-Wall.
PPP-F-320 - Fiberboard; Corrguated and Solid, Sheet Stock (Container Grade), and Cut Shapes.

Federal Standards:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies).
Fed. Test Method Std. No. 191 - Textile Test Methods.
Fed. Std. No. 751 - Stitches, Seams, and Stitchings.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C. 20402.

FSC 7290

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, Washington.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

Textile Fiber Products Identification Act.

(Copies of the Textile Fiber Products Identification Act may be obtained free of charge from the Federal Trade Commission, Washington, D.C. 20580.)

National Classification Board:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., Attn: Tariff Order Section, 1616 P Street, N.W., Washington, D.C. 20036.)

Uniform Classification Committee:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, 202 Union Station, Chicago, Ill. 60606.)

3. REQUIREMENTS

3.1 Ironing boards, types I and II.

3.1.1 Material. The ironing surface and legs of type I and type II ironing boards shall be made of carbon steel.

3.1.2 Design and construction.

3.1.2.1 Type I and Type II ironing board. The board shall be designed to provide a stable, smooth, ventilated ironing surface. One end of the board shall be square, with corner radius, the other end tapered. The board shall be adjustable in height to accommodate either "sit down" or "stand up" ironing. The board shall be designed to fold flat for vertical storage. Mechanism for opening, closing, and locking the board in the various height adjustments shall be provided.

3.1.2.1.1 Top. The top shall be vented or perforated. The size and spacing of the openings shall be at the manufacturer's option. The top shall be of sufficient strength and rigidity to support the minimum load requirements as specified in 3.1.4. The top shall have a rolled or smoothly finished edge. The dimensions of the top shall be in accordance with table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

TABLE I. Dimensions of ironing board top

	Inches
Length	54 ± 1
Width	14-1/2 ± 1/2
Corner radius (wide end), minimum	1-3/8
Radius (narrow end), minimum	1-1/2
Length of taper	22-1/4 ± 5
Edge width	1 + 3/4 − 0

3.1.2.1.2 Legs. Legs shall be made from welded, lock seam, or seamless steel tubes, either round, square, hexagonal, or rectangular. The size, thickness, and number of legs shall be at the manufacturer's option. The base ends of the legs or feet shall be equipped with plastic or rubber caps that shall not mar or mark floors (see 4.4.2.4).

3.1.2.1.3 Operating mechanism. Board shall be equipped with a mechanism for opening, closing, as well as locking in at least 10 different position heights. Locked position heights shall range from a low of 22 ± 2 inches to a full open height of 36 ± 2 inches. The design of the mechanism shall be at the option of the manufacturer.

3.1.3 Protective coating. All surfaces of the top and operating mechanism shall be painted. The legs shall be nickel-chrome plated or painted, as specified (see 6.2). Unless otherwise specified (see 6.2), hue, value, and chroma of the color of all painted components shall be at the manufacturer's option.

3.1.4 Performance. Ironing boards shall be rigidly constructed, free of wobble, capable of supporting 50 pounds when set in any ironing position (see 4.4.2.1), and shall not tip when tested in accordance with 4.4.2.2. The operating mechanism shall not show malfunction when tested in accordance with 4.4.2.3.

3.1.5 Marking. Ironing boards shall be clearly marked with the manufacturer's name or trademark.

3.2 Pads, type III.

3.2.1 Material. Type III, class A and B pads shall be made of a uniform combination of cellulosic fibers (except bast and structural) and synthetic fibers, and plastic foam (polyurethane).

3.2.2 Design and construction.

3.2.2.1 Type III class A. Pads shall be constructed of uniform combination of cellulosic fibers (except bast and structural) and synthetic fibers held together by needle punching. The weight of the pads shall not be less than 12 ounces per square yard.

3.2.2.2 Type III class B. Pads shall be constructed of a layer of foam plastic (polyurethane) laminated to a uniform combination layer of cellulosic fibers (except bast and structural) and synthetic fibers. The combination layer shall be held together by needle punching. The weight of the laminated pad shall not be less than 12 ounces per square yard.

3.2.2.3 Edging. The entire edge of the type III pads shall be finished using a 64 x 56 minimum bias-cut cotton binding. The width of the binding shall not be less than 1-1/2 inches. The binding shall be stitched to the pad not less than 4 stitches per inch, using a 40/3 thread, minimum.

3.2.2.4 Dimensions. The finished overall length of the pad shall be 55 ± 1 inches. The width at the wide end shall be 15 ± 1/2 inches. The pad shall have a gradual taper starting not more than 38 inches from the wide end and tapering to a minimum radius of 3-1/2 inches at the narrow end. The pad shall be not less than 1/4 inch in thickness.

3.2.3 Fiber identification. Each pad or bag containing pad, shall be labeled, ticketed, or invoiced for fiber content in accordance with the rules and regulations under the Textile Fiber Products Identification Act.

3.3 Covers, type IV.

3.3.1 Material. Type IV, class A, B, C, and D, covers shall be constructed of cotton, cotton with the addition of silicone-aluminum coating, cotton with the addition of polytetrafluoroethylene coating, or acetylated cotton. Covers shall be fabricated of either sheeting or drill cloth at the option of the manufacturer. Sheeting shall conform to the requirements of CCC-C-430, type I, class I, style A. Drill cloth shall conform to the requirements of CCC-C-426, type III, class 2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

3.3.2 Design and construction.

3.3.2.1 Type IV, class A cover. Cover shall be made from unbleached cotton sheeting or drill cloth, and shall be one piece construction. The cover shall be a tapered envelope type, and the taper shall start 36 inches ± 1 inch from the wide end tapering to the narrow end. The edges of the covers shall have a 3/8 inch ± 1/8 inch wide hem, and shall extend the entire distance around the cover. The hem shall have an opening at either the narrow or the wide end for extending the ends of the cord (see 3.3.4), and the cord ends shall extend 4 inches beyond the opening. When tie tapes (see 3.3.3) are provided, at the option of the manufacturer, they shall be not less than 16-1/2 inches long, and shall be sewn into the hem, one at each side of the cover, approximately 26 inches from the wide end.

3.3.2.2 Type IV, class B, cover. Cover shall meet the requirements of 3.3.2.1 with the addition of a silicone-aluminum coating.

3.3.2.3 Type IV, class C, cover. Cover shall meet the requirements of 3.3.2.1 with the addition of a polytetrafluoroethylene coating.

3.3.2.4 Type IV, class D, cover. Cover shall meet the requirements of 3.3.2.1 except that the cotton shall be acetylated.

3.3.3 Tape (tie). Tie tapes shall be bleached or unbleached woven cotton fabric, 1/2 plus or minus 1/8 inch in width. There shall be not less than 25 yarns of 2 ply construction in the warp direction and not less than 16 yarns per inch in the filling direction.

3.3.4 Cord. The cord shall be of bleached or unbleached cotton, 3 strand cable construction, each strand consisting of 6 plies and shall be approximately 1/16 inch in diameter.

3.3.5 Sewing thread. Thread used for all sewing shall be not less than 50/3 cord conforming to type IA1 of V-T-276.

3.3.6 Stitches, seams, and stitching. All seaming and stitching operations shall be done with not less than 6 stitches per inch using lock stitch type 301 and any suitable seam type as described in Fed. Std. No. 751. Thread breaks and ends of all stitchings when not caught in other stitchings shall be securely backstitched.

3.3.7 Dimensions, Type IV covers. The finished overall length of the covers shall be not less than 56 inches. The width at the wide end shall be not less than 19 inches and the width at the narrow end shall be not less than 7 inches.

3.4 Workmanship. The ironing surface of the board shall be smooth. The edges and operating mechanism of the board shall be free from projections, sharp edges and defects that may damage fabrics or cause hand injuries. The pad, and cover shall not have any tears, holes, cuts, weak spots, puckers, or defects that might affect their serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling. The sampling size and levels shall be in accordance with MIL-STD-105.

4.2.1 Lot. Unless otherwise specified (see 6.2), a lot shall consist of all ironing boards, pads, and covers submitted for inspection at the same time.

4.2.2 Sampling for dimensional and visual inspection of end item. Sampling of ironing boards, pads, and covers for these characteristics shall be in accordance with level S-3.

4.2.3 Sampling for tests. Sampling for tests shall be in accordance with level S-2.

4.3 Inspection.

4.3.1 End item. Ironing boards, pads and covers selected in 4.2.2 shall be examined for defects listed in table II. The acceptable quality levels (AQL's) for defects shall be 2.5 percent defective for major defects and 4.0 percent defective for minor defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of defects, end item

Defects	Major	Minor
Ironing boards		
Dimensions not as specified.	X	
Top not vented or perforated.	X	
Board does not fold flat for storage.	X	
Uncoated area (paint or plating).	X	
Marking illegible or missing.		X
Damage or defects affecting function or serviceability.	X	
Damage or defects not affecting function or serviceability.		X
Any component missing or damaged.	X	
Pads and covers		
Any component missing or damaged, affecting serviceability.	X	
Hole, cut, or tear.	X	
Tender or weak spots.	X	
Edge not finished.	X	
Edges wavy, twisted, or puckered	X	
Oil, or grease spots or objectionable odor.	X	
Two or more warpwise rows of stitching broken or missing (except type III pad).	X	
Sewing thread, not as specified.	X	
Damage or defects affecting function or serviceability.	X	
Damage or defects not affecting function or serviceability.		X
Fiber identification missing (type III pad).		X

4.3.2 Inspection of preparation for delivery requirements. An inspection shall be made to determine that the packaging, packing, and marking comply with the requirements in section 5 of this specification. Defects shall be scored in accordance with table III. For examination of interior packaging the sample unit shall be one shipping container fully prepared for delivery, selected at random just prior to the closing operations. Sampling shall be in accordance with MIL-STD-105. Defects of closure listed in table III shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 with an acceptable quality level (AQL) of 4.0 defects per hundred units.

TABLE III. Classification of preparation for delivery defects

Examine	Defects
Markings (exterior and interior)	Omitted; incorrect; illegible; improper size, location, sequence, or method of application.
Materials	Any component missing or damaged.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping, inadequate stapling. Distortion of container.

4.4 Tests and examinations.

4.4.1 Acceptable quality level. The AQL for tests shall be 6.5 on the basis of percent defective.

4.4.2 Ironing boards.

4.4.2.1 Rigidity. With the ironing board opened to a standing position, place a 50 pound weight on the center surface of the board. The bearing area for the load shall not be more than 8 inches by 8 inches square (see 3.1.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

4.4.2.2 Stability. Open the ironing board and place it in a standing position on a smooth floor. Position a steel block approximately 3 by 7 by 7-1/2 inches and weighing 25 pounds on the centerline of the board, 1-1/2 inches from the wide end. Slide the weight along the centerline toward the narrow end to a point 7 inches from the tip (see 3.1.4).

4.4.2.3 Operation. The board shall be opened and closed a minimum of 10 times and the board shall be put in at least 5 different height positions, after which an examination shall be made to determine the workmanship and serviceability of the operating mechanism (see 3.1.2.1.3 and 3.1.4).

4.4.2.4 Marring. Place a 20 pound weight of convenient size, at or near the center of the board opened to any height position. Slide the board over a polished floor for a distance of at least 6 feet, a minimum of 3 times (see 3.1.2.1.2).

4.4.3 Type III, class A and B pads. Test in accordance with applicable methods of Fed. Test Method Std. No. 191 listed in table IV.

TABLE IV. Test methods for pads

Characteristics	Requirement reference	Test Method	No. determinations per individual unit of product	Results reported as
Fiber identification	3.2.1	1200 1500 1600	As required " "	Pass or fail " "
Weight in ounces (per sq. yd.)	3.2.2.1 3.2.2.2	5041 5041	5 5	Avg. determinations to nearest ounce "

4.4.4 Type IV, class A, B, C, and D covers. Test in accordance with the applicable methods of V-T-276, CCC-C-426, CCC-C-430, Fed. Std. No. 751, and referenced methods of Fed. Test Method Std. No. 191 in table V. Examine visually for conformance to yarn ply requirements in 3.3.3 and 3.3.4.

TABLE V. Test methods for covers

Test	Reference paragraph	Test Method
Identification of cotton Yarns per inch	3.3.1, 3.3.3, 3.3.4 3.3.3	1200 5050

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Type I, ironing board with pad and cover. Each type I ironing board with pad and cover shall be packaged in a close-fitting box conforming to PPP-B-636, class weather resistant. Cushioning and blocking shall be provided to prevent damage to the items. The box shall be closed and waterproofed in accordance with the appendix to the box specification.

5.1.1.2 Type II, ironing board without pad or cover. Each type II ironing board shall be packaged in a close-fitting box conforming to PPP-B-636, class weather resistant. Cushioning and blocking shall be provided to prevent damage to the item. The box shall be closed and waterproofed in accordance with the appendix to the box specification.

5.1.1.3 Type III or IV, pad or cover. Each type III pad or type IV cover shall be packaged in a plastic bag, closed or sealed.

5.1.2 Level B.

5.1.2.1 Type I, ironing board with pad and cover. Type I ironing board with pad and cover shall be packaged in a close-fitting box conforming to PPP-B-636, class domestic. Cushioning and blocking shall be provided to prevent damage to the items. The box shall be closed in accordance with the appendix to the box specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

5.1.2.2 Type II, ironing board without pad or cover. Type II ironing board shall be packaged in a close-fitting box conforming to PPP-B-636, class domestic. Cushioning and blocking shall be provided to prevent damage to the items. The box shall be closed in accordance with the appendix to the box specification.

5.1.2.3 Type III or IV, pad or cover. Each type III pad or type IV cover shall be packaged in a plastic bag, closed or sealed.

5.1.3 Level C. The ironing boards, pads or covers shall be packaged in accordance with the suppliers commercial practice.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A.

5.2.1.1 Type I or II ironing boards. Unit packages of type I or II ironing boards in quantities as specified (see 6.2) shall be packed in a close-fitting box conforming to PPP-B-585, class 3, PPP-B-591, class II, PPP-B-601, overseas type, PPP-B-621, class 2, PPP-B-636, weather resistant or PPP-B-640, class 2, grade A. The boxes shall be closed and strapped in accordance with the applicable specification or appendix thereto. The gross weight of the triple wall box or the wood boxes shall not exceed 200 pounds. The gross weight of the PPP-B-636 box shall not exceed the weight limitations of the box specification.

5.2.1.2 Type III or IV, pads or covers. Unit packages of type III pads or type IV covers in quantities as specified (see 6.2) shall be packed in a close-fitting box conforming to PPP-B-636, class weather resistant. The box shall be closed, waterproofed, and strapped in accordance with the appendix to the box specification.

5.2.2 Level B.

5.2.2.1 Type I or II, ironing boards. No packing required.

5.2.2.2 Type III or IV, pads or covers. Unit packages of type III pads or type IV covers in quantities as specified (see 6.2) shall be packed in a close-fitting box conforming to PPP-B-636, class domestic. The box shall be closed in accordance with the appendix to the box specification.

5.2.3 Level C. The ironing boards, pads, or covers shall be packed in containers to assure carrier acceptance and safe delivery at destination in compliance with Uniform Freight Classification Rules or National Motor Freight Classification Rules.

5.3 Marking.

5.3.1 Civil agencies. In addition to markings required by the contract or order, the interior packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.3.2 Military agencies. In addition to markings required by the contract or order, the interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. Ironing boards, pads and covers, covered by his specification are intended for ordinary household ironing chores.

6.2 Ordering data. Purchasers should select the preferred options permitted herein, and include the following data in procurement documents:

(a) Title, number, and date of this specification.
(b) Type and class (see 1.2.1).
(c) Finish of legs; color of painted components (see 3.1.3).
(d) Size of lot if different from 4.2.1.
(e) Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

MILITARY CUSTODIANS

Army - GL
Air Force - 84

Preparing activity:

GSA-FSS

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 10 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

GENERAL SERVICES ADMINISTRATION - FEDERAL SUPPLY SERVICE

SPECIFICATION COMMENT SHEET

BUDGET BUREAU NO. 29-R0175

INSTRUCTIONS

This form provides a way for users of this specification to inform the originator of problems encountered in its use. It is not to be used to request changes to accommodate proprietary features. All comments will be considered and appreciated, but please do not expect a reply. To comment: detach, complete, and Mail to General Services Administration., FSS (FMSH), Wash, D.C. 20406.

NOTE: Comments on this form do not constitute or imply authorization to waive any part of the document or serve to amend contractual requirements.

1. SPECIFICATION

RR-I-660B Ironing Board, Pads and Covers; (Household)

2. CONTRACT NO. *(If any)*	3. QUANTITY ON CONTRACT *(Optional)*	4. DOLLAR VALUE *(Optional)*

5. GENERAL NATURE OF PROBLEM *(e.g., inspection difficulties, manufacturers unable to meet tolerances, containers collapse under normal warehousing conditions, etc.)*

6. SPECIFIC REQUIREMENTS AFFECTED *(Include paragraph number and lines of wording)*

7. SPECIFIC PROBLEMS *(e.g. tests in 4.2.2 will not assure that the battery will last required time; temperature ranges in table 2 do not conform to commercially available items.)*

8. RECOMMENDATIONS

9. NAME OF MANUFACTURER, ASSOCIATION, GOVT., AGENCY, ETC.	10. ADDRESS *(Number, Street, City, State and Zip Code)*

11. NAME AND TITLE OF SUBMITTER	12. DATE

GSA PC 49-9741 FORM

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.