RR-P-00560(GSA-FSS)
March 23, 1967

INTERIM FEDERAL SPECIFICATION

POST, LEDGER AND BINDER, SCREW-TYPE

This Interim Federal Specification was prepared by the General Services Administration, Federal Supply Service, Standardization Division, Washington, D. C. 20406, based upon currently available technical information. It is recommended that Federal agencies use this document in procurement and forward recommendations for changes to the preparing activity.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers requirements for screw-type posts designed primarily for retaining punched papers in ledger and post binders.

1.2 Classification.

1.2.1 Type and grade. The posts shall be of but one type and grade.

1.2.2 Lengths of posts. Posts shall be furnished in the lengths listed in 3.3.2, as specified (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 The following specifications and standards of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification:

Federal Specifications:

QQ-A-225 - Aluminum Alloy Bar, Rod, Wire or Special Shapes; Roller, Drawn, or Cold Finished; General Specification for.
QQ-A-225/1 - Aluminum Alloy Bar, Rod, and Wire; Rolled, Drawn, or Cold Finished, 1100.
PPP-B-566 - Boxes; Folding, Paperboard.
PPP-B-636 - Box, Fiberboard.
PPP-B-665 - Boxes; Paperboard, Metal-Stayed (Including Stay Material).
PPP-B-676 - Boxes, Setup.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, and Seattle, Wash.

FSC 7510

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:10Z
Check the source to verify that this is the current version before use.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specification:

MIL-P-116 - Preservation, Methods of.

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material. The wire from which the screw-type ledger and binder posts are fabricated shall be aluminum alloy conforming to the chemical composition, and other requirements as applicable, of QQ-A-225 and QQ-A-225/1.

3.2 Design and construction. Each post shall consist of two sections, an internally threaded post section and a matching externally threaded post section. Internal threads shall be countersunk and external threads shall be chamfered in a manner to provide a smooth, secure fit and easy assembly and disassembly of the sections. Unless otherwise specified, the threaded part of each post section shall be a minimum length of 3/8 inch, except posts 1/4 inch in length which shall have 1/4-inch thread length. Each post section shall have a head and heads of posts with external threads shall be slotted. Slots shall be centered in the head. Unless otherwise specified, heads shall be "pan" or "truss" style. Head and shank of posts shall be concentric. The assembled posts shall withstand normal conditions of use for the purpose intended.

3.3 Dimensions and tolerances.

3.3.1 Outside diameter. Internally threaded posts shall have an outside diameter of 0.203 ± 0.0015 inch. Heads of externally threaded post sections shall be 3/8 ± 1/32 inch.

3.3.2 Lengths of posts. Posts shall be furnished in the following lengths, as specified (see 6.1):

Lengths (in inches): 1/4, 3/8, 1/2, 5/8, 3/4, 1, 1-1/4, 1-1/2, 1-3/4, 2, 2-1/2, 3, 3-1/2, and 4.

3.4 Finish. Posts shall have a bright, barrel-tumbled finish or a finish in accordance with the manufacturer's normal commercial practice provided it is similar in appearance to that specified.

3.5 Workmanship. Workmanship shall be in accordance with good commercial practice. Posts shall be clean and free from burrs, rough or sharp edges, grease, oil, and other defects which might affect the serviceability. Threads shall be true to form, cleanly cut and free from any defects which might affect the serviceability. Particular attention shall be given to concentricity of head and shank, formation, fit and mating of parts, and accuracy of dimensions within tolerances permitted. The posts shall be free from any defects which adversely affect the appearance or performance of the items.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:10Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order (see 6.1), the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling.

4.2.1 Lot. For purposes of sampling, a lot shall consist of all posts of one size (length) offered for acceptance at one time.

4.2.2 Sampling for visual and dimensional examination (end item). A random sample of posts shall be taken from each lot in accordance with MIL-STD-105, inspection level S-3, acceptable quality level (AQL) 4.0 percent defective. The sample unit shall be one post.

4.3 Inspection.

4.3.1 Visual, functional, and dimensional examination. Samples taken in accordance with 4.2.2 shall be examined for defects listed in table I. Any post in the sample containing one or more defects shall be rejected. If the number of defective posts in the sample exceeds the acceptance number for that sample, the lot represented by the sample shall be rejected.

TABLE I. Visual, functional, and dimensional examination of end item

Examine	Defects
Design and construction.	Sections not as specified; section missing. Threaded parts not as specified; do not mate; and do not fit securely. Posts do not assemble smoothly and easily; not firm when assembled. Head not slotted as specified or suitable for purpose intended; slot not centered.
Dimensions and tolerances.	Not as specified, within tolerances permitted.
Size (length).	Not as specified, within tolerance permitted.
Finish.	Not as specified.
Workmanship.	Not as specified. Head and shank eccentric.

4.3.2 Inspection of preparation for delivery. Inspection shall be made to determine compliance with the packaging, packing, and marking requirements of section 5. Defects shall be scored in accordance with table II. The sample unit shall be one shipping container prepared for delivery and selected just prior to the closing operation. Defects of closure listed below shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the AQL, 4.0 defects per 100 units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:10Z
Check the source to verify that this is the current version before use.

TABLE II. Inspection of preparation for delivery

Examine	Defects
Marking (exterior and interior.	Omitted, incorrect, illegible, of improper size, location, sequence, or method of application; not as specified.
Materials and workmanship.	Any component missing; damaged -- affecting serviceability. Bulging or distortion of containers. Inadequate application of components, such as incomplete closure of container flaps; loose strapping.
Contents (count)	Number per container is more or less than required.
Closure.	Not as specified.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C, as specified (see 6.1).

5.1.1 Level A. One hundred posts of like description shall be packaged in accordance with method IC-2 of MIL-P-116.

5.1.2 Level B. One hundred posts of like description shall be packaged in a close-fitting box conforming to PPP-B-566, PPP-B-665, or PPP-B-676.

5.1.3 Level C. The posts shall be packaged to afford protection against corrosion, and damage from the supplier to the initial destination.

5.2 Packing. Packing shall be level A, B, or C, as specified (se 6.1).

5.2.1 Level A. Unit packages of posts of like description, in lengths and quantities as specified (see 6.1), shall be packed in a close-fitting box conforming to PPP-B-636, class: weather-resistant. The box shall be closed and strapped in accordance with the appendix to the box specification.

5.2.2 Level B. Unit packages of posts of like description, in lengths as specified (see 6.1), shall be packed in quantities as specified in table III.

TABLE III. Packing quantities (level B)

Lengths (inches)	Unit packages per shipping container
Less than 1	100
1	70
1-1/4	60
1-1/2	60
1-3/4	60
2	50
2-1/2	50
3	40
3-1/2	30
4	30

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:10Z
Check the source to verify that this is the current version before use.

5.2.3 Level C. The posts shall be packed to insure carrier acceptance and safe delivery at destination in containers complying with the rules and regulations applicable to the mode of transportation.

5.3 Marking.

5.3.1 Civil agencies. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with Fed. Std. No. 123, including specification classification, such as size (length), etc.

5.2.3 Military agencies. In addition to any special marking required by the contract or order, interior packages and exterior shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Ordering data. Purchasers should select the preferred options permitted herein (see 3.2; 3.3) and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Length of post required (see 1.2.2 and 3.3.2).
(c) Data; inspection responsibility if other than as specified.herein (see 4.1).

(d) Levels of packaging and packing required and any special marking for shipment desired (see 5.1, 5.2, and 5.3).

GSA DC 67-15475

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:10Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:10Z
Check the source to verify that this is the current version before use.