RR-P-586a
FEBRUARY 20, 1958
SUPERSEDING
Int. Fed. Spec. RR-P-00586(GSA-FSS)
August 25, 1955, and
Fed. Spec. RR-P-586,
September 23, 1938

FEDERAL SPECIFICATION

POT, MELTING, (NONELECTRIC, SOLDER STYLE)

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 **Scope.**—The solder pots covered by this specification are for the use of tradesmen such as plumbers, tinners, electricians, machinists, etc., for the melting of solder, babbitt, or lead. These pots are heated by means of open flame as contrasted to the electric pots covered by Federal Specification GGG-P-611.

1.1.1 *Federal specification coverage.*—This specification does not include all types, and sizes of solder pots, but includes only those most commonly used by the Federal Government.

1.2 **Classification.**

1.2.1 *Type.*—The solder pots covered by this specification shall be of but one type (see fig. 1).

1.2.2 *Sizes.*—The solder pots shall be of the sizes indicated in table I and as specified in the invitation for bids, contract, or order (see 6.1).

2. APPLICABLE SPECIFICATIONS, STANDARDS, AND OTHER PUBLICATIONS

2.1 **Specifications and standards.**—The following specifications and standards of the issues in effect on date of invitation for bids, form a part of this specification:

Federal Specifications:

QQ-I-652—Iron, Gray; Castings.
PPP-B-566 — Boxes, Folding, Paperboard.
PPP-B-585—Boxes, Wood, Wirebound.
PPP-B-591—Boxes, Fiberboard, Wood-Cleated.
PPP-B-601—Boxes, Wood, Cleated-Plywood.
PPP-B-621 — Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636—Boxes, Fiber.
PPP-B-676 — Boxes, Set-Up, Paperboard.
PPP-T-60 — Tape, Pressure Sensitive Adhesive, Waterproof for Packaging and Sealing.

Federal Standard:

Fed. Std. No. 102—Preservation, Packaging and Packing Levels.

(Activities outside the Federal Government may obtain copies of Federal Specifications and Standards as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which in-

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:10Z
Check the source to verify that this is the current version before use.

cludes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington 25, D. C.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, Seattle, and Washington, D. C.

(Federal Government activities may obtain copies of Federal Specifications and Standards and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specifications:

JAN–P–100 — Packaging and Packing for Overseas Shipment General Specification.

MIL–P–116—Preservation, Methods of.

MIL–B–138—Boxes, Wood, Fiberboard-Lined for Overseas Shipment (for Weight of Contents not Exceeding 500 Pounds).

MIL–B–4229—Boxes; Paperboard, Metal-Stayed.

MIL–B–10377—Box, Wood, Cleated, Veneer, Paper Overlaid.

MIL–L–10547 — Liners, Case, Waterproof.

Military Standards:

MIL–STD–105 — Sampling Procedures and Tables for Inspection by Attributes.

MIL–STD–129 — Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by the contractor in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. — The following publications, of the issues in effect on date of invitation for bids, form a part of this specification:

Nongovernmental:

Consolidated Freight Classification Rules and Container Specifications.

(Application for copies should be addressed to the Consolidated Classification Committee, 202 Chicago Union Station, Chicago 6, Illinois.)

3. REQUIREMENTS

3.1 Illustration. — The illustration shown herein is for the convenience of identification and is not intended to preclude the purchase of solder pots which are otherwise in accordance with the requirements of this specification.

3.2 Material.

3.2.1 *Castings.*—The solder pots covered by this specification shall be made of cast iron, free from blowholes, porosity, checks, and other defects. Wall thickness shall be uniform and the pots shall be clean and smooth. Strength and other essential physical properties of the castings shall be adequate throughout for the purpose intended. When specified, the castings shall conform to the requirements of Federal Specification QQ–I–652 for class of casting designated in the invitation for bids, contract or order (see 6.1).

3.2.2 *Handle.*—The pot handle shall be of the bail type made of wrought iron or steel.

3.3 Design.

3.3.1 *Pot.*—The solder pot shall be rounded and so shaped that when cold the entire contents of metal may be readily removed. A suitable bail shall be securely attached to ears cast integral with the pot. The exterior bottom of the pot shall have a projecting rim approximately ¼ inch thick to prevent the pot from tipping over when placed on a smooth surface.

3.3.2 *Ears.*—The ears of the pot shall be cast integral with the pot in such a manner that the bail will not interfere with the removal of hot or cold metal. They shall be positioned diametrically opposite each other.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:10Z
Check the source to verify that this is the current version before use.

3.3.3 *Bail.*—The bail shall fit smoothly into the ears. It shall move freely in the ears and, when laid horizontally, shall project slightly beyond the top rim of the pot to provide easy gripping of the handle.

3.4 **Dimensions, weights and capacities.**—The solder pots shall conform to the dimensions, weights and capacities specified in table I, and shall be similar to figure 1.



FIGURE 1.—Solder pot.

3.5 **Marking.**—Each pot shall be marked in a plain and permanent manner with the nominal size of the pot and the manufacturer's name or with a trade-mark of such known character that the source of manufacture may be readily determined.

3.6 **Workmanship.**—Workmanship shall be first class in every respect. The solder pots shall be free from defects which may affect their appearance or serviceability.

4. SAMPLING, INSPECTION, AND TEST PROCEDURES

4.1 **Sampling for lot acceptance.**

4.1.1 *Inspection lot.*—All melting pots of the same size, offered for delivery at one time, shall be considered a lot for purposes of acceptance inspection and tests.

4.1.2 *Sampling for inspection and tests.*—From each lot a random sample of melting pots shall be selected for inspection and tests in accordance with Military Standard MIL–STD–105 at inspection level III for lots of 40 and under, inspection level II for lots of 41 to 300, and inspection level I for lots over 300. The acceptance quality level (A.Q.L.) shall be 1.5 percent defective.

4.2 **Inspection and tests.**—Each of the sample pots selected in accordance with 4.1.2 shall be visually and dimensionally inspected for visible cracks, blowholes, sand inclusions, and dark colored chilled spots and shall be subjected to the test specified in 4.3. Any pot in the sample containing one or more visual or dimensional defects, or failing the test shall be rejected, and if the number of defective pots in any sample exceeds the acceptance number for that sample, the lot represented by the sample shall be rejected.

4.3 **Test procedure.**

4.3.1 Each sample pot selected in accordance with 4.1.2 shall be subjected to a light tap on the side to obtain a resonant ring. A flat nonresonant ring indicates an invisible crack and shall be cause for rejection.

TABLE I.—*Sizes, dimensions, weights, and capacities of solder pots*

Nominal size	Wall and bottom thickness (min.)	Weight (min.)	Capacity (min.)	
			Volume	Lead
Inches	*Inch*	*Pounds*	*Cu. In.*	*Pounds*
5	7/32	2½	25	10
6	7/32	3½	50	20
7	7/32	5	60	25
8	7/32	7	100	40
9	7/32	10	145	60
10	7/32	14	225	90

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:10Z
Check the source to verify that this is the current version before use.

4.4 Rejected lots.—Rejected lots may be offered again for inspection provided that the contractor has repaired or removed all nonconforming pots. The inspector shall again select and examine samples from such resubmitted lots to verify compliance with the specification requirements.

5. PREPARATION FOR DELIVERY

(Nonmilitary agencies.—Federal Standard No. 102 should be referred to for definitions and applications of the various levels of packaging protection for supplies and equipment.)

5.1 Preservation and packaging.

5.1.1 *Level A.*—Package one item each in containers conforming to Federal Specifications PPP–B–566, PPP–B–636, PPP–B–676, or Military Specification MIL–B–4229.

5.1.2 *Level C.*—Level C preservation and packaging shall be in accordance with the contractor's commercial practice.

5.2 Packing.

5.2.1 *Level A.*—Pots preserved and packaged as specified in 5.1.1 shall be packed in export-type shipping containers conforming to Federal Specification PPP–B–601, PPP–B–585, PPP–B–621, PPP–B–636, or Military Specification MIL–B–138. As far as practical, exterior containers shall be of uniform shape and size, of minimum cube and tare consistent with the protection required, and shall contain identical quantities. The gross weight of each pack shall be limited to approximately 200 pounds. Strapping and closure shall be in accordance with the appendix of the applicable container specification. Containers shall be provided with a case liner conforming to Military Specification MIL–L–10547 and shall be sealed in accordance with the appendix thereto. As an alternate method, V-board symbol containers conforming to Federal Specification PPP–B–636 may be sealed at all joints and seams with tape conforming to Federal Specification PPP–T–60.

5.2.2 *Level B.*—Pots preserved and packaged as specified in 5.1.1 shall be packed in domestic-type exterior containers conforming to Federal Specification PPP–B–591, PPP–B–585, PPP–B–636, PPP–B–601 or Military Specification MIL–B–10377. Exterior containers shall be of minimum cube and tare consistent with the protection required. As far as practical, exterior containers shall be of uniform shape and size and shall contain identical quantities. The gross weight of each pack shall be limited to approximately 200 pounds. Strapping and closure shall be in accordance with the appendix of the applicable container specification. When fiberboard containers are used, the fiberboard shall meet the special requirements table of Federal Specification PPP–B–585 or PPP–B–636.

5.2.3 *Level C.* — Packages which require overpacking for acceptance by the carrier shall be packed in commercial exterior shipping containers in a manner that will insure safe transportation at the lowest rate to the point of delivery. Containers shall meet Consolidated Freight Classification Rules or regulations of other common carriers as applicable to the mode of transportation.

5.3 Physical protection. — Cushioning, blocking, bracing, and bolting, as required, shall be in accordance with Military Specification JAN–P–100 except that for domestic shipments, waterproofing requirements for cushioning materials and containers shall be waived. The drop tests of Military Specification JAN–P–100 shall be waived when packaging and packing are for immediate use or when the drop tests of Military Specification MIL–P–116 are applicable.

5.4 Marking.

5.4.1 *For military purchases.* — Interior packages and exterior shipping containers shall be marked in accordance with Military Standard MIL–STD–129.

5.4.2 *For nonmilitary purchases.*—Unless otherwise specified, shipping containers shall

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:10Z
Check the source to verify that this is the current version before use.

be marked with the name of the article, the size, and the quantity contained therein, as defined by the contract or order under which shipment is made, the name of the contractor, the number of the contract or order, and the gross weight (see 6.1).

6. NOTES

6.1 Ordering data. — Procurement documents should specify the following:

(*a*) Title, number and date of this specification.

(*b*) Size pot required (see 1.2.1 and table I).

(*c*) Casting requirements, if different than specified (see 3.2.1).

(*d*) Packaging, packing, and marking requirements (see section 5).

6.2 This specification is believed to adequately describe the item under consideration. Normally, no samples will be necessary prior to award to determine specification compliance. When samples are believed necessary, both the request for the sample and the purpose to be served should be specifically stated in the invitation for bids.

6.3 Illustration. — The illustration shown herein is for the convenience of identification and is not intended to preclude the purchase of solder pots which are otherwise in accordance with the requirements of this specification.

6.4 Intended use.—The solder pots covered by this specification are for use by tradesmen such as plumbers, tinners, electricians, machinists, etc., for melting solder, babbitt, or lead. These pots are heated by open flame. When electric soldering pots are desired they should be purchased in accordance with the requirements of Federal Specification GGG–P–611.

Notice. — When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

MILITARY INTERESTS:
Army—O E Sig T
Navy—Sh Y
Air Force.

Copies of this specification may be purchased for 5 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:10Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:10Z
Check the source to verify that this is the current version before use.