RR-P-586a

INTERIM AMENDMENT 1 (DOD)
17 SEPTEMBER 1963

INTERIM AMENDMENT TO FEDERAL SPECIFICATION

POT, MELTING, (NONELECTRIC, SOLDER STYLE)

This Interim Amendment was developed by the U.S. Army Natick Laboratories (GL), Natick, Massachusetts, based on currently available technical information. This Interim Amendment has been approved by the Department of Defense and is mandatory for use by the Department of the Army, the Navy and the Air Force. It is recommended that Federal Agencies use it in procurement. The General Services Administration has authorized the use of this Interim Amendment as a valid exception to Federal Specification RR-P-586a, dated February 20, 1958.

Pages 1 and 2, paragraphs 2.1 and 2.2—Delete in their entirety and substitute:

"2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

FEDERAL SPECIFICATIONS

QQ–I–652	— Iron, Gray; Castings
PPP–B–566	— Boxes, Folding, Paperboard
PPP–B–636	— Box, Fiberboard
PPP–B–665	— Boxes, Paperboard, Metal Stayed, (Including Stay Material)
PPP–B–676	— Boxes, Set-Up, Paperboard

FEDERAL STANDARDS

Fed. Std. No. 102	— Preservation, Packaging, and Packing Levels
Fed. Std. No. 123	— Marking for Domestic Shipment (Civilian Agencies)

(Activities outside the Federal Government may obtain copies of Federal Specifications and Standards as outlined under General information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington 25, D. C.).

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Atlanta, Chicago, Kansas City, Missouri; Dallas, Denver, San Francisco, Los Angeles, Seattle, and Washington, D. C.).

(Federal Government activities may obtain copies of Federal Specifications, Standards and the Index of Federal Specifications and Standards from established distribution points in their agencies).

MILITARY STANDARDS

MIL–STD–105 — Sampling Procedures

FSC 5120

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:10Z
Check the source to verify that this is the current version before use.

and Tables for Inspection by Attributes

MIL–STD–129 — Marking for Shipment and Storage

(Copies of Military Specifications and Standards required by the supplier in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)"

Pages 3 and 4, paragraph 4 through 4.4— Delete and substitute the following:

"4. SAMPLING, INSPECTION AND TEST PROCEDURES.

4.1 **Responsibility for inspection.** Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 **Preproduction sample inspection.** When required, the preproduction sample shall be examined in accordance with the classification of defects in 4.3.2.1, specified dimensions, and shall be tested in accordance with 4.4.1.

4.3 **Sampling for inspection and acceptance.** Sampling for inspection and acceptance shall be performed in accordance with the provisions set forth in Standard MIL–STD–105 except where otherwise indicated.

4.3.1 *Component and material inspection.* In accordance with 4.1 above, the supplier is responsible for insuring that components and materials used are manufactured, tested, and inspected in accordance with requirements of referenced subsidiary specifications and standards to the extent specified, or, if none, in accordance with this specification.

4.3.2 *End item inspection.* All the melting pots of the same type and size offered for acceptance at one time shall be considered a lot for the purpose of inspection. The sample unit for these inspections shall be one completely fabricated melting pot.

4.3.2.1 *Visual examination.* The completely assembled end item shall be examined for defects in design, construction and workmanship, and marking as outlined below. The inspection level shall be II and the acceptable quality level (AQL) shall be 2.5, expressed in terms of defects per hundred units.

Examine	*Defect*
Design	Ears of the pot interfere with removal of cold metal.
	Ears not positioned diametrically opposite each other.
	Bail holes in ears not positioned diametrically opposite each other.
Construction and workmanship.	Bail is not diametrically larger than diameter of pot (at top) to permit free removal of cold metal.
	Pot does not have ¼ inch thick exterior, cast, projecting rim or bottom to prevent the pot from tipping when placed on a smooth surface.
	Pot wall surface not clean or smooth or has dark colored chilled spots.
	Bail does not operate freely.
Marking and identification	Not marked in plain or permanent manner with nominal size of pot or with manufacturer's name or trademark.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:10Z
Check the source to verify that this is the current version before use.

4.3.2.2 *Dimensional, weight and capacity examination.* Inspection shall be of the end item for compliance with dimensions, weight and capacity specified. Any non-compliance with specified requirements shall constitute a defect. The inspection level shall be L6 and the (AQL) shal be 4.0, expressed in terms of defects per hundred units.

4.3.3 *End item testing.* Each sample unit shall be tested as specified in 4.4.1. Any determination not meeting the specified requirement shall constitute a defect. The inspection level shall be L4, and the AQL shall be 4.0, expressed in terms of defects per hundred units.

4.3.4 *Inspection of preparation for delivery.* An examination shall be made to determine that preservation, packaging, packing and marking as required by section 5 of this specification are complied with. Defects shall be scored as specified below. The inspection level shall be L4 with an AQL of 6.5, expressed in terms of defects per hundred units. The sample unit shall be one shipping container fully prepared for delivery. The lot size shall be the number of containers offered for acceptance at one time.

Examine	*Defect*
Markings	Omitted; incorrect; illegible; or improper size, location, sequence, or method of application.
Materials	Any nonconforming component; component missing, damaged, or otherwise defective affecting serviceability.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping, inadequate stapling; bulging or distortion of containers.
Weight	Gross/net weight exceeds requirement.

4.4 Test.

4.4.1 The melting pot shall be subject to a light tap on the side to obtain a resonant ring. A flat nonresonant ring indicates an invisible crack and shall be cause for rejection."

Section 5, delete and substitute the following:

"5. PREPARATION FOR DELIVERY

Federal Standard No. 102 shall be referred to for definitions and application of the various levels of packaging and packing for civilian agency procurements.

5.1 Packaging. Packaging shall be level A or C as specified (see 6.1).

5.1.1 *Level A.* Each solder pot shall be packaged in a paperboard or fiberboard box conforming to Specification PPP–B–566, PPP–B–636, PPP–B–665, or PPP–B–676, except that the dimensional and weight limitations of the applicable box specification shall not be exceeded. Each solder pot shall be cushioned in such a manner as to prevent damage while in transit. Each box shall be closed in accordance with the appendix of the applicable box specification.

5.1.2 *Level C.* Solder pots shall be packaged in accordance with the industry's practice.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.1).

5.2.1 *Level A.* Solder pots of one size only, packaged as specified in 5.1, shall be packed in a snug-fitting, fiberboard shipping container conforming to class 2, V3c or V3s, style RSC of Specification PPP–B–636. Each shipping container shall be closed, waterproofed by means of tape and reinforced with flat steel strapping or tape banding in

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:10Z
Check the source to verify that this is the currentversion before use.

accordance with the appendix of the container specification. The weight of contents of each shipping container shall not exceed 65 pounds.

5.2.2 *Level B.* Solder pots of one size only, packaged as specified in 5.1, shall be packed in a snug-fitting, fiberboard shipping container conforming to type I or II, class 1, style RSC of Specification PPP–B–636, except that minimum bursting strength of the fiberboard shall be 200 p.s.i. All flaps of the fiberboard shipping container shall be securely sealed with an adhesive commercially used for the specific product being packed by application throughout the entire area of contact between the flaps or by a combination of metal stitching the bottom flaps and sealing the top flaps with adhesive. The weight of contents of each shipping container shall not exceed 65 pounds.

5.2.3 *Level C.* Solder pots, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with rules or regulations of carriers applicable to the mode of transportation.

5.3 Marking.

5.3.1 *Civilian agencies.* In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with Federal Standard No. 123.

5.3.2 *Military requirements.* In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with Standard MIL–STD–129."

Military Custodian:
Army—GL
Navy—Ships
Air Force—MOA **Project No. 5120–0392**

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:10Z
Check the source to verify that this is the currentversion before use.