RR-S-00630(GSA-FSS)
October 6, 1970

INTERIM FEDERAL SPECIFICATION

SPRAYER, LIGHT LIQUID, MANUALLY CARRIED, PRESSURIZED

This Interim Federal Specification was developed by the Standardization Division, Federal Supply Service, General Services Administration Washington, D. C., 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers one type of pressurized hand operated metal sprayer for fog and jet stream spraying of light liquids such as lubricants, solvents, water, insecticides, ink, mould release or other liquid having a viscosity not greater than SAE 10 W motor oil.

1.1.1 Federal specification coverage. Federal specifications do not include all varieties of the commodity as indicated by the title of the specification, or which are commercially available, but are intended to cover only those generally used by the Federal Government.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specification:

PPP-B-636 - Box, Fiberboard.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintended of Documents, U. S. Government Printing Office, Washington, D. C. 20402.

(Single copies of this specification and other Federal specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, D. C., Atlanta, Chicago, Kansas City, Mo., Forth Worth, Denver, San Francisco, Los Angeles, and Seattle, Washington.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

FSC 3740

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issues in effect on date of invitation for bids, or request for proposal shall apply.

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the National Motor Freight Traffic Association, Inc., Agent, 1616 P Street, N. W., Washington, D. C. 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Tariff Publishing Officer, Room 202 Union Station, 516 W. Jackson Blvd., Chicago, Illinois 60606.)

3. REQUIREMENTS

3.1 Material. All materials used in the fabrication of the sprayer shall be new and of the quality necessary to produce a sprayer to meet the requirements described herein, and shall be free from any defects or imperfections which might affect appearance or serviceability.

3.2 Design. Sprayers covered by this specification shall be the manufacturer's standard design and shall consist of a tank, nozzle, trigger, handle and a pneumatic tire type valve.

3.2.1 Capacity. Unless otherwise specified (see 6.2) the tank shall have a rated capacity of one quart liquid, plus adequate air chamber capacity.

3.2.2 Valve assembly. Sprayers shall be equipped with a valve assembly for the controlled release of pressure when the sprayer is in use. It shall have a self-closing feature incorporated in the valve assembly to prevent the loss of pressure when not in use.

3.2.3 Nozzle. Sprayers shall be provided with a single nozzle capable of releasing either a solid stream, or a spray or with two separate nozzles, one of which shall be capable of producing a solid stream, and the other for producing a spray (see 4.4.2.1 and 4.4.2.2).

3.2.4 Charging pressure valve. Sprayers shall be fitted with a pneumatic tire type valve to pressurize the tank. Pressure charging through the discharge nozzle is not acceptable.

3.2.5 Fill opening. The fill opening shall have a minimum inside diameter of 1/2 inch.

3.3 Construction. When soldering, welding, crimping, riveting or brazing is used in the frabrication of the sprayer, it shall be of high quality workmanship, free from sand, dirt, fins, sprues, scale, flux or other extraneous matter. The sprayer shall be assembled and finished in a thoroughly workmanlike manner to assure a sprayer free from leaks and of good quality and neat appearance. There shall be no evidence of leakage or deformation when tested in accordance with 4.4.3.

3.4 Performance. At the completion of all tests conducted to determine compliance with requirements herein, there shall be no evidence of damage or leakage to the sprayer or noticeable defects which may adversely affect safe usage or performance.

3.5 Interchangeability. Parts subject to wear shall be manufactured to such standards as will permit each manufacturer to replace or adjust worn parts without modification of the worn parts or sprayer.

3.6 Rough usage. The sprayer shall be capable of withstanding rough usage without adversely affecting its strength to withstand the working pressure and operating capability (see 4.4.1).

3.7 Finish. Exterior surfaces, other than those of corrosion resistant materials, shall be coated to resist corrosion by painting, or zinc, nickel or chrome plating. Painted surfaces shall be yellow.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

3.8 Rated pressure. Unless otherwise specified (see 6.2), the rated maximum operating pressure shall be 100 p.s.i. to discharge the entire contents of the sprayer in an efficient manner without repressurizing.

3.9 Instruction decal. An instruction decal shall be attached to the side of the sprayer tank and shall indicate the rated working pressure (see 3.8), maintenance of the sprayer and shall include the following statement: "NOT RECOMMENDED FOR FLAMMABLE OR TOXIC LIQUIDS." The decal shall not be affected in any manner by accidental spilling of any liquids while being refilled.

3.10 Marking. Each sprayer shall be plainly marked with the manufacturer's name or trademark of such known character that the source of manufacture may be readily determined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements, as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.1.1 Inspection of materials and components. In accordance with 4.1 above, the supplier is responsible for insuring that materials and components used were manufactured, tested and inspected in accordance with the requirements of referenced subsidiary specifications and standards to the extent specified herein, or if none, in accordance with this specification.

4.2 Sampling for inspection and acceptance. Sampling for inspection and acceptance shall be in accordance with the provisions of MIL-STD-105.

4.2.1 End item inspection. A lot shall consist of all sprayers of the same size and construction offered for inspection at one time. The sample unit shall be one sprayer.

4.3 Visual and dimensional examination. The completely assembled end item shall be examined for defects in finish, construction, workmanship, markings, and nonconformance with dimensional requirements. Defects shall be as classified in table I. The inspection level shall be level II with an acceptable quality level (AQL) of 2.5 percent for major defects and 6.5 percent for total defects, expressed in terms of defects per hundred units.

TABLE I. Classification of defects

Examination	Defects	Classification	
		Major	Minor
Construction and Workmanship	Any part missing.	X	
	Any part broken, fractured or cracked	X	
	Sharp edges.	X	
Welding	Weld omitted, not fused, broken or burnt through.	X	
Soldering	Solder omitted, not fused, spatter not removed.	X	
Crimping	Crimping not complete, not uniform.	X	
Punched or cut openings	Punched or cut hole oversize.	X	
	Openings off center.	X	
	Opening not punched or cut.	X	
Finish	Exterior surfaces other than corrosive resistant, not painted or plated.	X	
	Area of no paint or flaking.		X
	Contains lumps, blisters or sags.		X
	Not yellow.	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects (Con.)

Examination	Defects	Classification	
		Major	Minor
Charging	Valve missing.	X	
Pressure	Wrong type of valve.	X	
Valve, core and Cap	Valve stem missing.	X	
	Valve core missing.		X
	Valve cap missing.		X
Identification Marking	Missing, illegible, incomplete, incorrect, wrong size or location.		X

4.4 Test.

4.4.1 Abuse test. The fully charged and pressurized sprayer shall be dropped from its normal upright position a distance of three feet to a concrete floor without incurring any damage which would affect the satisfactory operation of the sprayer.

4.4.2 Jet test. The sprayer shall be filled 2/3 full of water and pressurized to 100 p.s.i. maximum. It shall be placed on a table so that the jet nozzle is in a horizontal position. Pressure shall be applied to the trigger for 5 seconds. The sprayer shall propel a pin stream a minimum of 20 feet from the nozzle.

4.4.2.2 Spray test. With the sprayer in the same position as in 4.4.2.1,a vertical target shall be set up 18 inches from the end of the spray nozzle. Pressure shall be applied to the trigger for 5 seconds. The spray pattern shall be a minimum of 6 inches in diameter.

4.4.3 Pressure test. Sprayers shall be tested by the hydrostatic method or by air pressure, at the option of the manufacturer. The sprayer shall be pressurized to 300 pounds minimum, then submerged for not less than ten seconds in a clear tank of water and checked for leaks. When removed from the tank, the sprayer shall be checked for any deformations which may have occurred in the sprayer during the holding period.

4.5 Inspection of preparation for delivery requirements. An inspection shall be made to determine that the packaging, packing, and marking comply with the requirements in section 5 of this specification. Defects shall be scored in accordance with table II. For examination of interior packaging, the sample unit shall be one shipping container fully prepared for delivery, selected at random just prior to the closing operations. Sampling shall be in accordance with MIL-STD-105. Defects of closure listed shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 with an AQL of 4.0 percent defects per hundred units.

TABLE II. Classification of preparation for delivery defects

Examine	Defects
Markings (exterior and interior)	Omitted; incorrect; illegible; improper size; location, sequence, or method of application.
Materials	Any component missing or damaged.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping, inadequate stapling. Distortion of container.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C, as specified (see 6.2).

5.1.1 Level A. Each sprayer shall be packaged in a close-fitting box conforming to PPP-B-636, class weather-resistant.

5.1.2 Level B. Each sprayer shall be packaged in a close-fitting box conforming to PPP-B-636, class domestic.

5.1.3 Level C. The sprayers shall be packaged to afford protection against corrosion and damage from the supplier to the initial destination.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

5.2.1 Level A. The sprayers in quantities, as specified (see 6.2), shall be packed in a close-fitting box conforming to PPP-B-636, class weather-resistant.

5.2.2 Level B. Twelve sprayers shall be packed in a fiberboard box conforming to PPP-B-636, class domestic, style optional.

5.2.3 Level C. The sprayers shall be packed to insure carrier acceptance and safe delivery at destination in containers complying with the requirements of the Uniform Classification Committee or the National Motor Freight Classification Rules, as applicable to the mode of transportation.

5.3 Marking.

5.3.1 Civil agencies. In addition to markings required by the contract or order, the interior packaging, and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.3.2 Military agencies. In addition to markings required by the contract order, the interior packaging, and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The sprayer covered by this specification is a general purpose sprayer. It is used in industry, agriculture, hospitals, schools, forestry, etc., where spraying of light liquids is required. IT IS NOT INTENDED FOR USE WITH TOXIC OR FLAMMABLE LIQUIDS.

6.2 Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

(a) Title, number, and date of specification.

(b) Capacity when different (see 3.2.1).

(c) Rated pressure when different (see 3.8).

(d) Quantity of unit packages required in shipping container (see 5.2.1).

(e) Selection of applicable levels of packaging and packing required (see 5.1 and 5.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

GENERAL SERVICES ADMINISTRATION - FEDERAL SUPPLY SERVICE

SPECIFICATION COMMENT SHEET

BUDGET BUREAU NO. 29-R0175

INSTRUCTIONS

This form provides a way for users of this specification to inform the originator of problems encountered in its use. It is not to be used to request changes to accommodate proprietary features. All comments will be considered and appreciated, but please do not expect a reply. To comment: detach, complete, and mail to: General Services Administration, FSS (FMSK), Wash., D.C. 20406.

NOTE: Comments on this form do not constitute or imply authorization to waive any part of the document or serve to amend contractual requirements.

1. SPECIFICATION

RR-S-00630(GSA-FSS) Sprayer, Light Liquid, Manually Carried, Pressurized

2. CONTRACT NO. *(If any)*	3. QUANTITY ON CONTRACT *(Optional)*	4. DOLLAR VALUE *(Optional)*

5. GENERAL NATURE OF PROBLEM *(e.g., inspection difficulties, manufacturers unable to meet tolerances, containers collapse under normal warehousing conditions, etc.)*

6. SPECIFIC REQUIREMENTS AFFECTED *(Include paragraph number and lines of wording)*

7. SPECIFIC PROBLEMS *(e.g. tests in 4.2.2 will not assure that the battery will last required time; temperature ranges in table 2 do not conform to commercially available items.)*

8. RECOMMENDATIONS

9. NAME OF MANUFACTURER, ASSOCIATION, GOVT., AGENCY, ETC.	10. ADDRESS *(Number, Street, City, State and Zip Code)*

11. NAME AND TITLE OF SUBMITTER	12. DATE

FORM GSA FEB 69 2200

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.