RR-S-700a
December 12, 1966

SUPERSEDING
Int. Fed. Spec. RR-S-00700 (GSA-FSS)
March 1, 1966

FEDERAL SPECIFICATION

STAND, TRASH AND GARBAGE CAN

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers one type of trash and garbage can stand.

1.2 Classification.

1.2.1 *Sizes.* The stand covered by this specification shall be of the following sizes, as specified (see 6.2):

A—For 24 gallon can.
B—For 32 gallon can.

2. APPLICABLE DOCUMENTS

2.1 The following specifications and standards, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

PPP-B-566—Boxes, Folding, Paperboard.
PPP-B-585—Boxes, Wood, Wirebound.
PPP-B-591—Boxes, Fiberboard, Wood-Cleated.
PPP-B-601—Boxes, Wood, Cleated-Plywood.
PPP-B-621—Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636—Box, Fiberboard.
PPP-B-640—Boxes, Fiberboard, Corrugated, Triple-Wall.
PPP-B-665—Boxes; Paperboard, Metal Stayed (Including Stay Material).
PPP-B-676—Boxes, Setup.

Federal Standard:

Fed. Std. No. 123—Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C. 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D. C., Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, and Seattle, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specification:

MIL-P-116—Preservation, Methods of.

Military Standards:

MIL-STD-105—Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129—Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials.

3.1.1 *Top ring, bottom bracket, and legs.*

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:
Check the source to verify that this is the current version before use.

The top ring, bottom bracket, and legs shall be made from carbon steel strip.

3.1.2 *Fasteners.* The bolts, nuts, and lockwashers shall be zinc or cadmium coated carbon steel.

3.1.3 *Chain or cordage.* When chain is used, it shall be made of zinc or cadmium coated carbon steel. When cord is used in lieu of chain, it shall be of nylon.

3.2 Design and construction.

3.2.1 *Sizes A and B.* Sizes A and B trash and garbage can holders shall be designed to hold a can above the ground and in an upright position. The stands shall consist of a top ring, a bottom bracket, and a minimum of 4 legs. All components shall be provided with holes for bolting assembly and shall be packaged in an unassembled condition.

3.2.2 *Top rim.* The top rim shall be of one piece welded construction and circular in shape. The rim shall be designed with holes equally spaced around the circumference for attaching the legs.

3.2.3 *Bottom bracket.* The bottom bracket shall be of one piece square or crisscross welded construction. The bottom bracket shall be designed with holes for attaching the legs and shall be the platform on which the trash or garbage can rests.

3.2.4 *Legs.* Each of the legs shall be provided with 2 holes, one for attaching the top rim, the other for attaching the bottom bracket. Each of the legs shall be pointed on one end, and shall be constructed with an offset so the holder may be anchored in the turf by exerting downward foot-pressure to the offsets.

3.2.5 *Fasteners.* The stand shall be assembled with bolts not less than 0.250 inch diameter, and 0.750 inch in length, with suitable nuts and lockwashers.

3.2.6 *Lid attachment.* A chain or cord not less than 3 feet in length shall be furnished for attaching the can top to the stand.

3.3 Protective coating. The top ring, bottom bracket, and legs shall be painted, zinc or cadmium coated at the option of the manufacturer.

3.4 Dimensions. The stands shall conform to the dimensions in table I.

TABLE I. *Dimensions (inches)*

	Size A	Size B
Thickness—top ring, bottom bracket, legs	1/8 min.—3/16 max.	1/8 min.—3/16 max.
Width, top ring and bottom bracket	1 min.	1 min.
Width—legs	5/8 min.—1 max.	5/8 min.—1 max.
Inside diameter—top ring	19 ± 1/2	21 ± 1/2
Height—overall	17-1/2 ± 1/2	19-3/4 ± 1/2
Distance—top of bottom bracket to top of stand	9-1/2 ± 1/2	10-3/4 ± 1/2
Length—pointed legs (feet)	5± 1	6 ± 1
Width—offset step (each leg)	1-1/2 min.	1-1/2 min.
Inside diameter—stand at bottom bracket	19 ± 1/2	21 ± 1/2
Distance—top of bottom bracket to ground line	3 ± 1/2	3 ± 1/2

3.5 Stability. When tested in accordance with 4.4.2, the sizes A and B stands shall support a trash or garbage can, in an upright position, without permanent deformation to any component of the stand.

3.6 Workmanship. Except for the pointed legs, the stands shall be free from sharp edges and projections. Surfaces shall be free from cracked or peeled plating or paint.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Govern-

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

ment reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling.

4.2.1 *Lot.* Unless otherwise specified (see 6.2), a lot shall consist of each size of stands submitted for inspection at the same time.

4.2.2 *Visual, dimensional, and workmanship of end item.* Stands shall be examined for these characteristics in accordance with level S-3 in MIL-STD-105.

4.2.3 *Sampling for tests.* Samples for tests shall be in accordance with level S-2.

4.3 Inspection.

4.3.1 *End item.* Stands shall be examined for defects listed in table II. The acceptable quality levels (AQL's) for defects listed in table II shall be 2.5 percent defective for major defects and 4.0 percent defective for minor defects.

TABLE II. *Classification of defects, end item*

Defects	Major	Minor
Size not as specified	X	
Dimensions not within tolerances	X	
Poor fit, when assembled	X	
Sharp edges and projections	X	
Surfaces not completely painted or plated	X	
Fasteners missing or not as specified	X	
Plated or painted surfaces, loose or scratched		X
Damage or defects not affecting function or serviceability		X
Damage or defects affecting function or serviceability	X	

4.3.2 *Inspection of preparation for delivery requirements.* An inspection shall be made to determine that the packaging, packing, and marking comply with the requirements in section 5. Defects shall be scored in accordance with table III. For examination of interior packaging, the sample unit shall be one shipping container fully prepared for delivery, selected at random just prior to the closing operation. Sampling shall be in accordance with MIL-STD-105. Defects of closure listed shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S2 with an AQL of 4.0 defects per hundred units.

TABLE III. *Classification of preparation for delivery defects*

Examine	Defects
Markings (exterior and interior)	Omitted; incorrect; illegible, improper size, location, sequence or method of application.
Materials	Any component missing or damaged.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping, inadequate stapling.
	Distortion of container.
Contents (exterior and interior container)	Number per container is more or less than required. Net weight exceeds requirements.

4.4 Tests.

4.4.1 *AQL.* The AQL for tests shall be 6.5 percent on the basis of percent defective.

4.4.2 *Stability.* Test shall be conducted by placing the stands on a level hard surface such as concrete or steel.

4.4.2.1 *Size A.* Place a can (24 gallon capacity) containing sand or similar material, weighing 60 ± 2 pounds in the stand for a minimum of 15 minutes, for conformance to requirements of 3.5.

4.4.2.2 *Size B.* Place a can (32 gallon capacity) containing sand or similar material, weighing 100 ± 2 pounds in the stand for a minimum of 15 minutes, for conformance to requirements of 3.5.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C, as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.

5.1.1 *Level* A. Each stand disassembled to the minimum cubage, with applicable parts shall be packaged in accordance with method III of MIL-P-116.

5.1.2 *Level B.* Each stand disassembled to the minimum cubage, with applicable parts shall be packaged in a close-fitting box conforming to PPP-B-566, PPP-B-665, PPP-B-676, or PPP-B-636.

5.1.3 *Level C.* The stands shall be packaged in accordance with the supplier's commercial practice.

5.2 **Packing.** Packing shall be level A, B, or C, as specified (see 6.2).

5.2.1 *Level A.* Stands of like description shall be packed in close-fitting boxes conforming to PPP-B-585, class 3; PPP-B-591, class II; PPP-B-601, overseas type; PPP-B-621, class 2; PPP-B-636, class weather resistant; or PPP-B-640, class 2, grade A. The boxes shall be closed and strapped in accordance with the applicable specification or appendix thereto. The gross weight of the triple-wall fiberboard box and the wood boxes shall not exceed approximately 200 pounds. The gross weight of the PPP-B-636 fiberboard box shall not exceed the weight limitations of the box specification.

5.2.2 *Level B.* Six unit packages of stands of like description shall be packed in a close-fitting box conforming to PPP-B-636, class domestic. The box shall be closed in accordance with the appendix to the box specification.

5.2.3 *Level C.* The stands shall be packed to insure carrier acceptance and safe delivery at destination in containers complying with the rules and regulations applicable to the mode of transportation.

5.3 **Standard pack (civil agency procurements).** The standard pack for civil agency procurements shall be as specified in 5.1.2 and 5.2.2.

5.4 **Marking.**

5.4.1 *Civil agencies.* In addition to markings required by the contract or order, the packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.4.2 *Military agencies.* In addition to markings required by the contract or order, the packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 **Intended use.** Stands covered by this specification are intended to be used for keeping trash and garbage cans off the ground, in an upright position, thus preventing tipping and wind damage.

6.2 **Ordering data.** Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(*a*) Title, number, and date of this specification.
(*b*) Size required (see 1.2).
(*c*) Size of lot, if different from 4.2.1.
(*d*) Selection of applicable levels of packaging and packing required (see 5.1 and 5.2).

MILITARY CUSTODIANS:

Army—GL
Navy—Docks
Air Force—69

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:11Z
Check the source to verify that this is the current version before use.