INCH-POUND

MIL-C-24640A
SUPPLEMENT 1
26 June 1995

MILITARY SPECIFICATION

CABLES, LIGHT WEIGHT, ELECTRIC, LOW SMOKE, FOR SHIPBOARD USE
GENERAL SPECIFICATION FOR

This supplement forms a part of MIL-C-24640A, dated 26 June 1995.

SPECIFICATION SHEETS

MIL-C-24640/1 - CABLE, ELECTRIC, 600 VOLTS, LIGHT WEIGHT, TWO CONDUCTOR, POWER, TYPE DX (INCLUDING VARIATION TYPE DXA)
MIL-C-24640/2 - CABLE, ELECTRIC, 600 VOLTS, LIGHT WEIGHT, THREE CONDUCTOR, POWER, TYPE TX (INCLUDING VARIATION TYPE TXA)
MIL-C-24640/3 - CABLE, ELECTRIC, 600 VOLTS, LIGHT WEIGHT, FOUR CONDUCTOR, POWER, TYPE FX (INCLUDING VARIATION TYPE FXA)
MIL-C-24640/4 - CABLE, ELECTRIC, 600 VOLTS, LIGHT WEIGHT, MULTI PAIR AWG 20, TYPE TTX (INCLUDING VARIATION TYPE TTXA)
MIL-C-24640/5 - CABLE, ELECTRIC, 600 VOLTS, LIGHT WEIGHT, MULTI PAIR AWG 20, TYPE TTXS (INCLUDING VARIATION TYPE TTXSA AND TTXSO)
MIL-C-24640/6 - CABLE, ELECTRIC, 600 VOLTS, LIGHT WEIGHT, MULTI PAIR AWG 22, TYPE 2XAO
MIL-C-24640/7 - CABLE, ELECTRIC, 600 VOLTS, LIGHT WEIGHT, MULTI-CONDUCTOR, AWG 22, TYPE 1XMSO
MIL-C-24640/8 - CABLE, ELECTRIC, 600 VOLTS, LIGHT WEIGHT, MULTI-CONDUCTOR, AWG 20, TYPE MXO
MIL-C-24640/9 - CABLE, ELECTRIC, 600 VOLTS, LIGHT WEIGHT, MULTI PAIR, AWG 22, TYPE 2XS (INCLUDING VARIATION TYPE 2XSA AND 2XSO)
MIL-C-24640/10 - CABLE, ELECTRIC, 600 VOLTS, LIGHT WEIGHT, MULTI-CONDUCTOR, AWG 22, TYPE MXSO
MIL-C-24640/11 - CABLE, ELECTRIC, 600 VOLTS, LIGHT WEIGHT, MULTI TRIAD AWG 18, TYPE 3XS (INCLUDING VARIATION TYPE 3XSA)
MIL-C-24640/12 - CABLE, ELECTRIC, 600 VOLTS, LIGHT WEIGHT, MULTI PAIR AWG 26, TYPE 2XO
MIL-C-24640/13 - CABLE, ELECTRIC, 600 VOLTS, LIGHT WEIGHT, MULTI PAIR AWG 26, TYPE 2XSX0
MIL-C-24640/14 - CABLE, ELECTRIC, 600 VOLTS, LIGHT WEIGHT, MULTI-CONDUCTOR, AWG 22, TYPE 1XSOW

AMSC N/A FSC 6145
DISTRIBUTION STATEMENT A. Approved for public release; distribution unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T23:39Z
Check the source to verify that this is the current version before use.

MIL-C-24640/15 - CABLE, ELECTRIC, 600 VOLTS, LIGHT WEIGHT, MULTI-PAIR, AWG 22, TYPE 2XSAW (INCLUDING VARIATION TYPES 2XSAOW AND 2XSAWA)
MIL-C-24640/16 - CABLE, ELECTRIC, 600 VOLTS, LIGHT WEIGHT, MULTI-PAIR, AWG 18, TYPE 2XSW (INCLUDING VARIATION TYPES 2XSOW AND 2XSWA)
MIL-C-24640/17 - CABLE, ELECTRIC, 600 VOLTS, LIGHT WEIGHT, MULTI-PAIR, AWG 26, TYPE 2XOW
MIL-C-24640/18 - CABLE, ELECTRIC, 600 VOLTS, LIGHT WEIGHT, MULTI-TRIAD, AWG 18, TYPE 3XSW (INCLUDING VARIATION TYPES 3XSOW AND 3XSWA)
MIL-C-24640/19 - CABLE, ELECTRIC, 600 VOLTS, LIGHT WEIGHT, TWO CONDUCTOR, POWER, TYPE DXW (INCLUDING VARIATION TYPES DXOW AND DXWA)
MIL-C-24640/20 - CABLE, ELECTRIC, 600 VOLTS, LIGHT WEIGHT, THREE CONDUCTOR, POWER, TYPE TXW (INCLUDING VARIATION TYPES TXOW AND TXWA)
MIL-C-24640/21 - CABLE, ELECTRIC, 600 VOLTS, LIGHT WEIGHT, FOUR CONDUCTOR, POWER, TYPE FXW (INCLUDING VARIATION TYPES FXOW AND FXWA)
MIL-C-24640/22 - CABLE, ELECTRIC, 600 VOLTS, LIGHT WEIGHT, SEVEN CONDUCTOR, POWER, TYPE 7XW (INCLUDING VARIATION TYPE 7XWA)
MIL-C-24640/23 - CABLE, ELECTRIC, 600 VOLTS, LIGHT WEIGHT, MULTI-CONDUCTOR, AWG 18, TYPE MXCW (INCLUDING VARIATION TYPES MXCOW AND MXCWA)
MIL-C-24640/24 - CABLE, ELECTRIC, 600 VOLTS, LIGHT WEIGHT, MULTI-PAIR, AWG 22, TYPE TTXW (INCLUDING VARIATION TYPES TTXOW AND TTXWA)

Preparing activity:
Navy - SH

Agent
DLA-IS

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T23:39Z
Check the source to verify that this is the current version before use.