INCH-POUND
MIL-DTL-24640B
SUPPLEMENT 1A
9 October 2008

DETAIL SPECIFICATION

CABLES, LIGHT-WEIGHT, ELECTRIC, LOW SMOKE, FOR SHIPBOARD USE,
GENERAL SPECIFICATION FOR

This supplement forms a part of MIL-DTL-24640B, dated 22 August 2002.

SPECIFICATION SHEETS

MIL-DTL-24640/1	-	Cable, Electric, 600 Volts, Light-Weight, Two-Conductor, Low Power, Type DX
MIL-DTL-24640/2	-	Cable, Electrical, 600 Volts, Light-Weight, Three-Conductor, Low Power, Type TX
MIL-DTL-24640/3	-	Cable, Electric, 600 Volts, Light-Weight, Four-Conductor, Low Power, Type FX
MIL-DTL-24640/4	-	Cable, Electric, 600 Volts, Light-Weight, Multi-Pair, AWG 20, Type TTX
MIL-DTL-24640/5	-	Cable, Electric, 600 Volts, Light-Weight, Multi-Pair, AWG 20, Type TTXS (Including Variation Type TTXSO)
MIL-DTL-24640/6	-	Cable, Electric, 600 Volts, Light-Weight, Multi-Pair, AWG 22, Type 2XAO
MIL-DTL-24640/7	-	Cable, Electric, 600 Volts, Light-Weight, Multi-Conductor, AWG 22, Type 1XMSO
MIL-DTL-24640/8	-	Cable, Electric, 600 Volts, Light-Weight, Multi-Conductor, AWG 20, Type MXO
MIL-DTL-24640/9	-	Cable, Electric, 600 Volts, Light-Weight, Multi-Pair, AWG 22, Type 2XS (Including Variation Type 2XSO)
MIL-DTL-24640/10	-	Cable, Electric, 600 Volts, Light-Weight, Multi-Conductor, AWG 16, Type MXSO AND MXSOW
MIL-DTL-24640/11	-	Cable, Electric, 600 Volts, Light-Weight, Multi-Triad, AWG 18, Type 3XS
MIL-DTL-24640/12	-	Cable, Electric, 600 Volts, Light-Weight, Multi-Pair AWG 26, Type 2X0
MIL-DTL-24640/13	-	Cable, Electric, 600 Volts, Light-Weight, Multi-Pair, AWG 26, Type 2XSX0
MIL-DTL-24640/14	-	Cable, Electric, 600 Volts, Light-Weight, Multi-Conductor, AWG 22, Type 1XSOW
MIL-DTL-24640/15	-	Cable, Electric, 600 volts, Light-Weight, Multi-Pair, AWG 22, Type 2XSAW (Including Variation Type 2XSAOW)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T23:38Z
Check the source to verify that this is the current version before use.

MIL-DTL-24640/16	-	Cable, Electric, 600 Volts, Light-Weight, Multi-Pair, AWG 18, Type 2XSW (Including Variation Type 2XSOW)
MIL-DTL-24640/17	-	Cable, Electric, 600 Volts, Light-Weight, Multi-Pair, AWG 26, Type 2XOW
MIL-DTL-24640/18	-	Cable, Electric, 600 Volts, Light-Weight, Multi-Triad, AWG 18, Type 3XSW (Including Variation Type 3XSOW)
MIL-DTL-24640/19	-	Cable, Electric, 600 Volts, Light-Weight, Two-Conductor, Power, Type DXW (Including Variation Type DXOW)
MIL-DTL-24640/20	-	Cable, Electric, 600 Volts, Light-Weight, Three-Conductor, Low Power, Type TXW (Including Variation Type TXOW)
MIL-DTL-24640/21	-	Cable, Electric, 600 Volts, Light-Weight, Four-Conductor, Low Power, Type FXW (Including Variation Type FXOW)
MIL-DTL-24640/22	-	Cable, Electric, 600 Volts, Light-Weight, Seven-Conductor, Low Power, Type 7XW
MIL-DTL-24640/23	-	Cable, Electric, 600 Volts, Light-Weight, Multi-Conductor, AWG 18, Type MXCW (Including Variation Type MXCOW)
MIL-DTL-24640/24	-	Cable, Electric, 600 Volts, Light-Weight, Multi-Pair, AWG 22, Type TTXW (Including Variation Type TTXOW)
MIL-DTL-24640/25	-	Cable, Electrical, -20 °C to + 125 °C, 600 Volts, Type 9XS
MIL-DTL-24640/26	-	Cable, Electrical, -20 °C to + 125 °C, 600 Volts, Type 5XO

Custodians:
Army – MI
Navy – SH

Preparing Activity:
Navy – SH

Review Activities:
Army – AR, AV, CR, CR4
Navy – CG, EC

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T23:38Z
Check the source to verify that this is the current version before use.